

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

Section Corner to Secs. 19 & 30, T30-6W. & Secs. 24 & 25, T30-7W. ¹⁵⁴
Found - Orig. 18", now 40" Pine S.60°W. 46.2 ft., shows good scar.
Orig. 12", now 30" Pine N.48°E. 81.8 ft., previously opened,
shows good scribing.

No other Orig. BT's. found.

Also find 1" I. Pipe at Corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office 1963

R7W $\frac{S24}{S25}$ | $\frac{S19}{S30}$ R6W T30S

New BT's: 25" Pine bears S.40°E. 24.0 ft. scribed S30 T30S R6

Note - We find 18" Pine N.84°W. 49.7 ft., shows good scribing, See
Cor. Ren. No. 5, T30-7W.

J.H. Markham's axe he used to open the N.E. BT. couldn't
have been very sharp.

*Fd. OK 5/6/91
DC50
C.S. 64/15*

$\frac{1}{2}$ Section Corner to Sec. 19; T30-6W. & Sec. 24, T30-7W. ¹⁵⁵
Found - Mound of Stone & Stake at Corner.
Orig. 6", now 24" Cedar North 20°E. 83.2 ft., prev, opnd. good scbng.
Original N.W. BT., down & mostly rotted.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963

$\frac{1}{2}$ S24/S19 T30S
R7W R6W

New BT's: 10" R. Fir bears N. 7° W. 14.0 ft. scribed $\frac{1}{2}$ S24 CS BT.

12" Cedar bears S:81°E. 19.4 ft. scribed $\frac{1}{2}$ S19 CS BT.

Note - Corner is under 18" Cedar Log.

James W. Byron, Deputy County Surveyor
Mike Darby and Jim Halterman
November & December 1963
C. S. File No. 53/40

N. W. Corner D. L. C. No. 49. ¹⁵⁶
Found - Brass Cap at Corner, See Ren. No. 69. ²⁰³
Also now 14" Fir N.72 $\frac{1}{2}$ °E. 17.0 ft., shows good scars.
West Bearing Tree down.
New BT: 6" Laurel bears S.66°W. 10.5 ft. scribed NW DLC 49 CS BT.

Section Corner to Secs. 21 - 22 - 27 - 28. ¹⁵⁷
Found - All Orig. BT's.-Orig. 6", now down 12" Oak, open & find gd. scrbng.
Orig. N. E. & N. W. BT's. standing, old faces rotted
Orig. S.W. BT., down & mostly rotted.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963 ²³⁴
New BT's: 10" W. Oak bears S. 59°W. 27.5 ft. scribed S28 T30S R6W CS BT.
6" Laurel bears S.16°E. 23.7 ft. scribed S27 CS BT.
Rescribe - 22" W.O. N.39°E. 12.8 ft. S22 T30S R6W CS BT.
36" W.O. N.43°W. 37.0 ft. S21 T30S R6W CS BT.
Note - Fence Corner at N. W. Bearing Trees.

$\frac{1}{4}$ Corner to Sections 18 and 19. ¹⁵⁸
Found - Bearing Trees as recorded & Stake at Corner. See Ren. No. 85.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963 $\frac{1}{4}$ $\frac{S18}{S19}$ T30S R6W
No New Bearing Trees Marked.

$\frac{1}{4}$ Corner to Sections 21 and 22. ¹⁵⁹
Found - Orig. 5", now 8" B. Oak, weopen & find good reverse scribing.
Original S. W. Bearing Tree not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963 ²⁴⁵
New BT's: 8" R. Fir bears S.26°W. 11.2 ft. scribed $\frac{1}{4}$ S21 CS BT.
14" R. Fir bears S.20°E. 26.0 ft. scribed $\frac{1}{4}$ S22 CS BT.
Note - Fence to North & East.

$\frac{1}{4}$ Corner to Sections 3 and 10. ¹⁶⁰
Found - $\frac{3}{4}$ " I. Shaft & 1' below surface covered by Fire Trail Const.
Set - Brass Cap alongside & Mkd: County Surveyor's $\frac{1}{4}$ $\frac{S3}{S10}$ T30S R6W
N.E. BT. alive. All other BT's. dead, See Ren. No. 101.
No trees near for Bearing Trees.