

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 6 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

206

S. ^E Corner D. L. C. No. 43.

Found - No trace of Iron Pipe, buried in edge of skid road, under large down tree, Ren. #9.

16", now 18" B.Oak, N.27°W. 27.7 ft., scribe visible "43 R6W" & other marks, burnt face.

18" B. Oak, now stump, S. 54° E. 26.7 ft., shows scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 6 W
Office, 1970 S E

DLC 43/

New BT's: 10" Laurel N.10°W. 21.6 ft. scribed "S E C 43 CS BT".
(N-S Wire Fence imbeded in BT)

6" D.Fir S.14°E. 51.2 ft. scribed "S E DLC 43 CS BT".

Brass Cap set 1.0 ft. north of corner point due to down & buried log.
12/8/70

207

1/4 Corner to Sections 24 and 25.

Found - No trace of 1" Iron Pipe. Falls in skid road, See. Ren.#27.

12" D.Fir, now stump, S.51°W. 47.5 ft., opened for scribe "BT".

12", now 23" B.Oak, N.89°W. 26.5 ft., shows scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 6 W
Office 1970 1/4 S 24
S 25

New BT; 8" D.Fir S.20°E. 44.4 ft. scribed "1/4 S25 CS BT".

11/25/70

208

Section Corner to Sections 15 - 16 - 21 - 22.


Found - Scribing for Renewal BT's., See Ren. No. 81 & 162, destroyed and iron pipe removed.

The Ash used by J. H. Markham to locate the Sec. Cor. was not of record. It does show old axe work & very old scribe marks.

Orig. 6", now 12" B.Oak, S.28°W. 120.9 ft., opened for scribe "21".

No trace of other Orig. BT. The Black Oak used on this date to monument the corner checks record in all respects. Also tie from old Nickel Mountain Road traverse checks within a few feet of present corner location.

Tie from Brass Cap to Iron Pipe in Ren. #81.



Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 6 W
Office 1970 S 16 | S 15
S 21 | S 22

New BT's: 7" W. Oak N. 9°W. 55.0 ft. scribed "T30S R6W S16 CS BT".

19" W. Oak N.42°E. 36.5 ft. scribed "T30S R6W S15 CS BT".

10" W.Oak S.77 1/2°W. 12.7 ft. scribed "T30S R6W S21 CS BT".

8" B.Oak S.70°E. 21.0 ft. scribed "T30S R6W S22 CS BT".

12/8/70

209

1/4 Corner to Sections 16 and 21.

Set by Survey by proportionate measurement.

Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 6 W
Office 1971 1/4 S 16
S 21

New BT's: 30" D.Fir N.59°E. 22.3 ft. mkd: "1/4 S16 CS BT".

48" D.Fir S.45°E. 42.6 ft. mkd: "1/4 S21 CS BT".

1/7/71

210

East 1/16 btwn. Sections 16 and 21.

Set Brass Cap by proportionate measurement: County Surveyor T30S R6W
Office 1971 E 1/16 S 16
S 21

New BT's: 16" Maple N.40°E. 24.9 ft mkd: E 1/16 S16 CS BT.

28" D.Fir S. 5°E. 34.0 ft. mkd: E 1/16 S21 CS BT.

This corner lies on westerly side of draw running S.E. about 10 ft.
East to bottom of draw.

1/7/71

John M. Powell
Willie Penley & J. Heritage
C.S. File No. 53/40

James W. Byron, County Surveyor
John M. Powell & Crew
C. S. File No. 54/120