

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 T. S. R 6 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

228

C O N T. - - - - -

Douglas County Surveyors Office
Gary Langlitz, Party Chief
L.E. Monrean; Karen Reed; Peter Earle
June 4, 1979
RM 3 - 26 C.S. file 61/3

New BT's - A D. Fir, 17" scribed "T31S R6W S1 CS BT" on a double blaze (oriented N.24°E.) bears S.70°W., 61.4 ft.
A 10" Maple scribed "T30S R6W S36 CS BT" on a double blaze (oriented West) bears N.45°W., 14.1 ft.
A 20" D.Fir scribed "T30S S36 CS BT" on a double blaze (oriented S.14°E.) bears N.49°W., 66.8 ft.
A 12" D.Fir scribed "T30S R6W S36 CS BT" on a double blaze bears N.74 1/2°W., 83.6 ft.
A 28" D.Fir scribed "T31S R5W S6 CS BT" on a double blaze bears S.52 1/2°E., 32.1 ft.
Found - From Wenderoth's I.P. Ren. #43, we find the following BT's:
A 26" Fir, now a 20" rotted stump with no marks visible on open double blaze bears N.81 1/2°E., 16.7 ft. (Rec. N.81°28'E., 16.0 ft.)
An 8" now 12" I.Cedar, alive with well healed double blaze bears S.5 1/2°E., 41.6 ft. (Rec. S.5°35'E., 41.6 ft.)
An 18" Fir now an 18" stump with scribing "5 CS S36 BT" visible on an open double blaze bears N.27°W., 26.6 ft. (rec. N.26°53'W., 26.6 ft.)
A 26" now 28" D.Fir alive with well healed double blaze bears S.80°W., 44.5 ft. (Rec. S.80°00'W., 44.5 ft.)
Bearing trees marked by J.W. Byron, 1963, Ren. #142 referencing monument set by Wenderoth:
A 14" Maple alive with well healed single blaze bears North 37.6 ft
A 6" now 10" D. Fir alive with well healed double blaze bears N.70°E., 30.9 ft.
We chop out and destroy entirely all markings found on Wenderoth's 1946 bearing trees and on Byrons 1963 BT's. We leave the I.P. set by Wenderoth at its found location.

6/4/79

229

1/4 Corner for Sec. 36; and Sec. 31 of T.30-5
Found - A 3/4" I.P. as per C.S. 38/118, Ren. 41 Pipe set aby Wenderoth in 1946 survey and renewed by Bryon in 1963. Ren. #143
We find this corner to have been set by improper procedure. See narrative in C.S. 39/118.
Do not find original post.
BT's - Original bearing trees not found.
A 14" B. Oak, now 18" bears N.53°E., 54.8 ft. dist. (Rec. 54.4 ft.) with well healed blaze. We open to find a visible "1/4" scribe. Ren. #41.
A 36" B. Oak, now 40" diam. stump, bears S.49°W., 38.8 ft. to face and 40.5 ft. dist. to center. Ren. #41
A 16" R. Fir now a 19" diam. snag bears S.8°W., 10.4 ft. dist. with a healed over double blaze. We open to find visible "1/4" S36 CS BT" scribing. Ren. #143
WE DESTROY ALL SCRIBING.
Set - A 1" x 36" I.P. with brass cap marked "Douglas County Surveyor" T30S R6W 1/4 S36 S31 R5W 1979" at proper single proportioned distance determined by our 1979 survey.
Corner falls on moderate southeast slope. Wenderoth's 3/4" I.P. bears S.38°31'27"W., 25.08 ft. dist. from brass crp.
New BT's - A 10" D. Fir scribed "1/4 S36 CS BT" in a double blaze bears N.65°W., 25.9 ft. dist.
A 9" D. Fir scribed "1/4 S36 CS BT" in a double blaze bears S.52°W. 64.4 ft. dist.
A 9" D. Fir scribed "1/4 S31 CS BT" in a double blaze bears S.84°E., 33.9 ft. dist.
A 10" D. Fir bears N.52°E., 39.4 ft. dist. scribed "1/4 S31 CS BT" in a double blaze.

6/13/79

230

1/4 Corner for Sec. 36; and Sec. 1 of T.31-6
Note - A careful search of the area reveals no trace of the original corner monument or accessories. We therefore proceed to determine a survey location by single proportionate measurement.
Found - From our 1979 survey location, a 1/4" I.P. set by Wenderoth in 1946 (Ren. #42 and C.S. 39/118) bears N.43°33'55" W., 16.50 ft. Wenderoth's 3/4" I.P. was set along the west side of the stump of a fir tree which was marked as the corner tree by Cain in 1919. (Ren. #8). Neither Cain nor Wenderoth specifically describe the old bearing trees that they allegedly found and we cannot

FD. 3/86
DOMBENTZ
M 101-1

RE-FILED
#239