

Douglas County Surveyor's Record of  
Government Corners Renewed

T 30 T. S. R 6 R. W. W. M.

MOORE-CHAPMAN CO., EUGENE, ORE. 21881

230

C O N T - - - - -

find conclusive evidence of the remains of the origi. BTs. The area around this corner is basically undisturbed except for scattered cutting of Fir and Oak trees. We do not accept the corner position adopted by Cain and Wenderoth.

Set - At our 1979 survey location, we set a 1" x 36" I.P. 3/4" in the ground with brass cap a-tached marked: "Douglas County Surveyors' T30S R6W 1/4 S36 S1 T31S 1979.

and mark the following bearing trees: (Note: During the month of May, 1979 we set a monument and marked new bearing trees for this corner position which relied on a double proportionate measurement position for the township corner located approx. one-half mile east of the location. Additional investigation at the township corner led to the discovery of the original corner. This causes our earlier position for the 1/4 corner to be wrong and also causes the blazes on some of the newly marked bearing trees not to face the correct corner location. The direction of the blazes will be noted with the descriptions of the new BTs:

- A 16" D. Fir, scribed "1/4 S1 CS BT" on a double blaze which faces N.35°E., bears West 26.1 ft.
- A 10" Madrone, scribed "1/4 S36 CS BT" on a double blaze which faces the corner correctly bears N.66 1/2°W., 45.3 ft.
- A 12" D. Fir, scribed "1/4 S36 CS BT" on a double blaze which faces S.65°W., bears N.40°E., 32.0 ft.
- An 18" D. Fir, scribed "1/4 S1 CS BT" on a double blaze which faces N.20°W., bears S.8°E., 34.6 ft.

We return to the corner position of Cain and Wenderoth and find the following:

- A 12" Fir, now a 22" stump established as a corner tree by Cain in 1919 with a 3/4" I.P. set along the west side of Cain's corner tree by Wenderoth in 1946. No marks were found on Cain's corner tree.
- A 16" B. Oak, now a 17" snag with faint illegible scribing visible on unhealed upper blaze, bears S.7°E., 52.1 ft. (Rec. S.5 1/4°E. 52.1 ft.) Ren. #8
- A 22" B. Oak, now a 24" stump, no marks found, bears N.72 1/2°E. 18.5 ft. (Ren. #8)
- 14" D. Fir, now an 18" stump with healed double blaze bears N.33°17'W., 11.2 ft. Ren. #42
- A 10" now 18" I. Cedar, with well healed double blaze bears S.43°04'W., 26.6 ft. (Rec. S.43°04'W., 25.9 ft.)
- A bearing tree marked by Byron in 1963 Ren. #169, a 12" now 17" D. Fir with healed double blaze bears N.28°W., 17.9 ft.

Note: We completely destroy all markings on the bearing trees associated with the corner position of Cain and Wenderoth. Wenderoth's 3/4" I.P. is left in place alongside Cain's corner tree which is also located at the corner of fences running north and east.

-/13/79

Section Corner for Secs. 26, 27, 34 and 35.

231

- Set - Brass cap
- BT's - A 6" Plum tree bears N.53°E., 460.5 ft. scribed "T30S R6W S26 BT" a double face.
- A 34" Pine bears S.78°E., 541.5 ft. scribed "T30S R6W S35 BT" on a double face.
- A 6" Plum bears S.60°W., 188.5 ft. scribed "T30S R6W S34 BT" on a double face.
- A 6" Plum bears N.60°W., 61.4 ft. scribed "T30S R6W S27 BT" on a double face.

1/4 Corner for Secs. 26 and 35.

232

- Set - Brass cap
- BT's - A 15" D. Fir bears N.15°W., 98.3 ft. scribed "1/4 S26 BT" on a double face.
- A 10" Oak bears S.84°E., 190.3 ft. scribed "1/4 S35 BT" on a double face.

Douglas County Surveyors Office  
Gary Langlitz  
L.E. Monrean; Karen Reed; S. Flauser; F. Silagy  
June 1979  
RM 3 - 26 C.S. 61/3

George Grubb  
For: Ralph Huffman  
March 1980  
M 79 - 34

FOOK BY  
Raymond Brown  
5/94  
Bodine / Lamphear  
1994-52

RE-RENEWED. SEE CORNER NO. 239