

Douglas County Surveyor's Record of
Government Corners Renewed

T 30

T. S.

R 6

R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 21881

cont.

249

Doug. Co. Surveyors
R. Smith; S. Flause
T. Franssen
April, 24, 1991
C.S. 64/13

18" dia. Ash double blazed and scribed "T30S R6W S28 CS BT"
on southeasterly trunk, bears N.26°W., 42.4 ft. to center of
scribed trunk at base.

No reasonable trees to the south.

4/24/91

Section Corner for Secs. 18 and 19; and 13 & 24 of T.30-7

Found - A 3½" dia. 1973 BLM brass cap on a 2¼" O.D. iron pipe
protruding 12" above ground.

250

23" now 38" dia. 40 ft. high dead B.Oak snag with an opened
blaze marks "S" visible bears N.76°E., 48.0 ft. (Rec.
N.70°E., 46.2 ft.) Orig. BT.

15" now 36" dia. 12" high B.Oak stump with possible lower blaze,
bears S.47°E. 79.6 ft. (Rec. S.50°E., 80.5 ft. dist. is a
slope measurement) Orig. BT.

24" now 48" dia. 4 ft. high B.Oak stump with a "V" open rotted
blaze bears S.62°W., 215.8 ft. (Rec. S.60°W., 215.8ft.) Orig.

25" now 26" dia. Ponderosa Pine with partially healed double
blaze illegible scribing visible, bears N.51°W., 3.6 ft.

(agrees with record) Ren. No. 130

20" now 19" dia. 17 ft. high Ponderosa Pine snag with partially
healed double blaze, illegible scribe marks visible bears
S.29½°W., 55.8 ft. (Rec. S.28°W., 58.0 ft. dist. is a slope
measurement) Ren. No. 130

NE BT from Ren. No. 130 is gone.

New BTs - 5" dia. D. fir double blazed and scribed "T30S R7W. S24 CS BT"
bears S.45½°W., 11.7 ft.

5" dia. D. fir, double blazed and scribed "T30S R6W S18 CS BT"
bears N.40°E., 9.0 ft.

5" dia. D. fir double blazed and scribed "T30S R6W S19 CS BT"
bears S.66½°E., 52.2 ft.

5/3/91

251

N. W. Corner D.L.C. #49

Found - A 2½" dia. 1969 County brass cap on a 1 3/8" O.D. iron pipe firmly
set, leaning approx. 0.35 ft southwesterly from plumb and
protruding 12" above ground. Ren. #203, 156 and 69

The BC/IP monument described in Ren. #69 (1953) is found loose
on ground surface 4 ft. southwest from above found monument.

I.P. is broken, remaining pipe and BC measures approx. 12" long.

(Accessories are checked from plumb position of BC monument.)

(No evidence of original BTs remains, same trees Ren. #1; Cole, 1915)

Found - 12" Fir now burned fir bark and roots in a stumphole bears West
30.0 ft. dist. as per record. Ren. #69

NE BT removed by road work (from Ren. #69)

(No BTs described as new in Ren. #156, Byron, 1963, are found)

38" W.Oak now a 39" DBH B.Oak with the scribing "C49" visible
in a partially healed double blaze bears South 171.8 ft. dist.
as per record. (Ren. #203, Powell, 1969)

42" W.Oak now a 44" DBH B.Oak with a fully healed double blaze
bears N.83½°E., 124.0 ft. dist. as per rec. Ren. No. 203.

Set - Found monument from Ren. No. 203 (1969) is returned to plumb
position. Broken monument from Ren. No. 69 (1953) is deposited
on west edge of above monument.

New BTs - An 8" DBH Madrone scribed NW DLC 49 CS BT on a double blaze
bears S.61°E., 41.2 ft. distant.

A 10" DBH Jeffrey Pine scribed NW DLC 49 CS BT on a double blaze
bears S.30°E., 33.6 ft. distant.

In scrub area northwest from open pastures.

4/29/91

Douglas County
Surveyors Office
Randall Smith, deputy
Wit: Stephen Flause
Hilary Simmons
John Pike
May 3, 1991
C.S. 64/15

Douglas County
Surveyors Office
Stephen Flause
T.R. Franssen
April 29, 1991
C.S. 64/15

cont. next page