

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T. 30 S. T. S. R. 6 W. R. W. W. M.

FOKE-CHAPMAN CO., EUGENE, ORE. 97101

Mark Smalley  
For: Roseburg Resources  
May-July 1992  
M 112 - 52

1/4 Corner for Section 31 and Section 36 of T.30-7. 255  
Set - 5/8" x 48" iron rod and alum. cap.  
New Accessories -  
9" madrone bears N.41°W., 22.8 ft. scribed "1/4 S36 BT"  
18" Pine bears S.88°E., 56.5 ft. scribed "1/4 S31 BT"  
18" Pine bears N.81°W., 45.2 ft. scribed "1/4 S36 BT"  
7" Pine bears N.06°E., 13.3 ft. scribed "1/4 S BT"  
----- 7/92 -----

Center 1/4 for Section 31. 256  
Set - 2" Brass Tablet in rock.  
New Accessories -  
5" Oak bears S.62°E., 13.6 ft. scribed "C $\frac{1}{4}$  S31 BT"  
7" Oak bears N.63°E., 8.3 ft. scribed "C $\frac{1}{4}$  S31 BT"  
6" Oak bears N.37°W., 21.8 ft. scribed "C $\frac{1}{4}$  S BT"  
6" Oak bears N.24°E., 21.2 ft. scribed "C $\frac{1}{4}$  S BT"  
----- 7/92 -----

1/4 Corner for Section 31 and Section 6 of T.31-6. 257  
Found BT's -  
26" Pine bears N.38 $\frac{1}{2}$ °W., 99.0 ft. healed face.  
24" Maple bears S.62°E., 311.8 ft. found scribe. (rec. 283.8 ft.)  
Set - 5/8" x 48" iron rod and alum. cap on line between section corners  
at call distance from NW BT. (SE BT did not match rec. call dist.)  
New Accessories -  
27" Fir bears N.20°W., 118.4 ft. scribed "1/4 S31 BT"  
25" Fir bears S.73°E., 223.0 ft. scribed "1/4 S6 BT"  
----- 7/92 -----

Sec.Cor. for 24 and 25 only 258  
Found - A 1 $\frac{1}{2}$ " O.D x 36" badly bent northerly Iron pipe protrudes 12"  
above ground. Ren. #196  
3/4" I.Rod. West, 15.0 ft., bent southerly flush with ground,  
(.R. (West 20 ft.) is horizontal near record position.  
Corner for secs. 19 and 30, T.30-5 bears South, 106.8 ft.  
Set - Plumb position of I.P. is referenced and a 2 3/8" dia. brass cap  
on a 1 3/8" O.D. x 32" long Iron pipe is set at referenced  
position, BC/IP is set 12" below ground. Cap marked:  
DOUGLAS COUNTY SURVEYOR'S  
T 30 S  
R S 24 | S19 R  
6 S 25 | 5  
W 1993 W  
Office

New Accessories:  
28" dia. Pine, double blazed and scribed T30S R6W s25 CS BT  
bears S.63°W., 38.8 ft.  
26" dia. Pine double blazed and scribed T30S R6W S24 CS BT" bears  
N.19°W., 149.5 ft.  
3/4" x 30" long I.Rod reset, West 20.0 ft. flush with ground.

Sec. Cor. for 19 and 30 only of T.30-5 259  
Found - 1 $\frac{1}{2}$ " O.D. x 36" long Iron pipe bent northerly, protruding 12"  
above ground (no brass cap) Ren. No. 197  
2 3/4" I. rod's flush with ground East 15.0 ft. and 20.0 ft.  
No fence posts from previous renewal found.  
Corner Secs. 24 and 25, T.30-6 bears North, 106.8 ft.  
Set - Plumb position of I.P. is referenced and a 2 3/8" dia. brass cap on  
a 1 3/8" O.D. x 32" long Iron pipe is set at referenced position  
BC/IP is set 12" below ground. Cap is marked:  
DOUGLAS COUNTY SURVEYORS  
T 30 S  
R S 25 | S 19 R  
6 S 30 | 5  
W 1993 W  
Office

New BTs - 28" dia. Pine double blazed and scribed "T30S R5W S30 CS BT" bears  
S.88 $\frac{1}{2}$ °E., 35.9 ft.  
26" dia. Pine double blazed and scribed "T30S R5W S30 CS BT" bears  
S.1 $\frac{1}{4}$ °E., 113.7 ft.

Douglas County Surveyors Office  
Randall Smith, Deputy  
Stephen Flaue  
Feb. 19, 1993  
C.S. File 64/39