

Douglas County Surveyor's Record of  
Government Corners Renewed

30 T.S. 7 R. W. W. M.

Wm  
Dm 995  
Sept 13 1897  
FB2 Pg 20

W. P. BRIGGS  
Mel. 24, 1892

FB +  
Pg 57

Eng. -- John H. Markham, Jr.  
Witness - J. H. Brown  
May 10, 1951

C.S. 40/311

Eng. -- John H. Markham, Jr.  
Witness - Geo. Vaughn  
J. H. Brown  
May 19, 1951

C.S. 40/311

John H. Markham  
Reg. Eng'r 2880  
Wit. Geo. Vaughn  
P. J. Holmes  
June 21, 1951

1 CORNER BETWEEN SECTIONS 4 and 5.  
Rock Monument  
Fir 12" dia. bears S. 31 1/2° W., 37 lks.  
Cedar 4" dia. bears N. 70° E., 29 lks.

2 CORNER BETWEEN SECTIONS 11 and 14.  
Red Fir 5 inches dia. for corner marked 1/2 S. C.S. from  
which  
A Fir 5 1/2 in dia. bears S. 5° W., 5 lks.  
A Fir 4" in dia. bears North 7 lks.  
The original B.T.s could not be found.

3 SEC. COR. 23 - 24 - 25 - 26  
Determined by O. B. T.  
A cedar 30 in. diam. bears N 1° W, 26.0 ft. dist. O.B.T.  
A Fir 26 in. diam. bears N 13° E, 35.0 ft. dist. O.B.T.  
A Fir Snag bears S 65° E, 35.0 ft. dist., found scribe on all O.B.T.s  
At corner point set 1" x 30" iron pipe, from which  
A Fir 10 in. diam. bears S 45° E, 13.0 ft. dist. marked S 25, B. T.  
A W. Fir 33 in. diam. bears S 32° W 6.0 ft. dist. marked S 26, B.T.

4 SEC. COR. 24- 25  
I rescribed both O.B.T.s  
At corner point set 1" x 30" iron pipe, from which O.B.T.s bears  
A Pine 46 in. diam. bears N 32° E, 18.5 ft. dist.  
A Pine 34 in. diam. bears S 30° W, 21.5 ft. dist.

5 S.E. COR. SEC. 24  
Determined by chopping 3 hrs. on 30 in. Pine  
A Pine 30 in. diam. (now chopped 1/2 in two) bears N 48° E 82.0 ft. dist.  
found old scribe.  
A Pine 36 in. diam. bears S 60° W 49.0 ft. dist., I remarked this O.B.T.  
S 25, B.T.  
At corner point set 1" x 30" iron pipe, from which  
A Pine 14 in. diam. bears N 85° W, 50.5 ft. dist. marked S 24, B.T.  
A Pine 14 in. diam. bears S 78° E 37.0 ft. dist. marked S 30 B. T.

6 SEC. COR. 13 - 14 - 23 - 24  
Determined by O.B.T.  
A Fir 70 in. dia. bears S 80° E, 14.0 ft. bark scribed S24, T30S, R7W, B.T.  
A Laurel 30 in. dia. bears S 48° W, 50.0 ft. dist. O.B.T.  
At corner point set wood stake, from which  
A Laurel 30 in. dia. bears N 67° W, 42.5 ft. dist. marked S 14, B.T.  
A Laurel 40 in. dia. bears N 2° W 38.0 ft. dist. marked S 13, 2880, B.T.

7 Section 34- South 1/2 sec. cor.  
Location determined by a pile of stones and old BT a  
Pine snag 30" dia. N 50° E 21.0 ft. with scribe mks. and a  
Laurel (dead) 24" dia. S 68° E 29. ft.  
Drove a 1"x30" iron pipe for corner from which a  
Pine 12" dia. bears S 49° E 49.0 ft. scribed 1/4 S3 BT  
Fir 52" dia. " North 225 ft. scribed 1/4 S 34 BT.  
Road bears North 480 ft.  
This corner lies in an old burn on a little flat on the  
nose of a ridge.