

Douglas County Surveyor's Record of  
Government Corners Renewed

30

T. S.

7

R. W. W. M.

KOHS-CHAPMAN, EUGENE, ORE. 97196

A. R. Evans  
Witnesses:  
M. E. Evans  
T. S. Harris  
July 16, 1953  
Done for S. P. Davis For S. P. Davis  
Filed in 41/253

corner secs. 25-36.  
Reset from O. B. T. - 30° Madrone N. 30° W., 147.0 feet.  
Set 5/8" iron rod. New B.T.  
18" pine, S. 10° W., 4.0 feet, mkd  $\frac{1}{4}$  S 36 - RE 2741 B.T. **72**

A. R. Evans  
Witnesses:  
G. E. Johnson  
Merle Evans  
June 14, 1953  
For D. Kartes  
File 41/252

Corner to secs. 25, 26, 35, and 36.  
Reset from O. B. Ts. - Fir NW., Fir stump SW.  
Old corner post.  
Set 4" x 4" x 48" Fir post, 3 B.Ts.  
8" live Oak N. 20° E., 10.3 feet, mkd T30S-R7W, S 25 RE 2741 BT.  
6" L. O. S. 68° E., 11.8 feet, mkd T30-R7 S36.  
6" L. O. S. 11° W., 16.4 feet., T30-R7 S35. **71**

A. R. Evans  
Witness:  
G. E. Johnson  
June 14, 1953  
For D. Kartes  
File 41/252

1/4 corner secs. 25 and 30, T30S, R6W and T30S, R7W.  
Set by proportional measurement.  
Set 4" x 4" x 36" pine stake in mound of rock.  
2 B.T's.:  
14" Pine - N. 68° W., 27.7 feet, mkd  $\frac{1}{4}$  S 25 - RE 2741 B.T.  
14" Pine, N. 74 1/2° E., 54.8 feet, mkd  $\frac{1}{4}$  S 30 - RE 2741 B.T. **54**

A. R. Evans  
Witness:  
G. E. Johnson  
June 15, 1953  
For D. Kartes  
File 41/252

Section corner to secs. 25, 30, 31, and 36, T30S, R6W., and T30S, R7W.  
Found 22" Pine, N. 35° W., 12 lks.  
20" Pine, S. 23° E., 178 lks. - Both dead and down.  
Set 4" x 4" x 48" pine stake.  
4 B.Ts.  
14" Pine, S. 44 1/2° W., 31.6 feet, mkd. T30S, R7W., S. 36.  
18" Pine, S. 15 1/2° E., 8.8 feet, mkd. T30S, R6W., S. 31.  
16" Pine, N. 19° E., 48.5 feet, mkd. T30S, R6W., S. 30.  
14" Pine, N. 47° W., 14.5 feet, mkd. T30S, R7W., S. 25. **53**

R. H. Gee  
March, 1955.  
For Roseburg Lumber Co.  
C. S. File No. 41/385.

1/4 sec. corner to secs. 11 and 12.  
Found white Oak B. T.  
Set 4 inch by 4 inch by 3 foot cedar post marked  $\frac{1}{4}$  S 11 on West face and  $\frac{1}{4}$  S 12 on east face from which bears:  
A White Oak, 22 inches, S. 28° E., 19.8 feet mkd.  $\frac{1}{4}$  S 12. **79**  
A Fir, 14 inches, S. 25° W., 24.5 feet marked  $\frac{1}{4}$  S 11 T30S, R7W.  
Metal tag placed on the fir. March 24, 1955.

1/4 sec. cor. to secs. 19 and 20.  
Found an old cedar B. T. in sec. 20, scribe marks visible, tree dead and down, stump hole very plain.  
Reset corner with 3 inch X 3 inch X 40 inch cedar post marked  $\frac{1}{4}$  S 20 on east face &  $\frac{1}{4}$  S 19 on west face from which bears **51**  
A Hemlock, 24 inches, N. 10 1/2° E., 8.0 feet marked  $\frac{1}{4}$  S 20 T 30 S, R 7 W., B. T. Tree is tagged.  
A Cedar, 8 inches, N. 83° W., 55.0 feet marked  $\frac{1}{4}$  S 19 T 30 S, R 7 W., B.T. Tree is tagged. March 11, 1955.

Fd. I.P. #875  
7/22 GLAD  
Admin. Survey  
SEE GTS  
FILE

Section corner to Sec's 7 & 18 (T30S, R7W) and secs. 12 and 13 (T30S, R8W).  
Set a 1/2 inch iron rod from which bears:  
A Fir, 26 inches, N. 56° E., 14.5 feet - O. B. T.  
A Fir, 10 inches, S. 75 1/2° W., 25.6 feet marked S 13, T 30 S, R 8 W., W. M.  
A Fir, 14 inches, N. 59 1/2° W., 29.0 feet marked S 12, T 30 S, R 8 W., W. M.  
A Pine, 8 inches, S. 25° E., 41.6 feet marked S 18, T 30 S, R 7 W., W. M.  
March 11, 1955.

SAME

Sec. corner to secs. 7 & 18, T30S, R7W., and secs. 12 & 13, T30S, R8W.  
Set an 1/2 inch iron pipe.  
From which:  
Fir, 26 inches, N. 56° E., 14.5 feet. - old B. T.  
Fir, 10 inches, S. 75 1/2° W., 25.6 feet. - new B. T.  
Fir, 14 inches, N. 59 1/2° W., 29.0 feet - new B. T.  
Pine, 8 inches, S. 25° E., 41.6 feet. - new B. T.