

Douglas County Surveyor's Record of  
Government Corners Renewed

30

T. S.

7

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97196

Township corner to secs. 1, 6, 31 and 36, Twps. 29 & 30, Rgs. 6 & 7 W.  
Point for corner determined by O. B. T.s:

A 24 inch W. O., bears N73E., 14.5 feet dist., - I rescribe S 31 B. T.

A 20 inch W. O., bears S20E., 33.0 feet dist., - I rescribe S 6 B. T.

A 44 inch Y. Pine windfall bears S19W., 30.4 feet dist., - ~~28~~ B. T.

At corner point set 2 inch x 36 inch solid steel bolt,  
from which:

A 21 inch W. O., bears N49W., 177.0 feet dist., mkd. S 36 T29S, R7W., B.T.

A 22 inch La. bears N4E., 55.0 feet dist. mkd. S31, T29S, R6W., B.T.

A 14 inch W. O., bears S33E., 30.5 feet dist., mkd. S 6, T30S, R6W., B.T.

An old fence runs N - S.

21

John H. Markham Jr.  
Work done for Stomar  
Lumber Co.  
Sept. 17, 1956.  
C. S. File No. 42/191.

$\frac{1}{4}$  corner to sec. 2, T30S, R 7 W., and sec. 35, T29S, R7W.

Point for corner determined by O. B. T.s:

A 14 inch La. bears S.60°E., 30.4 feet dist., - found scribe.

At corner point set 1 inch x 36 inch truck axle with flange up,  
from which

A 42 inch La. bears N.50°E., 42.5 feet dist. mkd.  $\frac{1}{4}$  S 35, T29S., R7W.,  
2880 B. T.

A 9 inch Fir bears S18E., 41.8 feet dist. mkd.  $\frac{1}{4}$  S 2 B.T.

Old fences run N - S - W from corner.

Fence corner bears S.46°E., 17.3 feet distant.

22

John H. Markham Jr.  
Work done for Stomar Lumber Co.  
April - September, 1956.  
C. S. File No. 42/192.

Section corner to secs. 1 & 2, T30S, R7W., and secs. 35 & 36, T29S, R7W.

Corner point determined by O. B. T.s:

A 24 inch La. bears S.68E., 27.7 feet dist. - O. B. T. - found scribe.

At corner point set  $\frac{3}{4}$  inch x 30 inch iron pipe,  
from which:

An 18 inch La. bears S.86W., 34.0 feet dist. mkd. S 2, T30S, R7W., B.T.

A 30 inch La. bears N21W., 35.0 feet dist., mkd. S 35, T29S, R7W., B.T.

A 15 inch La. bears N39E., 36.0 feet dist. mkd. S 36, T29S, R7W., B.T.

A 35 inch La. bears S.24E., 45.0 feet dist. mkd. S11, T30S, R7W., W. M., B.T.

23

$\frac{1}{4}$  corner to sec. 1, T30S, R7W., and sec. 36, T29S, R7W.

Point for corner determined by O. B. T.s:

A 67 inch Pine stump bears N40E., 141.0 feet dist. - found scribe.

At corner point set 2 inch x 16 inch solid steel shaft  
from which:

An 8 inch W. O. bears N23W., 38.0 feet dist. mkd.  $\frac{1}{4}$  S 36 B. T.

A 15 inch Cedar bears S18E., 39.6 feet dist. mkd.  $\frac{1}{4}$  S S 1 B. T.

Road bears East 230.0 feet.

24

Section corner to secs. 1, 2, 11, and 12.

A 72 inch Pine bears S70E., 63.4 feet dist. - O. B. T.

At corner point set large truck axle with flange up,  
from which:

A 12 inch Cedar, bears N20W., 5.7 feet dist. mkd. S 2 B. T. #119

A 12 inch Cedar bears N80W., 7.8 feet dist. mkd. S 11 B. T.

A 5 inch W. O. bears N72E., 34.0 feet dist. mkd. S 1 B. T.

A 12 inch Cedar bears S.52E., 11.8 feet dist. mkd. S 12 B. T.

Road bears South 53.0 feet.

Fence runs N.55E., and S.55W., through corner.

25

*Wit. Cor.*  $\frac{1}{4}$  Section Corner to Sections 9 and 16.

Found - Both Orig. BT's.: Orig. 15", now 36" Fir, shows good bark  
scribing, " $\frac{1}{4}$ " S N.52°E. 23.8 ft.

Orig. 15", now 34" Fir S.25°W. (record S.52°W. 38.3 ft.)  
shows good bark scribing " $\frac{1}{4}$ " S.

Set Brass Cap 80' West of corner mkd: County Surveyor's -Wit. Cor. 80'E.  
Office, 1960 to  $\frac{1}{4}$  S9 T30S  
S16 R7W

Note -  $\frac{1}{4}$  Cor. is in Roadway of Proposed Road.

New BT's: 40" Cedar bears S.43°W. 11.5 ft. scribed WC  $\frac{1}{4}$  S16 CS BT.

34" R. Fir bears S.48°E. 12.3 ft. scribed WC  $\frac{1}{4}$  S16 CS BT.

7/73 - Fr. O.K. - V.R.T. - C.S. 56/34

26

James W. Byron, Deputy  
Milo E. Godfrey  
Olete Putnam  
April 1, 1960  
C. S. File No. 52/22