

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 S. T. S. E. 7 W. R. W. W. M.

NOKE-CHAPMAN CO. EUGENE, ORE. 97301

1/4 Corner to Sections $\frac{S33}{S4}$ T29 1/2 S R7W T30-8 #129 40
Found - Stone & Both BT's. as recorded. BT's. now have rotted faces.
New BT's: 6" R. Fir bears S. 35° E. 8.0 ft. scribed 1/4 S4 CS BT.
7" Laurel bears N. 17° E. 16.4 ft. scribed 1/4 S33 CS BT.

RE-RENEWED SEE CORNER NO. #129

Renew $\frac{S36}{S1/S6}$ T29S-8W 41
T30-R8 T30-R7
Found - Cedar S. 56° E. 17.5 ft. Both trees had been previously opened.
Cedar N. 27° 31.0 ft. Found old axe work on S.E. Tree but
scribing had rotted. Evidence of corner being used. Corner also
checks bearing & distance from 36, 31 & 6 (7.08 chains).
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 T29S R8W $\frac{S36}{S1/S6}$ R7W T30S
Rescribed O.B.T.: 36" Cedar S. 56° E. 12.5 ft. T30S R7W S36 CS BT.
New BT's: 14" Hemlock N. 1° E. 10.7 ft. T29S R8W S36 CS BT.
14" Cedar S. 71 1/2° W. 21.4 ft. T30S R8W S1 CS BT.

1/4 Corner to Sec. 18, T30-7W. & Sec. 13, T30-8W. 42
Found - Both Orig. BT's. as recorded, previously opened, shows good scribing "S". #138
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 R8W 1/4 S13/S18 R7W T30S
Note - Both BT's. in good condition. We do not scribe new BT's.

RE-RENEWED SEE CORNER NO. #138

Section Corner to Secs. 34 & 35, T30-7W. & Secs. 2 & 3, T31-7W. 43
Found - Orig. 15", now 26" Pine S. 85° W. 19.8 ft., shows good scribing.
Orig. 24", now 38" Pine Snag shows old axe work N. 63° E. 139.9 ft.
Other Orig. BT's. not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 $\frac{S34}{S3}$ | $\frac{S35}{S2}$ T30S R7W T31S
New BT's: 23" Cedar bears N. 30° E. 13.6 ft. scribed S35 T30S R7W CS BT.
12" Pine bears S. 31° E. 8.7 ft. scribed S2 T31S R7W CS BT.
8" Pine bears N. 3° W. 47.3 ft. scribed S34 CS BT.
Dec. 27, 1962

FD OK. 10/62
H. Johnson
M 97-61

1/4 Corner to Sections 34 and 35. 44
Found - 1" x 30" I.P. at Cor. & in mound of Rock. Corner Pipe
has wood plug & bronze cap stamped RS. - See C. 8 FILE # 41/151
16" Pine Stump bears N. 83° W. 19.0 ft., shows scribing near base,
(not old)
Orig. 14", now 24" Pine N. 85° E. 49.5 ft., previously opened, shows
good scribing.
Orig. S. W. Bearing Tree not found.
New BT: 12" Pine bears N. 10° W. 9.8 ft. scribed 1/4 S34 CS BT.
Note - Corner Pipe is on Solid Rock.
May 22, 1963

Section Corner to Sections 26 - 27 - 34 - 35. 45
Found - Orig. 12", now 24" R. Fir Snag N. 75° W. 15.2 ft., prev. opened,
shows scribing.
Stool of Live Oak, shows old scars, bears S. 50° W. 18.0 ft.,
No trace of NE or SE Bearing Trees. (not 23.1 ft.)
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963 $\frac{S27}{S34}$ | $\frac{S26}{S35}$ T30S R7W
New BT's: 11" R. Fir bears S. 49° E. 87.5 ft. (on slope) scribed T30S R7W S35 CS BT.
18" Live Oak bears S. 66° W. 17.0 ft. scribed S34 CS BT.
8" Live Oak bears N. 19° W. 54.5 ft. scribed S27 CS BT.
Note - Corner is on steep rocky East slope & about 100' East of top ridge.
May 22, 1963

James W. Byron, Deputy County Surveyor
Dale McFarland and John Powell
June 21, 1962
C. S. File No. 49/139