

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 W. T. S. R 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Sec. Cor. to Secs. 13 & 24, T30-7W. & Secs. 18 & 19, T30-6W. 46
Found - 24" B.Oak S.60°W. 327 lks. (now 36" & Dying)
23" B.Oak N.70°E. 70 lks. (now 32" & Dying) REN #8
15" B.Oak S.50°E. 122 lks. (now 24" & Good)

Set - 1" x 30" Iron Pipe
Scribed :16" Pine S.28°W. 58.0 ft.
12" Fir N.51½°E. 50.0 ft.
22" Pine N.51°W. 5.6 ft.

RE-RENEWED, SEE CORNER NO. #136

Howard W. Johnstone
For Roseburg Lumber
August 18, 1962
C. S. File No. 51/163

¼ Corner for Sections 22 and 23. 47
Found - 20" Pine N.22°E. 34 lks.
Set - 1" x 30" Iron Pipe
Scribed - 15" D. Fir S.51½°W. 23.8 ft.
14" D. Fir N.50°E. 58.0 ft.

¼ Section Corner to Sec. 12, T30-7W. & Sec. 7, T30-6W. 48
Found - Orig. 7", now down, 10" Oak N.50°E. 85.8 ft., previously
opened, shows good scribing "BT".

Stump Hole that checks for Original S.W. Bearing Tree.

Note - E. - W. Fence 20 ft. North.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963

¼ R7W S12/S 7 R6W T30S

New BT's: 16" R.Fir bears N.33°E. 6.8 ft. scribed ¼ S7 CS BT.
10" R.Fir bears S.18°W. 15.3 ft. scribed ¼ S12 CS BT.

RE-RENEWED, SEE CORNER NO. #152

FD 1977
BLM ADMIN. SURVEY
SEEGIS FILE

James W. Byron, Deputy
Mike Darby
September 13, 1963

C.S. File
49/139

Section Corner to Secs. 1 & 12, T30-7W. & Secs. 6 & 7, T30-6W. 49
Found - All Orig. BT's: Orig. 36", now 42" Pine N.45°W. 7.9 ft., shows scrbing.
Orig. S.W. BT., now dead, checks record bear. & distance.
Orig. 22", now 30" Laurel, shows good scar S.82°E., not S.87°E., 81.2'.
Orig. 25", now 32" Laurel, shows good scar N.50°E., not N.45°E., 68.6'.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963

¼ R7W S1 | S6 R6W T30S
S12 | S7

New BT's: 10" W.Fir bears N.81°E. 5.4 ft. scribed S6 T30S R6W CS BT.
7" R.Fir bears S.25°E. 22.5 ft. scribed S7 CS BT.
12" W.Fir bears S.58°W. 21.2 ft. scribed S12 T30S R7W CS BT.

¼ Corner between Sections 16 and Section 17. 50

Found - Original Corner Tree, now 12" diam. D. Fir
6" D. Fir S.60°E. 9.2 ft. (now 16" diam.)

Scribed - 12" D. Fir S. 44½° W., 23.5 feet.

Sept. 4, 1963

Howard W. Johnstone
For Rsbrg. Lumber
Wit: Henrickson &
Clark
C.S. File 51/163

Section Corner to Secs. 24 & 25, T30-7W. & Sec. 19 & 30, T30-6W. 51

Found - Orig. 18", now 40" Pine S.60°W. 46.2 ft., shows good scar.

Orig. 12", now 30" Pine N.48°E. 81.8 ft., prev. opend, shows scrbing.

No other Original Bearing Trees found.

Find 1" I.Pipe at Corner. REN. No.5

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963

¼ R7W S24 | S19 R6W T30S
S25 | S30

New BT's: 25" Pine bears S.40°E. 24.0 ft. scribed S30 T30S R6
We find 18" Pine N.84°W. 49.7 ft., shows good scribing, See Ren. #5,
T30S R7W.

Note - J.H.M's axe he used to open the N.E. BT. couldn't have been very sharp.

FD 6K5/6/9
C.S. 5/1/5
James W. Byron, Deputy
Mike Darby & Jim Halterman
December 1963
C. S. File No. 53/40

¼ Corner to Sec. 24, T30-7W. & Sec. 19, T30-6W. 52

Found - Mound of Stone & Stake at Corner.

Orig. 6", now 24" Cedar N.20°E. 83.2 ft. prev. opend. shows scrbing.

Orig. N.W. BT., down & mostly rotted.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963

¼ R7W S24/S19 R6W T30S

New BT's: 10" R.Fir bears N.7°W. 14.0 ft. scribed ¼ S24 CS BT.
12" Cedar bears S.81°E. 19.4 ft. scribed ¼ S19 CS BT.

Note - Corner is under 18" Cedar Log.