

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 7 W. R.W.W.M.

KONE-CHAPMAN CO., EUGENE, ORE. 21991

53

James W. Byron, Deputy
Mike Darby & J. Halterman
December 1963
C. S. File No. 53/40

Sec. Cor. to Secs. 25 & 36, T30-7W. & Secs. 30 & 31, T30-6W.
Found - All BT's. as recorded Ren. No. 174,
S. W. Bearing Tree now snag.
Find base Corner Stake.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
New BT: 10" R.Fir bears S.27°W. 67.5 ft. scribed

FD. OK 7/72
M. SMALLEY M112-52

S25	S30	T30S
R7W	S36	S31 R6W
S36	T30S	R7W CS BT.

54

1/4 Corner to Sec. 25, T30-7W. & Sec. 30, T30-6W.
Found - Both Bearing Trees as recorded Ren. #16.
BT's. O. K. & We find Mound of Stone at Corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1963
1/4 R7W S25/S30 R6W T30S

55

1/4 Corner to Sections 5 and 6.
Found - 5/8" Iron Rod at Corner & Orig. 24", now 38" R.Fir N.16°W. 9.2 ft.
(Find good bark scribng. near base)
Orig. S. E. Bearing Tree not found.
Corner Stone, not found.
Note - Corner is on East Slope and about 100 ft. south of small stream.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
1/4 S6/S5 T30S R7W
Rescribed - Now 38" R.Fir N.16°W. 10.2 ft. 1/4 S6 CS BT.
New BT: 24" R.Fir bears N.58°E. 23.6 ft. scribed 1/4 S5 CS BT.

56

Sec. Cor. to Sections 5 - 6 - 7 - 8.
Found - 5/8" Iron Rod & Steel Fence Post at Corner.
All Orig. BT's. All check record.
Orig. N. E. & S. W. BT's. show good scribing.
10" R.Fir bears S.5°E. 33.7 ft. We open & find good scribing.
(This BT. scribed about 8 years ago, probably by Roger Gee.)

FD.I.R. 7/72
BLM ADMIN SEE
SURVEY - GIS FILE

57

1/4 Corner to Sections 19 and 20. (Witness Corner)
Found - All BT's. as recorded Cor. #19.
Note - Corner is in stream 4 ft. wide, I set Wit. Cor. 5 ft. West.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
Wit. Cor. 5 ft. West to 1/4 S19/S20 T30S R7W
New BT: 15" Hemlock bears S.5°W. 65 ft. scribed 1/4 S19 CS BT WC
8" Cedar bears N.83°W. 60.0 ft., previously scribed.
24" Hemlock bears N.32°W. 9.4 ft., previously scribed.

58

Sec. Cor. to Sections 7 - 8 - 17 - 18.
Found - All Orig. BT's., except S. W. BT. S.E. BT., now snag, shows gd. scrb.
N. E. BT., shows scribe marks.
Note - Corner is in old cat road, earth is excavated to solid rock.
Set - Brass Cap at Cor. & Build Mound of Rock
Mkd: County Surveyor's Office, 1964
New BT's: Rescribe, now 14" W.Oak N.34°W. 28.6 ft. scribed S7T30S R7W CS BT.
13" R.Fir bears N.18°E. 40.9 ft. scribed S8 T30S R7W CS BT.
10" Cedar bears S.49°E. 45.1 ft. scribed S17 T30S R7W CS BT.
6" R.Fir bears S.37°W. 37.6 ft. scribed S18 CS BT.

S 7	S 8	T30S R7W
S18	S17	

James W. Byron, Deputy County Surveyor
Mike Darby and Jim Halterman
February 1964
C. S. File No. 53/40

FD. B.C. & BT
7/72 - BLM
ADMIN. SURVEY
SEE GIS FILE

59

Sec. Cor. to Secs. 14 - 15 - 22 - 23.
Found - Orig. 60", now 50" Laurel S.48°W. 15.2 ft., shows good scribing.
Orig. 14", now 36" Fir Snag N.24°E. 75.2 ft., shows scribing.
Orig. S. E. BT. in slide area.
Now 30" Cedar N.18°W. 44.2 ft., not N.28°W. 44.2 ft., shows faint scar.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
New BT's: 11" R.Fir bears S.64°E. 25.8 ft. scribed S23 T30S R7W CS BT.
6" R.Fir bears S.48°W. 5.5 ft. scribed S22 CS BT.
14" R.Fir N.26°E. 28.2 ft. scribed S14 T30S R7W CS BT.
30" Cedar bears N.18°W. 45.7 ft. scribed S15 T30S R7W CS BT.

S15	S14
S22	S23