

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

60

$\frac{1}{4}$  Corner common to Sections 30 and 29.  
Found - Orig. 24", now 30" R. Fir N. 84° E. 44.9 ft., shows faint scribe.  
Corner Stone and S. W. BT. not found.  
Note - Corner is on steep 1:1 rocky slope.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
 $\frac{1}{4}$  S30/S29 T30S R7W  
New BT's: 20" Pine bears S. 18° E. 19.0 ft. scribed  $\frac{1}{4}$  S29 CS BT.  
12" R. Fir bears S. 42 $\frac{1}{2}$ ° W. 29.2 ft. scribed  $\frac{1}{4}$  S30 CS BT.

61

$\frac{1}{4}$  Corner to Sections 19 and 30.  
Found - Orig. 36", now 38" Fir Snag S. 18° E. 35.6 ft., shows good scribng.  
Orig. N. E. BT., now down, no scribing found.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
 $\frac{1}{4}$  S19 T30S R7W  
S30  
No Trees Near. - We mark sandstone boulder 5'x4'x3' high. We chisel 2"+ on pointed top, & B.O. on south face. + on top bears S. 14° W. 13.6 ft. from  $\frac{1}{4}$  corner.  
Note - Corner is on steep East Slope & about 150 ft. east of Logging Road.

62

$\frac{1}{4}$  Corner to Sections 5 and 4.  
Found - No Orig. BT's. Do find Rock Mound at Corner.  
12", now 24" R. Fir S. 31 $\frac{1}{2}$ ° W. 24.4 ft. We open & find good scribing.  
N. E. Bearing Tree not found, See Ren. # 1.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
 $\frac{1}{4}$  S 5/S 4 T30S R7W  
New BT's: 12" R. Fir bears N. 23° W. 9.5 ft. scribed  $\frac{1}{4}$  S5 CS BT.  
12" R. Fir bears S. 37° E. 26.7 ft. scribed  $\frac{1}{4}$  S4 CS BT.

63

$\frac{1}{4}$  Corner to Sec. 34, T30-7W. & Sec. 3, T31-7W.  
Found - 1" I.P. & Mound of Stone at Corner.  
Now 16" Pine BT. S. 49° E. 49.0 ft. See Cor. No. 7.  
New BT: 17" Cedar bears S. 43° W. 99.8 ft. scribed  $\frac{1}{4}$  S3 CS BT.

64

Sec. Cor. to Secs. 33 & 34, T30-7W. & Secs. 4 & 3, T31-7W.  
Found - Brass Cap at Cor. (GLO Brass Cap)  
N.#. & S.E. BT's. O.K. SW BT. now stump. NW BT not found.  
New BT's: 14" R. Fir bears S. 86° W. 24.7 ft. scribed T31S R7W S4 CS BT.  
7" Myrtle N. 10 $\frac{1}{2}$ ° W. 12.9 ft. scribed T30S R7W S33 CS BT.

65

$\frac{1}{4}$  Corner to Sec. 7, T30-7W. & Sec. 12, T30-8W.  
Found - Orig. 8", now 12" Laurel N. 75° W, not S. 75° W. 19.1 ft. We open & find good scribing.  
Orig. 20", now 30" Laurel N. 29° E. 7.3 ft., center rotted. no scribng.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
 $\frac{1}{4}$  S12/S 7 T30S  
R8W R7W  
New BT's: 7" R. Fir bears N. 58° W. 17.3 ft. scribed  $\frac{1}{4}$  S12 CS BT.  
12" R. Fir bears S. 16° E. 15.2 ft. scribed  $\frac{1}{4}$  S7 CS BT.

Fd B.C. 7/72  
BLM Admin.  
SURVEYOR  
SEE 615  
FILE

66

Section Corner Secs. 30 & 31, T30-7W. & Secs. 25 & 36, T30-8W.  
Found - GLO Brass Cap at Corner & All BT's. as recorded, except S. E. Bearing Tree, now snag.  
New BT: 7" Laurel bears S. 14 $\frac{1}{2}$ ° E. 17.2 ft. scribed S31 T30S R7W CS BT.

67

$\frac{1}{4}$  Corner to Sec. 30, T30-7W. & Sec. 25, T30-8W.  
Found - Both Orig. BT's. - Orig. 10", now 18" Fir Snag S. 72° E. 14.5 ft.  
(Open & find good scribing "B")  
Orig. 18", now 26" R. Fir N. 64° E. 14.5 ft., shows good scars.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
 $\frac{1}{4}$  R8S S 25/S 30 R7W T30S  
New BT's: Rescribe 26" R. Fir N. 64° W. 15.5 ft, bark scribe, C S.  
14" R. Fir bears S. 72° E. 40.6 ft. scribed  $\frac{1}{4}$  S30 CS BT.

James W. Byron, Deputy County Surveyor  
Mike Darby and Jim Halterman  
February 1964  
C. S. File No. 53/40

Fd ok  
6/18/64  
H. Johnson  
M 97-14

#105

#132

RE-RENEWED CORNER NO. #118