

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 7 W. R.W.W.M.

XOKE-CHAPMAN CO., EUGENE, ORE. 21881

81

$\frac{1}{4}$  Corner to Sections 10 and 11.  
Found - 8", now 18" D. Fir N.85°W. 7.3 ft. Open & find " $\frac{1}{4}$ " Scribe.  
No trace of Laurel to E.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T30S R7W  $\frac{1}{4}$  S10/S11  
New BT's: 14" D. Fir S.75°W. 20.0 ft. Mkd:  $\frac{1}{4}$  S10 CS BT.  
32" D. Fir S.66°E. 31.8 ft. Mkd:  $\frac{1}{4}$  S11 CS BT.  
Note - This corner lies approx. 100 ft. over top of ridge on N. slope.

82

Section Corner to Sections 2 - 3 - 10 - 11.  
Found - 30", now 36" D. Fir Snag N.64°W. 12.5 ft., open & find "BT" scribe.  
30", now 38" D. Fir(alive) S.70°E. 7.3 ft., shows good "S", bark scribe  
No trace of Laurel or Willow BT's.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T30S R7W  $\frac{S}{S}$   $\frac{3}{10}$  |  $\frac{S}{S}$   $\frac{2}{11}$   
New BT's: 25" W. Fir N.14°W. 38.8 ft. Mkd: T30S R7W S3 CS BT.  
15" W. Fir N. 3° E. 80.6 ft. Mkd: T30S R7W S2 CS BT.  
38" D. Fir S.70°E. 8.0 ft. (Orig. BT) Mkd: T30S R7W S11 CS BT.  
6" Laurel S.27°W. 43.2 ft. Mkd: S10 CS BT.

FD. OK - 10/20 H. JOHNSTONE

83

$\frac{1}{4}$  Corner to Sections 15 and 14.  
Found - Both Orig. BT's., now snags, as follows:  
36", now 44" D. Fir N.43°W. 16.5 ft., recorded as Pine, shows good scar  
40", now 48" Cedar S.80°E. 33.0 ft., not healed over, ring count  
reveals approx. 50 yrs. before tree died, shows " $\frac{1}{4}$ S BT" scribe.  
This was recorded as N.80°E.  
Set - Corner at Intersection of Dist. & Bear. on N. W. Tree.  
Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T30S R7W  $\frac{1}{4}$  S15/S14  
New BT's: 8" Cedar S.51°E. 11.8 ft. Mkd:  $\frac{1}{4}$  S15 CS BT.  
9" Cedar N.81°W. 11.9 ft. Mkd:  $\frac{1}{4}$  S14 CS BT.

84

$\frac{1}{4}$  Corner to Sections 35 and 36.  
Found - One Orig. BT standing & hole in ground where other BT. was.  
Markham's Corner, Ren. #12, obliterated.  
14", now 20" W. Oak N.85°W. 31.7 ft., find "/L" reverse scribing.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T30S R7W  $\frac{1}{4}$  S 35/S 36  
New BT's: 8" W. Oak S.23°E. 20.8 ft. Mkd:  $\frac{1}{4}$  S36 CS BT.  
9" W. Oak S.62°W. 17.5 ft. Mkd:  $\frac{1}{4}$  S35 CS BT.

RE-RENEWED, SEE CORNER NO. # 142  
Nov. 13, 1964

84-A

$\frac{1}{4}$  Corner to Section 33 only.  
Found - GLO Brass Cap, 1918, mkd. " $\frac{1}{4}$  S33 1918" & one live BT:  
24", now 28" Yellow Pine N.25°E. 14.5 ft., face burned, shows scribe.  
5" Rotted stump N.44 $\frac{1}{2}$ °W. 16.5 ft., trace of reverse scribe,  
possibly the "B".  
New BT's: 10" Pine N.12°W. 40.4 ft. Mkd:  $\frac{1}{4}$  S33 CS BT.  
26" Pine N.74°E. 33.7 ft. Mkd:  $\frac{1}{4}$  S33 CS BT.  
Note - This corner lies approx. 100 ft. W. of small creek flowing N. W.  
March 1965

85

$\frac{1}{4}$  Corner to Sections 22 and 27.  
Found - Stump of Orig. BT very badly rotted:  
40" Pine S.30°W. 3.3 ft., face with " $\frac{1}{4}$ S" scribe & old axe marks.  
10" Oak BT is gone. Find an oak down hill with center rotted away,  
but no scribe.  
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965  
T30S R7W  $\frac{1}{4}$   $\frac{S}{S}$   $\frac{22}{27}$   
New BT's: 10" D. Fir S.43°E. 6.0 ft. Mkd:  $\frac{1}{4}$  S27 CS BT.  
15" D. Fir N.46°W. 15.8 ft. Mkd:  $\frac{1}{4}$  S22 CS BT.  
Note - This corner is approximately 300 ft. west of ridge top.  
March 1965

FD. OK 7/24/53  
FD OK 4/93  
By M. Smalley  
CS 63/153

Vernon R. Tracy  
Mike Darby & Jack Barnett  
September 1964  
C. S. File No. 53/40