

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21861

86

$\frac{1}{4}$ Corner to Sections 28 and 27.
Found - Orig. 6", now 11" Fir S.50°E. 15.8 ft., open & shows " $\frac{1}{4}$ "
scribe, tree now snag, approx. 8.0 ft. high.
Orig. 30", now 38" Fir S.50°W. 33.7 ft., open & shows " $\frac{1}{4}$ S"
scribe, tree alive.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S R7W $\frac{1}{4}$ S 28/S 27
New BT's: 14" D. Fir S.83°W. 30.8 ft. Mkd: $\frac{1}{4}$ S28 CS BT.
8" D. Fir S. 4°E. 27.8 ft. Mkd: $\frac{1}{4}$ S27 CS BT.
Note - This corner lies on steep S.E. slope approx. 160.0 ft.
north of creek.

87

$\frac{1}{4}$ Corner to Sections 21 and 28.
Found - Orig. 7", now 7" Laurel, down & badly rotted, S.20°W. 3.3 ft.,
Find old face, scribe rotted away.
Orig. 8", now 9" Laurel N.25°E. 9.2 ft., down & upper face
rotted badly, find "B" scribe on lower face in poor cond.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S R7W $\frac{1}{4}$ S 21
S 28
New BT's: 22" D. Fir S.34°W. 9.4 ft. Mkd: $\frac{1}{4}$ S28 CS BT.
24" D. Fir N.55°E. 6.6 ft. Mkd: $\frac{1}{4}$ S21 CS BT. *FD OK 4/93 By M. Smalley c.s. 63/153*
Note - This corner lies on sidehill sloping S.16°E. *4/28/65*

88

$\frac{1}{4}$ Corner to Sections 16 and 21.
Found - Orig. 38", now 42" Pine N.31°E. 22.4 ft., shows " $\frac{1}{4}$ ",
bark scribe, appears very old. No trace of other BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S R8W $\frac{1}{4}$ S 16
S 21
New BT's: 14" W. Fir N.89°E. 11.2 ft. Mkd: $\frac{1}{4}$ S16 CS BT.
6" W. Fir S.50°W. 40.6 ft. Mkd: $\frac{1}{4}$ S21 CS BT.
Remark Orig. Pine on bark alongside old scribe. " $\frac{1}{4}$ S16 CS BT.
5/3/65

Vernon "Ray" Tracy
M. Darby & J. Barnett
April - May 1965
C. S. File No. 53/40

89

Section Corner to Sections 16 - 17 - 20 - 21.
Found - Orig. 7", now 8" Laurel N.78°E. 7.3 ft., down & out of
place, shows "S" & parts of other letters in reverse
scribe, badly rotted.
Orig. 7", now 8" Laurel S.24°E. 15.2 ft., shows parts of reverse
scribe, also down & rotted.
Orig. 15", now 30" Fir N.10°W. 29.7 ft., shows fair bark
scribe, "T30SR7WS17 BT", alive & in good condition.
No trace of other BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S

S17	S16
S20	S21

 R7W
New BT's: 13" D. Fir S.37°E. 12.8 ft. Mkd: T30S R7W S21 CS BT.
12" D. Fir N.64°E. 11.0 ft. Mkd: T30S R7W S16 CS BT.
7" D. Fir N.39°W. 30.0 ft. Mkd: T30S R7W S17 CS BT.
14" D. Fir S.81°W. 27.0 ft. Mkd: T30S R7W S20 CS BT.
5/20/65

$\frac{1}{4}$ Corner to Sections 20 and 21.
Found - Orig. 10", now 24" Fir S.80°W. 9.2 ft., open, shows "4 S".
No trace of Laurel BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S $\frac{1}{4}$ S 20/S 21 R7W
New BT's: 14" Cedar N.49°E. 14.7 ft. Mkd: $\frac{1}{4}$ S21 CS BT.
11" D. Fir N.54°W. 16.5 ft. Mkd: $\frac{1}{4}$ S20 CS BT.
Note - This corner lies approx. 100.0 ft. E. of foot of bluffs
65 feet high, running N. & S.

91

Section Corner to Sections 20 - 21 - 28 - 29.
Found - Orig. 14", now 17" Laurel S.42°E. 38.3 ft., shows scar, didn't open.
Orig. 14", now 22" Cedar S.40°W. 33.0 ft., now dead snag.
Prev. opened, log in front prevents seeing into opening.
Orig. 26", now 38" Fir N.69°W. 22.4 ft., shows scribing.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S R7W

S 20	S 21
S29	S 28

*FD OK 4/93
By M. Smalley
c.s. 63/153*