

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 7 W. R. W. W. M.

ROBE-CHAPMAN CO., EUGENE, ORE. 31881

103

John M. Powell
Frank Jones & Terry Connell
C. S. File No. 53/40 7/11/66

Section Corner to Secs. 13 - 14 - 23 - 24.
Found - 70" D. Fir, down, S. 80° E. 14.0 ft., bark scribe visible. O.B.T.
30" Laurel Snag S. 48° W. 50.0 ft., faint scribe visible. O.B.T.
30" Laurel, now 34", N. 67° W. 42.5 ft., shows good scar. (See
40" Laurel, now 42", N. 2° W. 38.0 ft., shows scar. (Ren. #6)
Set - Brass Cap at Cor. Mkd: County Surveyor's Office T30S R7W
1966 S 14 S 13
S 23 S 24
New BT's: 7" D. Fir S. 54° W. 30.1 ft. scribed T30S R7W S23 CS BT.
11" D. Fir S. 37½° E. 39.8 ft. scribed T30S R7W S24 CS BT.
9" D. Fir N. 74° E. 38.0 ft. scribed T30S R7W S13 CS BT.

104

¼ Corner to Section 3 and 2.
Found - 10" D. Fir, now 18", N. 12° E. 20.5 ft. Tree had been opened
for scribe "S". Opened more for ¼.
No trace of S.W. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1966 T30S R7W
¼ S 3/S 2
New BT's: 21" D. Fir S. 17° E. 47.0 ft. scribed ¼ S 2 CS BT.
No other good trees handy in Sec. 3 so reblazed & rescribed:
18" D. Fir N. 12° E. 20.5 ft. scribed ¼ S 2 CS BT.
Note - This corner lies at bottom of 15.0 rock bluff on very steep,
west slope about 75.0 ft. east of spring branch.

105

John M.
Powell
& Crew
11/25/66
C. S. File
No. 54/36

Section Corner to Secs. 33 & 34, T30-7W. and
Secs. 4 & 3, T31-7W.
Found - G.L.O. Brass Cap at Sec. Cor., properly marked in 1918, See Ren. #64.
Orig. 10", now 12" Laurel, N. 41° E. 46.9 ft., scribe visible "BT".
Orig. 20" Pine, now dead, S. 7° E. 38.9 ft., shows scar.
Orig. 30" Laurel, now stump, S. 13° W. 12.5 ft., scribe vis., "BT".
14" Fir, now dead, S. 86° W. 24.7 ft., pitched over scrb. visible.
7", now 9" Myrtle, N. 10½° W. 12.9 ft., scribe visible.
New BT's: 18" D. Fir S. 70° E. 32.1 ft. mkd. T31S R7W S 3 CS BT.
8" W. Oak S. 71° W. 42.8 ft. mkd. T31S R7W S 4 CS BT.
Note - This corner lies East of Cow Creek Road, approx. 65.0 ft.

MICROFILM TO HERE 10/67

106

Section Corner to Sections 27 - 28 - 33 - 34.
Found - 1918 GLO Brass Cap, firmly set in mound of stone & properly marked.
Orig. 30", now 36" Y. Pine S. 66° E. 42.9 ft., Alive, shows good scar.
Orig. 36" Y. Pine, now burned snag, S. 35° W. 111.5 ft., no scribe found.
Orig. 40", now 48" Y. Pine, N. 5° W. 77.9 ft., Alive, scribe visible. (Rec. 92.4')
30", now 32" Y. Pine, dying, N. 2½° E. 83.2 ft., scribe visible.
New BT's: 18" Y. Pine S. 9° W. 16.7 ft. mkd: "T30S R7W S33 CS BT".
13" Cedar N. 74° E. 17.5 ft. mkd: "T30S R7W S27 CS BT".
This corner lies on S.W. side of top of spur, ridge sloping S.

11/12/69

107

¼ Corner to Sections 28 and 33.
Found - 1918 GLO Brass Cap, in place and properly marked.
Orig. 48", now 54" Cedar, alive, N. 83° W. 44.9 ft., "¼ S BT" bark scribe, poor,
and "¼ S28 BT" on unhealed blaze.
1918 Pine, now burned snag, no scribe found.
New BT's: 12" D. Fir N. 9° E. 13.3 ft. mkd: "¼ S28 CSBT".
5" Cedar S. 81° E. 14.9 ft. mkd: "¼ S33 CS BT".
This corner lies in thicket of Laurel, young Fir and Pine.

11/12/69

108

Section Corner to Sections 28 - 29 - 32 - 33.
Found - 1918 GLO Brass Cap, in place and properly marked.
Orig. 30", now 40" W. Fir, Alive, S. 80° E. 15.8 ft., shows good scar, we tag.
Remains of 30" Fir N. 7° W. 38.3 ft., down, badly decayed, scribe on
unhealed blaze.

No trace other Original Bearing Trees.

New BT's: 8" W. Fir S. 47° W. 75.3 ft. mkd: "T30S R7W S32 CS BT".
14" W. Fir N. 80° W. 65.8 ft. mkd: T30S R7W S29 CS BT. FD. OK. 7/27/73
8" W. Fir N. 21° E. 54.3 ft. mkd: "T30S R7W S28 CS BT".
This corner lies on S.E. slope about 200 ft. N. of logging access road

11/12/69

Vernon "Ray" Tracy
Jack Heritage & V. Perron
November, 1969 C. S. File 53/40

FD. OK 9/8/73
H. J. J. STANB
M 97-50