

Douglas County Surveyor's Record of
Government Corners Renewed

30

T. S.

7

R. W. W. M.

Gary Langlitz, County Surveyors office
Peter Earle
Feb. 27, 1974
C.S. 56/43

KORE-CHAPMAN CO., EUGENE, ORE. 21881

114

Section corner, Secs. 11-12-13-14

Found - 1964 County Surveyor's brass cap . Ren. #77

Note - At this time, I find no indication on the monument as to it's range designation. I now mark the monument with a 7" to read "R7W"

Found - 7" D.Fir, burnt & dead, bears S.15°W., 6.9 ft. scribing has been chopped out.

12" D.Fir, burnt and dead, bears S.21°E., 16.8 ft. scribing grown over.

7" D.Fir, burnt & dead, bears N.87°E., 20.8 ft. face burnt out. The 2 original pine BT's mentioned in the 1964 renewal are now badly burnt.

A new BT, apparently marked by B.L.M Cadastral survey crew, an 18" D.Fir, burnt & dead, bears N.02°E., 11.2 ft. to face of blaze, scribed "T30S R7W S12 BT". This tree has been marked since the area burned, tag dated 10-73.

As there are no living trees in the vicinity, I set a steel fence post with survey marker warning sign attached 1.0 ft. north of corner point.

FD OK - FEB 1995 - M 121 - 52 - 2/27/74

JAN 75

Section Corner for Secs. 22,23,27 and 26

Found - 30" Oak, fallen over, N.28°W., 132.0 ft. Old face & chop marks, grown over. =

Set - Brass cap marked T30S R7W WM L.S. No. 1005

BT's - 7" Fir, N.57°W., 80.6 ft. Scribed "S22 BT"

8" Fir, S.70°W., 149.7 ft. Scribed "S27 BT"

13" W. Oak, scribed "S26 BT", S.65½°E., 59.1 ft.

24" Cedar, Scribed "S23 BT" bears N.41°E., 153.2 ft.

RE-RENEWED - SEE CORNER NO. #124

4/75

115

R. WARE
Don E. Garrett
for: Dean Sanders
April, 1975
M 57 - 3

L.E. Monrean
A.V. Cangie
4/24/75
C.S. 57/21

1/4 corner for Secs. 27 and 34

Found - 2" Post (unrecored)

From which:

A 40" D Fir bears N.9°E., 29.0 ft. (rec. N.10°E., 24.4 ft.) face chopped out no scribing visible. Broken off approx. 40 ft. above ground.

A large root hole bears S.60°E., 6.6 ft. 60" D Fir lying downhill 30 ft. from original standing place. Bark scribed 1/4S T.

Set - Brass cap stamped County Surveyors Office T30S R7W

1/4 S 27 / S 34

New BT's

10" D Fir bears S.37 1/2°W., 26.2 ft. scribed 1/4 S34 T30S R7W CS BT

8" D Fir bears N.60°W., 39.1 ft. scribed 1/4 S27 T30S R7W CS BT

4/23/75

116

Howard Johnstone
For: Roseburg
Lumber Co.
June 6, 1977
M 65 - 27

1/4 Corner for Sec. 1 and Sec. 6, T30-6

Set - 5/8" x 34" I. Rod and alum cap.

BT's - 9" Fir bears N.14°W., 9.8 ft.

6" Fir bears N.63°E., 18.5 ft.

6/6/77

117

R. B. Kimberling
M. W. Cline
Doug. Co. Surveyors
Office
Oct. 27, 1977
C.S 59/40

1/4 Corner for Sec. 34 and Sec. 3 of T31-7

Found - 1" Iron pipe in a mound of stone. Ren. #63

A 12" now 23" Sugar pine bears S.49°E., 49.0 ft. with a well healed double blaze.

A 17" now 16" Incense Cedar bears S.43°W., 99.8 ft. with visible scribing "1/4 S3 CS BT" in a partially healed double blaze.

Set - A 1" x 36" Iron pipe with brass cap set 9" above ground (in mound of stone and iron pipe along side) marked "Douglas County Surveyors T30S R7W 1/4 S34 S3 T31S R7W 1977.

No new accessories.

Note: Corner lies in old unit, 50 ft. north of tree line.

10/27/77

JAN 78

FD OK BY ROW Quimby 3/94 M 119-21

118