

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 T. S. R 7 R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

119

Section corner for Secs. 1, 2, 11 and 12.

Found - A 1 1/2" x 35" Axle with 5" flange down, spline end 15" above ground. Ren. #25

A 52" P. Pine bears S.70°E., 63.4 ft. with visible scribing "S2" in a chopped open blaze.

The East fork of a I. Cedar is (12") now 16" and bears N.20°W., 5.7 ft. with scribing "S2 BT" in a partly healed double blaze.

A 12" now 16" I. Cedar bears N.80°W., 7.8 ft. with a partly healed double blaze.

A 5" now 8" W. Oak bears N.74°E., (Rec. N.72°E.) 34.0 ft. with a well healed double blaze.

A 12" now 13" I. Cedar bears S.52°E., 11.8 ft. with visible scribing "S 12 BT" in a partly healed double blaze. Scribing is written up the trees.

Set - A 1" x 36" I.P. with brass cap 6" above ground at axle location marked: "County Surveyor" T 30 S R 7 W
1978 S 2 | S 1
Douglas S11 | S12

I set axle S.W. 0.3 ft. from the brass cap with the spline end 1.0 ft. above ground.

New BT - A 12" I. Cedar bears S.52°W., 11.7 ft. I double blaze and scribed "T30S R7W S11 CS BT".

Remains of a fence (NE-SW) are at the N.W. bearing tree. A BLM

4/4/78

120

Section Corner for Secs. 1 and 2; and 35 and 36 of T29-7

Found - A 3/4" I.P. 12" above ground, bears S.58°W., 2.0 ft. from corner, with a 3" x 3" squared post at the West side. Ren. #23

An OBT, a 24" Madrone (Laurel) bears S.68°E., 27.7 ft. with an opened blaze and visible scribing "S-T30S R7".

A 18" now 24" Madrone (Laurel) bears S.83 1/2°W., 35.7 ft. (Rec. S.86°W., 34.0 ft.) with visible scribing "S2 T30S R7" in a double partly healed blaze.

A 30" now 31" Madrone bears N.21°W., 35.0 ft. with visible scribing "3-29" in a double partly healed blaze.

A 15" now 18" Madrone bears N.39°E., 34.0 ft. (Rec. 36.0 ft.) with visible scribing "3-29-R7-BT" in a double partly healed blaze.

A 35" now 39" Madrone bears S.20 1/2°E., (Rec. S.24°E.) 45.0 ft. with visible scribing "S1 T30S R7WM" in a double partly healed blaze.

Note: Scribing is cut horizontal in all blazes.

Set - A 1" x 36" I.P. with brass cap set 6" above ground and marked: "Douglas County Surveyor" T 29 S
1978 R S 35 | S 36
7 S 2 | S 1
W T 30 S

No new accessories.

Corner is at the NW corner of old growth timber.

4/5/78

121

Center 1/4 Corner for Section 10

Set - 5/8" x 30" I.R. with Alum. cap marked T 30 S R 7 W C 1/4 S10 PLS 418 1978.

BT's - A 7" White Fir, S.40°W., 33.0 ft. marked C1/4 S10 BT.

A 8" D. Fir, N.42°W., 30.0 ft. marked C 1/4 S10 BT.

12/78

Center 1/4 Corner to Sec. 3

Set - 5/8" x 40" Iron rod with Alum. Cap

BT's - 6" Fir bears S.72°W., 10.9 ft.

6" Fir bears N.05°E., 7.4 ft.

122

Burton W. Holt
For: Sun Studs
Dec. 1978
M 74 - 66

Howard W. Johnstone
For: Rsbg. Lumber Co.
Sept. 1980
M 86 - 3

R. B. Kimberling
P. L. Earle
Doug. Co. Surveyors Office
April 5, 1978
C.S. 59/46

R. B. Kimberling
P.L. Earle
F.C. Silagy
Doug. Co. Surveyors
Office
April 4, 1978
S. 59/46