

Douglas County Surveyor's Record of  
Government Corners Renewed

T 30

T. S.

R 7

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

Howard Johnstone  
L.S. #498  
For: Roseburg Lumber  
Company  
Sept. 24, 1984  
M 97 - 50

Section corner for Secs. 32 and 33 only, South boundary. Ren. #100 **136**  
Found - Mound of stones but no brass cap and iron pipe.  
30" pine, N.59°W., 75.2 ft. snag.  
6" oak, N.87°E., 130.0 ft. rotted  
10" oak, N.25°E., 128.6 ft. good.  
Set - 5/8" x 18" iron rod and alum. cap in stone mound. Cap mkd. "LS 498".

Howard Johnstone  
L.S. #498  
For: Rsbg Lumber M97-61

Section corner for Secs. 34 and <sup>33</sup>~~35~~; and Secs. 3 & 4 of T.31-7 **137**  
Found - 1918 GLO brass cap/iron pipe.  
10" myrtle N.10 1/2°W., 12.9 ft. Face rotten  
12" madrone, N.41°E., 46.9 ft. Face open.  
18" fir, S.70°E., 32.1 ft. Snag  
14" fir, S.86°W., 24.7 ft. Down Ren. #105  
8" oak, S.71°W., 42.8 ft.  
New BT - 7" fir, S.57°E., 14.5 ft.

10/22/84

Douglas County  
Surveyors Office  
Randall Smith  
Stephen Flause  
Feb. 2, 1990  
C.S. 64/5

1/4 Corner for Section 18; and Sec. 13 of T.30-8 **138**  
Found - A 1962 Douglas Co. 2 1/2" dia. brass cap on a 1 1/4" O.D. iron  
pipe protrudes 14" above ground. Cap is erroneously stamped  
with reverse ranges. Ren. #42  
11" now 24" dia. D. fir with a previously opened blaze scribing  
visible "4S" bears S.44°E., 15.8 ft. (agrees w/rec.) Orig. BT.  
10" now 13" dia. madrone snag, no blazes or marks, is tagged  
with a yellow BLM tag (15.2 ft. dist. N.26°E., T.30S R8W S13  
post by CS 7/62). We open tree in two places no blazes  
or scribing found. A cat road running NW-SE is along westerly  
side of tree. This tree has been recorded as an orig. BT in  
previous records. We have some doubt about it being original,  
tree bears S.23°W., 15.2 ft.  
7" now 7" dia. D. fir with a partially healed single blaze,  
scribing visible "1/4 S13 BT" bears N.77 3/4°W., 4.6 ft. (Rec.  
N.80°W., 4.3 ft.) 1987 BLM D. resurvey BT  
Set - Erroneously stamped ranges are stamped out and correct marks are  
added to brass cap. Cap now reads: COUNTY SURVEYORS OFFICE  
T 30 S R  
R S13 | S18 R  
8 7  
W 1/4 W  
1962  
New BRs - 9" dia. D. fir double blazed and scribed "1/4 S13 CS BT"  
bears N.33°W., 12.0 ft.  
7" dia. D. fir double blazed and scribed "1/4 S18 CS BT" bears  
N.52 1/2°E., 4.4 ft.  
Corner lies at the edge of a NE-SW cut line.

2/2/90

SEE NEXT PAGE