T 30 T.S. R 7 R.W.M.

FORE-CHAPMAN CO., EUGENE, ORE. 81991

139

Douglas County
Surveyors Office
Randall Smith, Deputy
Stephen Flause
Wit: Hilary Simmons
John Pike
May 3, 1991
C.S. 64/15

Section Corner for Secs. 13 and 24; and 18 & 19 of T.30-6
Found - A 3¼" dia. 1973 BLM brass cap on a 2½" O.D. iron pipe protruding 12" above ground.
23" now 38" dia. 40 ft. high dead B.Oak snag with an opened blaze marks "S" visible bears N.76°E., 48.0 ft. (Rec. N.70°E., 46.2 ft.) Orig. BT.
15" now 36" dia. 12" high B.Oak stump with possible lower blaze, bears S.47°E., 79.6 ft. (Rec. S.50°E., 80.5 ft. dist. is a slope measurement) Orig. BT.
24" now 48" dia. 4 ft. high B.Oak stump with a "V" open rotted blaze bears S.62°W., 215.8 ft. (Rec. S.60°W., 215.8 ft.) Ori
25" now 26" dia. Ponderosa Pine with partially healed double blaze illegible scribing visible, bears N.51°W., 3.6 ft. (agrees with record.) Ren. No. 46
20" now 19" dia. 17 ft. high Ponderosa Pine snag with partiall healed double blaze, illegible scribe ;marks visible bears S.29½°W., 55.8 ft. (Rec.S.28°W., 58.0 ft. dist. is a slope measurement.) Ren. No. 46
NE BT from Ren. No. 46 is gone.
New BTs - 5" dia. D. fir double blazed and scribed "T30S R7W S24 CS BT" bears S.45½°W., 11.7 ft.
5" dia. D. fir, double blazed and scribed "T30S R6W S18 CS BT". bears N.40°E., 9.0 ft.
5" dia. D. fir double blazed and scribed "T30S R6W S19 CS BT" bears S.66½°E., 52.2 ft.

5/3/91

140

Douglas County Surveyors Office
Randall Smith - Stephen Flause
December 19, 1991
C.S. File 64/21

1/4 Corner Section 6; and Sec. 31 of T.29½-7
Found - 2½" dia. 1924 GLO brass cap on a 1" O.D. Iron pipe, protrudes 6" above ground.
12" down and rotted 14" Chinquapin, root hole bears S.15°E., 27.8 ft. (agrees w/rec) Orig. BT
22" now 20" dia. 1½ ft. high rotted D.Fir stump, with a rotted blaze, bears N.4°W., 21.8 ft. (agrees w/rec) 1024 BT
17" now 21" dia. W.Fir with a partially healed double blaze, illegible scribing visible, bears S.32°E., 36.2 ft. (Rec. S.32°E., 32.6 ft. error in rec.?) Ren. No. 33
7" now 10" diad Chinquapin with a fully healed double blaze, bears N.34°W., 11.3 ft. (agrees w/rec) Ren. No. 33
6" dia. D.Fir with a partially healed pitched over blaze, bears N.68°E., 11.3 ft. (tag reads N.68°E., 12.0 ft. dist. to center of trunk) Unrecorded 1988 BLM
New BTs -18" R.Cedar, double blazed and scribed "1/4 S31 CS BT" bears N.62½°W., 17.6 ft.
6" D.Fir double blazed and scribed "1/4 S6 CS BT" bears S.40°W., 17.0 ft.

12/20/91

141

Section Corner for 3 and 2; and 34 and 35 of T.29-7
Found - A 3½" dia. 1924 GLO brass cap on a 3" O.D. Iron pipe protrudes 14" above ground.
16" now 27" dia. D.Fir with a fully healed double blaze, bears N.52½°E., 44.9 ft. (Rec. N.54°E., 44.9 ft.) 1924 BT
1924 GLO S.75°E., 27.7 FT is gone.
8" now 11" dia. 2 ft. high Cedar stump, tree is down along side stump, scribing visible "R7" bears S.26°W., 13.9 ft. (agrees with record) 1924 GLO BT
30" now 36" dia. D.Fir with a fully healed double blaze, bears N.27½°W., 56.8 ft. (agrees w/rec) 1924 BT.
6" now down and rotting 6" D.Fir with illegible scribing visible bears N.34°E., 25.1 ft. (agrees w/rec.) Ren. No. 37
13" now 12" dia. 7 ft. high D.Fir stump with a fully healed single blaze, bears S.51°E., 13.9 ft. (Rec. S.54°E., 45.9 ft.) (tagged by B. Moyer in 1958, tag reads N.24½°E., 21 lks.) Unsure of reason for bad brgs and dist.) 1964 GLO
8" now 13" dia. W.Fir with a fully healed single blaze bears S.36°W., 25.5 ft. (Rec. S.36°W., 26.1 ft. dist. to center of trunk.) 1964 GLO BT
New BT - 8" D.Fir double blazed and scribed "T29S R7W S35 CS BT" bears N.43°E., 8.4 ft.
Cor. lies at the intersection of a south and east running cut lines, clear-cut to the southeast. Approx. 125 ft. north of a gravel road.

12/19/91