

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S T. S. R. 7 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97501

Mark Smalley LS # 2534  
For: Roseburg Resources  
May-July 1992  
M 112 - 52

Mark Smalley  
For: Roseburg  
Resources Co.  
April 1993  
C.S. 63/153

Ronald Quimby  
L.S. 1654  
For: Roseburg  
Resources  
3/94  
M 119-21

1/4 Corner for Sections 35 & 36 142  
Found - 1964 Brass Cap With iron Pipe properly marked.  
BT's Found - See Renewal # 84.  
8" Oak bears S.21 3/4°E., 21.8 ft. healed face.  
14" Oak bears N.85°W., 31.7 ft. down  
6" Oak bears N.67 1/2°W., 33.3 ft. stump.  
9" Oak bears S.62 3/4° W., 17.2 ft. stump  
New BT- 7" Oak bears N.23°W., 12.7 ft. scribed "1/4 S35 BT"  
- - - - - 7/92 - - -

1/4 Corner for Sections 25 and 36. 143  
Found - 1971 Cadastral Brass cap and iron pipe.. See Re1. # 72  
BT's Fnd -  
30" Laurel bears N.28°W., 143.9 ft. stump.  
18" Pine bears S.10°W., 3.6 ft. stump.  
New BT's -  
13" Fir bears N01°W., 37.5 ft. scribed "1/4 S BT"  
9" Madrone bears S. 13°E., 51.5 ft. scribed "1/4 S BT"  
- - - - - 7/92 - - -

Center 1/4 Corner for Section 36. 144  
Set - 5/8" x 48" iron rod and alum. cap  
New BT's -  
12" Fir bears S.71°E., 6.9 ft. scribed "C 1/2 S36 BT"  
27" Fir bears N.30°E., 12.0 ft. scribed "C 1/2 S36 BT"  
14" Myrtle bears S.9°E., 22.3 ft. scribed "C 1/2 BT"  
16" Fir bears N.14°W., 30.7 ft. scribed "C 1/2 BT"  
- - - - - 7/92 - - -

1/4 Corner for Section 36 and Section 31 of T.30-6 145  
Set - 5/8" x 48" iron rod and alum. cap  
New BT's -  
9" Madrone bears N.41°W., 22.8 ft. scribed "1/4 S36 BT"  
18" Pine bears S.88°E., 56.5 ft. scribed "1/4 S31 BT"  
18" Pine bears N.81°W., 45.2 ft. scribed "1/4 S36 BT"  
7" Pine bears N.06°E., 13.3 ft. scribed "1/4 S BT"  
- - - - - 7/92 - - -

Section corner to sections 21,22,27, & 28. 146  
Found - Brass cap with iron pipe.  
Fir, 10", N. 23 1/2°W., 19.1', snag, scribe visible.  
Fir, 22", N.58°E., 23.1', snag, with tag.  
Fir, 6", S.50°E., 14.2', down - rotted  
Fir, 6", S.25 1/2°W., 16.8', down - rotted.  
W. Fir, 14", S.57 1/2°E., 28.4, Good condition, Healed blazes with tag.  
New BT's -  
D. Fir, 14", N.64°E.,66.3', scribed "S. 22 BT", with tag.  
D. Fir, 5", S.58°W., 33.5', scribed "S.28 BT", with tag.  
Pine, 5", N.26°W., 36.2', scribed "S. 21 BT", with tag.  
Note - Steel fence posts were set on line from this corner east to the  
1/4 corner to sections 22 and 27.  
Corner lies 200' south of Rd. #27.0, and 450' west of Rd. #28.1.  
- - - - - 4/93 - - -

Center 1/4 Sec. 34 147  
Set - 5/8"x30" iron rod with 3 1/4" aluminum cap mkd:  
T30S R7W  
C 1/4 -|- S34  
RLS 1654  
1994  
New BTs-  
4" Cedar bears N.1°W., 31.7', scribed "XBT"  
10" Pine bears S.10°W., 88.7', scribed "C 1/4 S34 BT"  
31" Pine bears N.85°W., 7.7', scribed "C 1/4 S34 BT"  
18" Pine bears S.56°E., 29.4', scribed "C 1/4 S34 BT"