

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S.T.S. R. 7 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97401

Douglas County Surveyor's Office
Randall Smith, Stephen Flause
Nov. 2, 1994
C.S. File 64/52

Mark F. Smalley
For: Weyerhaeuser Co.
Feb. 1995
M 121 - 59

148

1/4 Corner for Section 2 & Section 35 of T.29-7.

Found - 1 1/2" O.D. axle with a 5" dia. flange on top, protrudes
6" above ground. (1956) See Renewal #22.

Accessories Found:

6" dia. now rotted Madrone remains of indeterminable
size, bears S.60°E., 30.4 ft. (1871)

No remains of NW 1871 BT found.

42" now 44" down Madrone with a partially healed burnt
blaze, bears N.50°E., 42.5 ft. to root hole, (1956)

9" now 22" dia. D.Fir with a fully healed double blaze,
bears S.16 1/2°E., 41.8 ft. (rec. S.18°E., 41.8 ft.
(1956)

New Accessories -

9" dia. D.Fir double blazed and scribed "1/4 S2 CS BT"
bears S.37°W., 17.2 ft.

6" dia. D.Fir double blazed and scribed "1/4 S35 CS BT"
bears N.11°E., 23.2 ft.

10" dia. I.Cedar double blazed and scribed "1/4 S35 CS BT"
bears N.56°W., 10.6 ft.

Note - Existing monument is good and stable on a fairly
steep easterly slope, did not want to disturb ground to
set a BC/IP. Remains of a down fence line visible south
of corner.

149

1/4 CORNER 1 & 12

Found - 1964 County brass cap & Iron pipe
72" fir, N.50°E. 15.8', bark scribe original BT.

15" fir, N.20°E. 41.8', healed.

28" oak, S.40°W. 18.5', healed original BT.

16" fir, S.2 1/2°E. 31.6', stump.

Scribed- 6" fir, N.44°W. 9', "1/4 S BT".

1/4 CORNER 11 & 12

Found - 1964 County brass cap & Iron pipe

30" cedar, N.43°W. 39.7', healed.

16" oak, N.51°E. 101.7', center rotten.

18" oak, S.28°E. 19.8', face rotten original BT.

14" fir, S.25°W. 24.5', snag.

Scribed- 11" cedar, S.60°E. 13.6', "1/4 S BT"

17" fir, S.29°W. 22.3', "1/4 S BT"

150

C 1/4 CORNER SEC. 12

SET - 5/8 X 48" Iron rod & Aluminum cap mkd. LS 2354

Scribed- 11" fir, N.49°W. 12.7', "C 1/4 S BT"

12" cedar, N.27°E. 5.3', "C 1/4 S BT"

9" cedar, N.69°E. 17.4', "C 1/4 S BT"

10" fir, S.1°E. 9.7', "C 1/4 S BT"

151

1/4 CORNER 12 & 7 OF T30-6

FOUND - 1963 County brass cap & Iron pipe

28" fir, N.33°E. 6.8', healed

14" fir, S.18°W. 15.3', healed

SCRIBED- 7" cedar, N.41°W. 18.5', "1/4 S BT"

22" fir, S.78°E. 21.2', "1/4 S BT"

152

SEC. CORNER 12, 13 & 7, 18 OF T30-6

FOUND - 1960 County brass cap & Iron pipe

17" fir, N.18°W. 43.4', healed

20" fir, N.20°E. 15.5', stump

14" fir, S.29°E. 26.8', healed

10" fir, S.23°W. 17.8', healed down

SCRIBED- 12" fir, S.89°W. 24.5', "S 13 BT"

153