

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 T. S. R 8 R. W. W. M.

HOSE-CHAPMAN CO., EUGENE, ORE. 21881

22

1/4 Corner common to Sections 23 and 26.
Set - Found - 1" x 30" Iron Pipe on north side of stump
Found - 12" Fir with 1/4 S on north face, now a stump.
27" Fir N. 1 1/2° E. 49.7 ft., now a badly burned stump, its REN. #9
scribe not discernible, rescribed this stump, 1/4 S BT S23.
Fir S. 50° W. 96.1 ft. is now a stump, scribe in good condition.
Note: This corner falls in the middle of a logging unit and there are
no standing trees for new bearing trees.

RE-PAVED, SEE CORNER NO. #113

23

1/4 Corner to Sections 14 and 23.
Found - 12" Cedar N. 25° E. 9.9 ft., down, scribe visible.
Set - 1" x 36" Iron Pipe
5" W. Fir S. 70° W. 55.8 ft. 1/4 S 23 BT.
13" D. Fir N. 80 1/2° E. 23.0 ft. 1/4 S 14 BT.

Sec. Cor. Comm to Secs. 13 - 24, T30-8W. & Sec. 18 & 19, T30-7W.
Could not locate the Original Corner Stone.
Found - 8" Fir N. 72° W. 9.9 ft.
17" Fir N. 38° E. 34.3 ft.
Set - 1" x 30" Iron Pipe in Stone Mound
12" Fir S. 69 1/2° E. 53.0 ft.
15" Fir S. 37° W. 68.5 ft.

24

Section Corner for Sections 13 - 14 - 23 - 24.
Found - 10" Fir S. 20° W. 12 lks. (dying)
10" Fir N. 43° W. 13 lks. (dying)
8" Fir S. 52° E. 22 lks. (snag)
11" Live Oak N. 38° E. 11 lks. (good)
Set - 1 1/2" by 24" Iron Pipe.
Scribed - 16" Cedar N. 59° W. 29.4 feet.
7" D. Fir S. 74 1/2° W. 54.0 feet.
12" Cedar S. 59 1/2° E. 31.0 feet.

CORNER NO. 152

25

1/4 Corner between Sections 23 and 24.
Found - 10" Fir S. 45° W. 15 lks. (scribe visible)
Set - 1" by 24" Iron Pipe
Scribed - 14" D. Fir N. 13° W. 28.6 feet.
8" Chinquapin S. 23° E. 30.6 feet.

27

1/4 Corner between Sections 24 and 25.
Found - 12" Fir S. 80° E. 17 lks. (good)
10" Fir N. 9° W. 36 lks. (down)
Set - 1" by 24" Iron Pipe
Scribed - 16" W. Fir S. 62° E. 27.0 feet.
22" D. Fir N. 62 1/2° W. 56.3 feet.

CORNER NO. #150

28

1/4 Corner between Sec. 24, T30-8W. & Sec. 19, T30-7W.
Found - 40" Fir is corner mkd. on west face (good)
36" Fir N. 48° E. 68 lks. (down)
14" Fir N. 80° W. 36 lks. (burned, no visible scribe)
Set - 1 1/2" by 24" Iron Pipe
Scribed - 6" D. Fir N. 68° E. 65.4 feet.
20" D. Fir S. 7° E. 41.0 feet (no trees in the west to scribe)

29

Section Corner for Sections 10 - 11 - 14 - 15.
Found - Original Corner Stone & Set - 1/2" by 30" Iron Pipe.
Scribed - 24" Cedar S. 19° E. 69.0 ft. - 6" D. Fir S. 52 1/2° W. 28.3 feet.
18" D. Fir N. 84° E. 108.0 ft. - 48" D. Fir N. 43° W. 23.0 ft.
The N. 43° W. tree is Orig. BT. but wasn't recorded, bark scribe)

30

1/4 Corner between Sec. 18, T30-8W. & Sec. 13, T30-9W.
Found - W. Oak S. 35° W. 45.5 ft. (down, no visible scribe)
12" W. Oak N. 42° E. 23.8 ft. (down, scribe visible)
Set - 1" by 36" Iron Pipe & Scribed - 16" D. Fir S. 43° W. 40.0 feet.
6" D. Fir N. 55° E. 9.7 feet.

FD OK 1/88
H. JOHNSTONE
M 106-51

31

Howard W. Johnstone
For Roseburg Lumber Co.
Wit: R. Henrickson & J. Clark
Sept. 15, 1961
C. S. File No. 51/163

Howard W. Johnstone
For Roseburg Lumber Company
May 28 1962
C. S. File No. 51/163