

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 S. T. S. R 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97101

Renew S36 T29-8W 32
T30-8W S 1 / S 6 T30-7W
Found - Cedar S.56°E. 17.5 ft. - Both Trees had been previously
Cedar N.27°E. 31.0 ft. opened. Found old axe work on
S.E. tree, but scribing had rotted. Evidence of corner being used.
Corner also checks bearing & distance from 36, 31 & 6. (7.08 chs.)
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1962 R8W S36 R7W
S 1/S 6
Rescribed O.BT: 36" Cedar S.56°E. 12.5 ft. T30S
Mkd: T30S R7W S6 CS BT.
New BT's: 14" Hemlock N. 1°E. 10.7 ft. T29SR8W S36 CS BT.
14" Cedar S.71½°W. 21.4 ft. T30S R8W S 1 CS BT.

James W.
Byron &
Crew
June 21, 1962
C.S. File
No. 49/139

¼ Corner to Sec. 13, T30-8W. & Sec. 18, T30-7W 33
Found - Both Original Bearing Trees as recorded. #138
S. E. BT. previously opened, shows good scribing "¼ S".
Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1962
¼ R8W S13/S18 R7W T30S
Note - Both Bearing Trees in good condition. We do not scribe new BT's.
July 6, 1962

¼ Corner to Sec. 12, T30-8W. & Sec. 7, T30-7W. 34
Found - Orig. 8", now 12" Laurel N.75°W., not S.75°W. 19.1 ft.
(We open & find good scribing.
Orig. 20", now 30" Laurel N.29°E. 7.3 ft., center rotted, no scbng.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
¼ R8W S12/S 7 R7W T30S
New BT's: 7" R.Fir bears N.58°W. 17.3 ft. scribed ¼ S12 CS BT.
12" R.Fir bears S.16°E. 15.2 ft. scribed ¼ S 7 CS BT.

Fd. B.C. 7/72
B.C.M. ADMIN. SURVEY
SEE G.I.S. FILE

Sec. Cor. to Secs. 25 & 36, T30-8W. & Secs. 30 & 31, T30-7W. 35
Found - GLO Brass Cap at Cor. & All BT's., as recorded, except
S. E. BT., now snag.
New BT: 7" Laurel bears S.14½°E. 17.2 ft. scribed S31 T30S R7W CS BT.

¼ Cor. to Sec. 25, T30-8W. & Sec. 30, T30-7W. 36
Found - Both Orig. BT's. as follows:
Orig. 10", now 18" Fir Snag S.72°E. 14.5 ft., open & fd. good scrbng.
Orig. 18", now 26" R.Fir N.64°E. 14.5 ft., shows good scars.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
¼ R8W S25/S30 R7W T30S
New BT's: Rescribe 26" R.Fir N.64°W. 15.5 ft., bark scribe, CS .
14" R.Fir bears S.72°E. 40.6 ft. scribed ¼ S30 CS BT.

¼ Corner to Sec. 1, T30-8W. & Sec. 6, T30-7W. 37
Found - Orig. 36", now 56" Fir S.40°E. 5.3 ft., shows good bark scribing.
Orig. S. W. BT., not found.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
¼ R8W S 1/S 6 R7W T30S
New BT's: Rescribe, now 56" Fir S.40°E. 6.8 ft., bark scribe ¼ S6 CS BT.
14" W. Fir bears N.53°W., scribed ¼ S 1 CS BT.
Note - Corner about 75 ft. N. of small stream & 30 ft. W. of Log. Road.

Sec. Cor. to Secs. 1 & 12, T30-8W. and Secs. 6 & 7, T30-7W. 38
Found - All Orig. BT's., Orig. 15", Pine S.24°E. 36.3 ft., shows good scrbng.
Orig. 24", now 32" Cedar N.64°E. 34.3 ft., shows good scribing.
N. W. BT., now remains of stump. S. E. BT., now down.
Note - Corner is at foot of 10 ft. high bluff.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964 R8W S 1 | S 6 R7W
S12 | S 7 T30S
New BT's: 8" R.Fir bears S.26°E. 66.0 ft. scribed S7 T30S R7W CS BT.
14" R.Fir bears N.72°W. 55.6 ft. scribed S1 T30S R8W CS BT.

James W. Byron, Deputy
Mike Darby and Jim Halterman

February 1964
C. S. File No. 53/40

Fd B.C.
BTS-7/72
SEE B.C.M.
ADMIN. SURVEY
G.I.S. FILE