

Douglas County Surveyor's Record of  
Government Corners Renewed

T. 30 S. T. S. R. 8 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

(continued)

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R8W  $\frac{1}{4}$  S 9  
Office, 1964 SL6

New BT's: 20" Cedar N.11°W. 41.4 ft. Mkd:  $\frac{1}{4}$  S9 CS BT.  
40" Cedar S.85°E. 26.4 ft. Mkd:  $\frac{1}{4}$  SL6 CS BT.

Note - This corner lies on the west side of small creek 7.0 ft. East.

$\frac{1}{4}$  Corner to Sections 10 and 15. 47

Found - 2" x 2" x 4' sq. Post & 14", now 24" Laure North 16.5 ft.,  
shows faint "T" Scribe.

10" Laurel S.54°W. 15.8 ft., down & mostly rotted away,  
found ">" reverse scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R8W  $\frac{1}{4}$  S 10  
Office, 1964 S 15

New BT's: 6" D.Fir N.16°W. 38.1 ft. Mkd:  $\frac{1}{4}$  S10 CS BT.  
16" D.Fir S.39°E. 17.5 ft. Mkd:  $\frac{1}{4}$  S15 CS BT.

Section Corner to Sections 4 - 5 - 8 - 9. 48

Found - 26", now 38" Orig. Cedar N.20°E. 19.8 ft., opened & shows,  
"30S R8W S4" scribed.

No trace of other BT's. Cedar has fire scars.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R8W S 5 | S 4  
Office, 1964 S 8 | S 9

New BT's: 9" D.Fir N. 7° W. 15.0 ft. Mkd: T30S R8W S5 CS BT.  
11" D.Fir N.43°E. 18.4 ft. Mkd: T30S R8W S4 CS BT.  
12" D.Fir S.40°E. 5.1 ft. Mkd: T30S R8W S9 CS BT.  
10" D.Fir S.50°W. 7.8 ft. Mkd: T30S R8W S8 CS BT.

Sec. Corner to Secs. 19 & 30, T30-8W & Secs. 24 & 25, T30-9W. 49

Found - Orig. 20", now 40" D.Fir S.66°E. 29.7 ft., shows very old bark  
scribe "3S R8W S" & BT scar.

Orig. 6", now 30", W.Fir S.32°W. 17.8 ft. Did not open.

Orig. 12", now 22" D.Fir N.42°E. 73.9 ft., shows good scar.

Did not open.

Orig. 24", now 48" D.Fir N.15°W. 80.5 ft., shows faint bark scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S S 24 | S 19  
Office, 1964 R9W S 25 | S 30 R8W

New BT's: 13" D.Fir N.44°E. 10.5 ft. Mkd: T30S R8W S19 CS BT.  
11" W.Fir N.39°W. 32.3 ft. Mkd: T30S R9W S24 CS BT.  
30" W.Fir S.32°W. 17.8 ft. Mkd: T30S R9W S25 CS BT.  
9" Yew S.43°E. 30.6 ft. Mkd: S 30 CS BT.

Filed C. S. 53/53

$\frac{1}{4}$  Corner to Sec. 30, T30-8W. & Sec. 25, T30-9W. 50

Found - Original BT., 8", now 14" Fir S.3°E. 8.6 ft. Open & find  
"BT" scribe.

40", now 52" Fir North 37.0 ft. (snag). This is line tree.  
No trace of Oak BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964  
T30S R9W  $\frac{1}{4}$  S 25/S 30 R8W

New BT's: 11" W.Fir S.25°E. 5.3 ft. Mkd:  $\frac{1}{4}$  S30 CS BT.  
12" D.Fir S.23°W. 18.5 ft. Mkd:  $\frac{1}{4}$  S25 CS BT.

Oct. 21, 1964 C.S. 53/53

Section Corner to Sections 8 - 9 - 16 - 17. 51

Found - Orig. 6", now 15" W. Fir N.55°E. (recorded N.65°E.) 37.0 ft.,  
shows good scars.

Orig. 14", now 15" Cedar Snag S.46°E. 17.8 ft., shows scribe.

Orig. 18", now 24" D.Fir S.15°W. 17.8 ft., shows bark scribe.

Orig. 20", now 30" D.Fir N.55°W. 32.3 ft., shows scribe (bark).

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R8W S 8 | S 9  
Office, 1965 S17 | S16

New BT: 8" W.Fir S.25°E. 34.7 ft. Mkd: T30S R8W S16 CS BT.  
Rescribed: 15" W.Fir N.55°E. 37.0 ft. Mkd: T30S R8W S9 CS BT.  
24" D.Fir S.15°W. 17.8 ft. Mkd: T30S R8W S17 CS BT.  
30" D.Fir N.55°W. 32.3 ft. Mkd: T30S R8W S8 CS BT.

7/73 - FD. O.K. V.R.T. C.S. 56/34  
STRAIGHTEN & RESET BRASS CAP.

March 24, 1965  
C.S. File 53/67

Vernon "Rag" Tracy  
Mike Darby and Jack Barnett  
September 1964  
C. S. File No. 53/67