

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 8 W. R.W.W.M.

ROSE-CHAPMAN CO., EUGENE, ORE. 21881

52

$\frac{1}{4}$ Corner to Sections 13 and 14.
Found - $\frac{3}{4}$ " I. Pipe & one Orig. BT: (No record of I. Pipe)
Orig. 18", now 40" Cedar, Down, N.30°W. 11.9 ft., prev. opened
& face burned. We open lower & find "BT" scribe.
Other BT's. gone, we find stump hole at correct bearing &
distance.
Set - Brass Cap at Corner Mkd: County Surveyor's Office, 1965
T30S R8W $\frac{1}{4}$ S14/S13
New BT's: 6" W.Fir N.45°E. 100.9 ft. Mkd: $\frac{1}{4}$ S13 CS BT.
9" Pine N.71 $\frac{1}{2}$ °W. 181.5 ft. Mkd: $\frac{1}{4}$ S14 CS BT.
Note - This corner lies in logged area approximately 500.0 ft. N.
of edge of timber course E. & W.

53

$\frac{1}{4}$ Corner to Sections 9 and 10.
Found - 14", now 28" Fir S.62°E. 8.6 ft., " $\frac{1}{4}$ S BT" bark scribe.
5", now 6" Chinquapin West 22.4 ft., mostly rotted away, found
partial face with possible reverse scribe "1".
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S R8W $\frac{1}{4}$ S 9/S 10
New BT's: 8" D.Fir S.38°W. 32.0 ft. Mkd: $\frac{1}{4}$ S 9 CS BT.
16" D.Fir S.26°E. 36.8 ft. Mkd: $\frac{1}{4}$ S10 CS BT.

54

Section Corner to Secs. 3 - 4 - 9 - 10. (Witness Corner)
Found - 60", now 62" Corner Tree alive with bark scribe "T30S R8W S3"
on NE side & "S" bark scribe on N.W. side.
No Orig. BT's. remain.
Set - Brass Cap at Cor. 10 ft. S. for Wit. Cor. & Mkd:
County Surveyor's Office, 1965 T30S W.C. 10 ft. N.

S 4	S 3
S 9	S10

 R8W
New BT's: 8" D.Fir East 55.5 ft. Mkd: W.C. T30S R8W S3 CS BT.
13" Chinq. N.45°W. 44.4 ft. Mkd: W.C. T30S R8W S4 CS BT.
12" W.Fir S.63°W. 26.5 ft. Mkd: W.C. T30S R8W S9 CS BT.
8" Hemlock S.35°E. 38.5 ft. Mkd: W.C. T30S R8W S10 CS BT.

55

$\frac{1}{4}$ Corner to Sections 2 and 1.
Found - Orig. 14", now 22" Cedar S.48°E. 13.2 ft., shows good scar. Didn't open.
Orig. 18", now 31" D.Fir S.60°W. 9.2 ft., shows old "BT" bark scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S $\frac{1}{4}$ S 2/S 1 R8W
Remarked Orig. BT's: 22" Cedar S.48°E. 13.2 ft. Mkd: $\frac{1}{4}$ S1 CS BT.
30" D.Fir S.60°W. 9.2 ft. Mkd: $\frac{1}{4}$ S2 CS BT.
Note - This corner lies on very steep N.W. clope of ridge, Brass Cap
is set in mound of stone.

56

Section Corner to Secs. 15 - 16 - 21 - 22.
Found - Orig. 24", now 32" Pine N.50°E. 6.6 ft., sign of faint scar.
Orig. 10", now 12" Pine Snag S.70°E. 7.9 ft., recorded S.60°E.,
Open & shows "T3 S BT".
Orig. 10", now 12" Laurel S.64°W. 20.5 ft., shows good scar, &
"T S" on face.
Orig. 14", now 26" Pine N.24°W. 26.4 ft., shows "RS scribe on face.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965 T30S R8W

S 16	S 15
S 21	S 22

Orig. 32" Pine N.50°E. 6.6 ft. Mkd: T30S R8W S15 CS BT.
New BT: 12" D.Fir S.45°E. 21.0 ft. Mkd: T30S R8W S22 CS BT.

57

Section Corner to Sections 22 - 21 - 28 - 27.
Found - Orig. 8", now 10" Fir N.33°E. 7.2 ft., tree face down & dead,
scribe visible on opened face.
Orig. 8", now 16" Fir S.25°W. 18.5 ft. (alive) very old Bark
scribe visible "W T & part of S".
Orig. 14", now 33" Fir N.71°W. 11.9 ft. (alive) shows "T $\frac{3}{4}$ R8W S2",
bark scribe.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965 T30S R8W

S 21	S 22
S 28	S 27

(continued over)

Vernon "Ray" Tracy,
Mike Darby & Jack Barnett
April 1965
C. S. File No. 53/67

Fd B.C. 26875
1976 - BLM ADMIN.
SURVEY - SEE
GIS FILE.

Fd B.C. 3875
BLM ADMIN. SURVEY
SEE GIS FILE

SEE CORNER INFO #139