

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 8 W. R.W.W.M.

KOKE-CHAPMAN CO. EUGENE, ORE. 21881

85

1/4 Corner to Sections 7 and 8.
1/4 Corner set at proportionate distance.
Set - 1" x 30" I. Pipe set at the point for the corner, from which:
BT's: 8" White Fir bears N. 36° 08' 12" W. 8.4 ft. mkd. 1/4 S 7 BT.
8" White Fir bears N. 87° 33' 43" E. 7.5 ft. mkd.

86

1/4 Corner to Sections 5 and 8.
Set at proportionate distance.
Set - 1" x 30" Galv. I. Pipe at the point for the corner, from which:
BT's: 7" White Fir bears N. 38° 48' 56" W. 21.09 ft. mkd. 1/4 S 5 BT.
18" Cedar bears S. 48° 41' 14" E. 25.5 ft.

87

1/4 Corner to Sections 8 and 9.
Set at proportionate distance.
Set - 1" x 30" Galv. Iron Pipe, from which:
BT's: 9" White Fir bears N. 55° 54' 11" W. 22.3 ft. mkd. 1/4 S 8 BT.
7" White Fir bears N. 42° 36' 39" E. 29.0 ft. mkd. 1/4 S 9 BT.

MICROFILM TO HERE 10/67

88

1/4 Corner to Sections 28 and 33. (Witness Corner).
Found - 1963 BLM Brass Cap, properly marked.
16" D. Fir, now 16", N. 54° W. 70.6 ft. scribe visible "1/4 S28 BT".
20", now 20" D. Fir, S. 71° E. 68.6 ft., pitched over, scribing visible.
A road is to be built over 1/4 corner, therefore, set Witness Corner:
Original Corner at Road Sta. 141+03.96.
Set - Brass Cap at Wit. Cor. Mkd: County Surveyor's T 30 S R 8 W
Office, 1968 W. C.
Placed BLM Brass Cap by 1968 CS B.C.) 60' East To: 1/4 S 28 S 33
New BT's: 10" Hemlock N. 81° W. 17.9 ft. mkd. W.C. 1/4 S28 CS BT.
15" D. Fir S. 27° W. 25.2 ft. mkd. W.C. 1/4 S33 CS BT.
7/73 FOUND O.K. VRT. C.S. 56/34

89

Sec. Cor. to Secs. 30 & 31, T30-8W. and Secs. 25 & 36, T30-9W. #134
Found - Orig. 15", now 28" Fir, alive, N. 47° W. 24.4 ft., open & scribe visible.
Orig. 30", now 54" Fir, alive, S. 1 1/2° W. 356.4 ft., open & scribe visible.
Orig. 15", now 30" Pine, alive, N. 25° E. 57.4 ft., open & scribe visible.
No trace of S. E. BT.
Set - Brass Cap at Cor. Mkd: County Surveyor's R T 30 S R
Office 1968 9 S 25 S 30 8
W S 36 S 31 W
New BT's: 9" D. Fir S. 52° E. 16.2 ft. mkd. T30S R8W S31 CS BT.
11" W. Oak N. 65° E. 34.2 ft. mkd. T30S R8W S30 CS BT.
8" W. Oak N. 10° W. 30.0 ft. mkd. T30S R9W S25 CS BT.
8" D. Fir S. 82° W. 26.6 ft. mkd. T30S R9W S36 CS BT.
This corner lies on steep, southwest slope. 8/15/68

90

1/4 Corner to Sec. 31, T30-8W. and Sec. 36, T30-9W.
Found - Orig. 15", now 36" Fir, alive, N. 52° W. 21.1 ft., open & shows
"B" & "1/4" bark scribe.
Find depression at the approx. location of N.E. BT. Tree gone.
Set - Brass Cap at Cor. Mkd: County Surveyor's R9W T 30 S R8W
Office, 1968 1/4 S 36 S 31
New BT's: 7" Hemlock N. 36° E. 16.7 ft. mkd. "1/4 S31 CS BT.
8" Hemlock S. 6° W. 13.8 ft. mkd. 1/4 S36 CS BT.
This corner lies on moderate N. E. Slope. 8/15/68

91

1/4 Corner to Sections 17 and 20.
Orig. 15", now 36" Pine, alive, N. 35° W. 31.0 ft., prev. opened, no scribe.
Orig. 6", now 9" Pine, dead, S. 54° E. 5.3 ft., scribe visible on opened blz.
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 8 W
Office 1969 S 17 S 20
New BT's: 10" D. Fir S. 28° W. 30.1 ft. mkd: "1/4 S20 CS BT".
8" W. Fir N. 22° W. 11.5 ft. mkd: "1/4 S17 CS BT".
This corner lies on gentle, S. slope in dense small fir, pine & 8/17/69

Wm. C. Stiles, (Seek, Inc.)
For Moore Mill & Lbr. Co.
June 21, 1967
C.S. File No. 55/44
M 34-19

John M.
Powell &
Crew
7/12/68
C. S.
File
No.
53/67

Vernon "Ray" Tracy
Jack Heritage & V. Perron
August, 1968
C. S. File No. 53/67

Fd 6K 9/72
BLM ADMIN.
SURVEY - SEE
GIS FILE

RE-APPROVED, SEE CORNER NO. 134