

Douglas County Surveyor's Record of
Government Corners Renewed

T 30

T. S. R 8

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

112

R. E. Stuntzner
for Reservation
Ranch
M 53 - 9
March, 1974

Center 1/4, Section 32
Set - 1 1/2" Capped Iron pipe from which:
BT's - 18" Fir, N.86°E., 20.1 ft.
18" Fir, N.15°W., 60.9 ft.

3/25/74

113

1/4 Corner for Sections 23 and 26.
Found - 12" Fir stump with possible scribed area chopped away. Also
found a 1 1/4" I.P. set on northerly edge of stump. Ren. #'s 9 and 22.
from which - 52" Fir stump bears S. 45 E., 6.0 ft. to center of stump, 3.4 ft.
to apparent face of stump. Orig. notes indicate a 46" Fir at
record measurement S. 31 E., 3.3 ft. This stump badly burnt.
27" Fir stump bears N.1 1/2 E., 50.6 ft. (Rec. N.1 1/2 E., 49.7 ft.) scrib
"1/4 S BT S23"
20" Fir stump bears S.50 W., 96.1 ft. scribed "1/4 S BT Sec. 26"
Set - We set a steel fencepost with survey marker witness sign attached
alongside corner stump.
There are no trees near.

114

Section Corner for 23, 24 26 and 25.
Found - 4"x4" scribed wood post, nearly rotted off, mkd. "S 23" on NW face;
"S 24" on NE face; "S 25" on SE face and "S 26" on SW face, with
steel fence post set alongside. Ren. #3
from which: a 28" now 32" D.Fir bears N.71 E., 43.7 ft. scribing visible on
unhealed blaze.
a 36" now 48" D.Fir bears S.21 E., 108.8 ft. (Rec. S.21 E.,
110.0 ft.) scribing visible on unhealed blaze.
We find Yew wood remains in approx. position of orig. NE BT, no
markings found.
Logging activity has destroyed all other recorded BT's for this corner.

Set - We remove the scribed cedar post and replace it with a Brass cap set
flush with the ground mkd:

COUNTY SURVEYORS	T 30 S
OFFICE	S 23 S 24
1974	S 26 S 25
	R 8 W

Reset scribed wood post and steel fence post alongside brass cap and mark the
following:

New BT - An 8" D.Fir bears N.44 W., 73.7 ft. scribed "T30S R8W S23 CS BT"
No trees near to SW. Compass declination setting 20 East.

6/26/74

115

1/4 to Sec. 28 and 29
Found A USBLM brass cap properly marked and set firmly in place.
A fir 12" dia., uprooted. Approximate standing position bears N 71°E., 5.9 ft.
Partial scribe visible in blaze.
A fir 19" dia. uprooted. Approx. standing position bears S71°W., 21.8 ft.
Partial scribe visible in blaze.
New BT's - 7" dia. white fir bears S62 1/2°W., 14.4 ft. Tree Blazed find scribed
"1/4 S29 CS BT"
12" Dia. White fir bears N26°E., 44.5 ft. Tree Blazed and scribed "1/4 S
28 CS BT"
Mag. Dec. 20°E. 1/21/76

116

Sec. corner to sec. 17, 18, 19 and 20 REN.#70
Found Brass cap at section corner stamped:

COUNTY SURVEYORS OFFICE
1965

T30S	R8W
S18	S17
S19	S20

From which Orig. 12 now 18" dia. Laurel snag bears S11°E., 38.9 ft. Snag has
been opened, no scribing visible as snag is badly decayed. (All other orig.
B.T.S. are gone)
20" now 22" dia. red cedar bears N12 1/2°E., 32.0 ft. (record N11°E., 31.5 ft.)
tree scribed "T30S R8W S17 CS BT"
15" dia. W fir is uprooted, approx. standing position is N59°W, 9.6 ft.
Tree has good blaze.
15" dia. W Fir is uprooted approx. standing position is S1°E, 19.) ft.
Tree is scribed "T30S R8W S20 CS BT"

OVER

Gary Langlitz, County Surveyors Office
Peter Earle
C.S. 56/51
June 26, 1974

L.E. Monrean
P.L. Earle
J.H. Cook
1/21/76
C.S. 59/2

JAW'S