

Douglas County Surveyor's Record of
Government Corners Renewed

T 30

T. S. R 8

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21981

118 (cont.)

(Continued from preceding page)

9" dia. D. Fir is uprooted, approx. standing position is S31°W, 23.0ft. Tree has good blaze.

New BT's A 16" dia. D. Fir bears N13°W, 63.9 ft. Tree blazed and scribed "T30S R8W S18 CS BT"

A 13" dia. D. Fir bears S66°W., 32.1 ft. Tree blazed and scribed "T30S R8W S19 CS BT"

Set spike in 48" dia. fir stump, spike bears S57°E., 92.5 ft. Stamped "BO"
Mag. Dec. 20°E 1/21/76

L.E. Monrean
P.L. Earle
J.H. Cook
1/21/76
C.S. 59/2

1/4 Corner for Secs. 22 and 23.

Found - 1965 County Brass cap properly marked. Ren. #72

Orig. 12" now 26" Chinkapin, now dead, bears N. 56°W., 29.7 ft to face. Tree has rotted blaze, no scribing visible, tagged.

Orig. 20" Fir, bears N.25°E., 22.4 ft to face. Tree is now a badly decayed stump.

14" D. Fir, uprooted, standing position, East, 12.5 ft. double blazed and scribed "1/4 S23 CS BT"

12" now 14" D. Fir, uprooted, standing position, S.68°W., 14.3 ft. Tree has double blaze, pitched over.

New BT's-9" D. Fir, bears S.35 1/2°E., 58.4 ft. Tree double blazed & scribed "1/4 S23 CS BT"

9" D. Fir, bears S.42°W., 88.1 ft. double blazed and scribed "1/4 S22 CS BT"

Mag. Dec. 20°E

3/3/76

L.E. Monrean
J. H. Cook
March 3, 1976
C.S. 59/8

118

Section Corner for Secs. 22, 23, 27 and 26

Found - 1" I.P., 12" above ground with 1958 County Brass cap. Ren. #17
The NE and NW orig. BT's have both blown down, however they appear to have stood in their proper locations.

An orig. 15" Fir, now 18" snag bears S.57°E., 13.9 ft. with scribing "8W S26 visible on previously opened blaze.

We find no trace of the orig. SW BT.

A 20", now 22" D. Fir, alive and well healed, bears S.32°E., 40.0 ft.

An 18" D. Fir, now a snag with scribing "T30S R8W S27 CS BT" visible on a double blaze bears S.57°W., 31.8 ft. Ren. #17

New BTs- A 25" D. Fir, bears S.34 1/2°W., 68.5 ft. scribed "T30S R8W S27 CS BT" on a double blaze.

A 7" Grand Fir, bears N.42°W., 86.0 ft. scribed "T30S R8W S22 CS BT" on a double blaze.

Note: The area NW of this corner has been clearcut. This cor. is located approx. 100 ft. east of the road 30-8-25 leading to Live Oak Mtn.

Com. Dec. setting: 20° east

2/18/76

Gary Langlitz
M. Lenora Ladig
A. Vic Cangie
Surveyors Office
Feb. 18, 1976
C.S. 59/8

119

Section corner for Secs. 27, 28, 33 and 34.

Found - 1958 County Surveyor's Office brass cap, Ren. #12
Cap dislodged by uprooted tree.

Orig. 17" now 21" R. Fir, is dead. Tree bears S.6°W., 13.2 ft. Tree is bark scribed "T30S R8W S33 BT"

Other orig. BT's found in 1958 are uprooted and cut below scribing. 10" now 14" W. Fir is dead. Tree bears N.48°E., 70.7 ft. (Rec. 69.5 ft.) Has good blaze, partially opened. Ren. #12

Other BT's per renewal #12 have been destroyed.

Renewal- I replace 1958 brass cap at section corner. I restamp date "1976"

A 11" R. Fir bears S.11°W., 30.9 ft. Tree blazed & scribed "T30S R8W S33 CS BT"

Set - bridge spike in 48" Fir stump. Spike bears S.60 1/2°E., 42.1 ft. Spike stamped "S34"

Set - Bridge spike in A 38" Fir stump. Spike bears N.77°E., 50.1 ft. stamped "S27"

Set - Bridge spike in a 30" Fir stump. Spike bears N.74°W., 9.2 ft. stamped "S28"

10/12/76

L.E. Monrean
P. L. Earle
Co. Surveyors
Office
Oct. 12, 1976
C.S. 59/24