

**Douglas County Surveyor's Record of  
Government Corners Renewed**

T 305 T.S. R 8 W R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Center 1/4 Cor. Sec. 6 145  
 Set - Aluminum cap on a 5/8"x48" iron rod mkd: "LS  
 2354 2002"  
 Scribed - 15" W.Fir S.20°W., 16.6' "C $\frac{1}{4}$  BT"  
 8" Hemlock N.54°W., 13.2' "C $\frac{1}{4}$  BT"  
 10" Hemlock N.2°W., 19.7' "C $\frac{1}{4}$  BT"  
 18" Hemlock S.72°E., 18.1' "C $\frac{1}{4}$  BT"  
 (Note - Previous renewal #66 by Hales in 1965) DCSO JC

1/4 Cor. Secs. 5 & 6 146  
 Found - 1965 Douglas Co. Surveyors brass cap on an iron  
 pipe. (Ren. #62)  
 14" W.Fir N.74°W., 11.0' healed (rec. N.72°W.,  
 10.0')  
 10" W.Fir S.72°E., 21.0' healed (rec. S.67°E.,  
 20.3')  
 Scribed - 13" Chinquapin N.53°E., 20.0' " $\frac{1}{4}$  BT"  
 9" W.Fir S.19 $\frac{1}{2}$ °W., 8.7' " $\frac{1}{4}$  BT"

1/4 Cor. Secs. 6 & 7 147  
 Found - 1965 Douglas Co. Surveyors brass cap on an iron  
 pipe. (Ren. #63)  
 84" stump S.46°W., 12.3' (OBT)  
 60" stump N.38°E., 27.3' (OBT)  
 24" stump S.4°E., 12.2' healed  
 26" Fir N.45°W., 3.4' healed  
 Scribed - 40" W.Fir S.12°W., 44.9' " $\frac{1}{8}$ S BT"  
 15" W.Fir N.71°E., 13.7' " $\frac{1}{8}$ S BT"  
 12" W.Fir S.78°E., 56.8' " $\frac{1}{8}$ S BT"

Center-east 1/16 Sec. 6 148  
 Set - Aluminum cap on a 5/8"x48" iron rod mkd: "LS  
 2354 2002"  
 Scribed - 18" W.Fir S.9°E., 15.8' "CE1/16 BT"  
 9" W.Fir S.42°W., 35.1' "CE1/16 BT"  
 (Note - Previous renewal #67 by Hales in 1965) DCSO JC

Center-South 1/16 Sec. 6 149  
 Set - Aluminum cap on a 5/8"x48" iron rod mkd: "LS  
 2354 2002"  
 Scribed - 28" Fir S.89°E., 38.2' "CS1/16 BT"  
 23" Fir N.62°W., 41.6' "CS1/16 BT"  
 (Note - Previous renewal #68 by Hales in 1965) DCSO JC

1/4 Cor. Secs. 24 & 25 150  
 Found - 2 $\frac{1}{2}$ " brass cap set by BLM  
 20" D.Fir bears N.74 $\frac{1}{2}$ E. 13.86' healed. BLM 1985  
 13" W.Fir bears S.40 $\frac{1}{2}$ W. 85.8' healed. BLM 1985  
 New - 8 $\frac{3}{4}$ " D.Fir bears S.57°E. 29.5' scribed " $\frac{1}{4}$  S25 BT"  
 10" D.Fir bears N.43 $\frac{3}{4}$ °W. 45.5' scribed " $\frac{1}{4}$  S24 BT"  
 Note - Corner lies on Northerly slope on the Westerly  
 side of a drainage & South of old skid rd.

Mark Smalley  
 For: Roseburg  
 Resources  
 & Moore Mill  
 8/2002  
 M 137-50

Greg Lang  
 5/3/2004  
 C.S. File  
 65/49-32