

Douglas County Surveyor's Record of
Government Corners Renewed

30

T. S.

8

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 91881

Douglas Co.
Surveyors Office
Stephen Flause
John Pike
2/24/2005
C.S. File 67/10-8

1/4 Cor. Secs. 26 & 35

151

Found - 5/8" I.R. w/1 1/2" Alum. cap mkd: "T30S R8W 1/4 26/35
1982 LS 498" protruding 7" out of ground.
Steel fence post bears West 2 ft. (Ren #132)
6" now 12" D.Fir healed single blaze visible
bears S.34°E., 2.8 ft. (agrees w/rec)
NE BT now down shows fully healed blaze, root
depression measures for brg. & dist.

New - 9" D.Fir, double blaze & scribed "1/4 S35 CS BT"
bears S.83°W., 13.3 ft.
18" D.Fir, double blazed & scribed "1/4 S26 CS BT"
bears N.38°W., 26.5 ft.
14" Grand Fir, double blazed & scribed "1/4 S26 CS
BT" bears N.40 1/2°E., 43.0 ft.

Note - Corners lies in old skid rd. just East of shallow
draw on Northwesterly slope. Heavily timbered

Greg Lang
For: Roseburg
Resources
3/2006
M150-3
C.S. File
65/58-2A

Corner Secs. 13, 14, 23, & 24

152

Found - 1 1/4" iron pipe set by Howard Johnstone from Orig
evidence.
A 15 1/2" Cedar bears S.61 1/2°E., 30.50 ft (1962 by
Howard Johnstone) REN #25
A 21" Fir bears S.17 1/2°W., 8.0 feet (Orig)
Found Johnstone's Fir to the Southwest but did not
field locate it. (Record is S.74 1/4°W., 54.0 ft)

New - 6 1/2" Fir bears N.82°E., 102.00 ft scribed "T30S R8W
S13 BT"
14 1/2" Fir bears N.20 1/2°W., 72.70 ft scribed "T30S R8W
S14 BT"

Note - We set a spikes in the side and base of all bearing
trees except the one existing tree mentioned
above which was not field located. These were
for measuring distances to the cor. Bearings
to the trees were measured to the center with
a total station & are based on the original
1882 Survey by W. H. Byars.
Corner lies on a Westerly slope about 150' from the
top of a ridge. It lies just above and not far
from an old logging road to the South.

1/4 Secs. 8 & 17

153

Douglas Co.
Surveyors
Office
Stephen Flause

John Pike
4/16/2007
C.S. 67/21-25

Found - 2 1/2" dia., brass cap, properly mkd on 1 1/4" O.D. IP
projects 6" above ground, firmly set.
Orig. 15" now 20" dia., madrone, now down, out of
position shows opened blazes, no scribes fd,
bears S.32°W., 16.5 ft. (agrees w/rec) OBT
8" now 13" dia., D.Fir, healed double blaze visible
bears S.67 1/2°W. 22.5 ft. (rec. S.71°W. 23.0 ft)
1965 BT. Possible 1965 crew read wrong side of
compass needle?
18" now 23" dia., x 7 ft. tall I. Cedar stump,
fully healed double blaze visible, top of
stump cut at angle to shed water, bears
N.4°E., 29.1 ft. (agrees w/rec) 1965 BT
Orig. 24" Madrone now root hole, agrees well w/rec.
(N.34°W., 33.0 ft.) OBT

New - 22" dia., chinquapin, double blazed & scribed "1/4 S17
CS. BT" bears S.21 1/2°E., 30.6 ft.
6" dia., G.Fir, double blazed & scribed "1/4 S8 CS BT"
bears N.57 1/2°W., 22.9 ft.

Note - Corner lies approx. 300 ft. south of graveled Rd. on
S side of ridge top.
Compass decl. 16 1/4°E.