

Douglas County Surveyor's Record of
Government Corners Renewed

30 T. S. 9 R. W. W. M.

Ben B. Irving June 21-25, 1927
Witnesses
LaVern Sutherland
Herman Aydelot
T. L. Clinton
Hyde - e.s. 37/115

H. L. Eppstein
County Sur.
May 28, 1931
Witness
L. C. Smith
E. A. Lane
e.s. file 18/9

James W. Byron, Deputy County Surveyor
R. C. Coffey (on vacation)
S. Bilow
July 9, 1958
C. S. File No. 49/100

1/4 CORNER BETWEEN SECTIONS 3 and 4.
Identified by old Fir snag N.46°W. 10 lks. bearing
scribe marks and stump (rotten) probably other O.B.T.
as it checks both bearing and distance.
Set 4" Cedar Post for corner and mark the new B.T.s
A 28" Fir S.36°10'W. 10.4 ft.
A 22" Fir N.26°25'E., 11.8 ft.

1

1/4 CORNER BETWEEN SECTIONS 4 and 5.
Identified by portion of original Post marked 1/4 S.
and hole where it set also by 10" Hemlock S.43°30'E.
15.8 ft.; 10" Hemlock N.74°45'W. 13.6 ft. One of these
B.T.s was only a rotten snag bearing scribe marks.
Set 4" Cedar post for corner and marked a new B.T.
A 12" Hemlock S.43°15'E., 13.6 ft. - SEARCHED FOR NOT FOUND 9/19/67
19/67 CS. 53/53

2

N.W. CORNER OF SECTION 3.
Identify by old cedar post, scribe marks rotted off.
Four O.B.T.s. Fir and stump of old Chinquapin check bearing
and distance. Hemlocks check neither S. W. 41 lks.
and N.55°W. 34 lks. Var. 20°E. SEARCHED FOR, NOT FOUND - OCT. 1967 Q.M.P.

3

CORNER BETWEEN SECTIONS 9 and 16.
Set from original B.T. Rock 6 x 8 x 14.
White Oak 12" dia. S.27°E., 30 1/2 lks. Old original
Fir 6" dia. N.2°W., 20 lks. B.T.s
Fir 14" dia. N.40°E., 15 lks.
Fir 24" dia. S.21°W., 22 lks. - DOWN

4

1/2 Section Corner to Sections 12 & 13.
Found - Both Orig. BTs.
Orig. 10", now 18" W.O., good scribing visible "BT" N.18°E. 83.8 ft.
Orig. 18", now 36" Laurel, S.78°E. 44.2 ft. I do not open.
Set Brass Cap at Corner Mkd: 1/2 S12 T30S R9W County Surveyor's
S13 Office, 1958
New BT's: 20" R.Fir bears S.74 1/2°E. 26.7 ft. scribed 1/2 S13 CS BT.
10" Cedar bears N.29°W. 39.6 ft. scribed 1/2 S12 CS BT.

5

Section Corner to Secs. 12 & 13, T30S, R9W & Secs. 7 & 18, T30S, R8W.
Found - 3 Orig. Bearing Trees:
Orig. 20", now 24" Pine Stump N.12°W. 19.1 ft. I open & find
good scribe "BT".
Orig. 18", now 28" W.Fir Snag has good bark scribing, N.45°E. 33.0 ft.
Orig. 20", now 30" R.Fir, has good bark scribing.
No trace of Orig. S. W. BT.
Set Brass Cap at Corner Mkd: R9W S12/S7 R8W T30S County Surveyor's
S13/S18 Office, 1958.
New BT's: 8" R.Fir bears N.89°W. 9.4 ft. scribed S12 T30S R9W CS BT.
9" Chinquapin -S.43°W. 35.6 ft. scribed S13 T30S R9W CS BT.
10" R.Fir bears S.30°E. 9.9 ft. scribed S18 T30S R8W CS BT.
4" W.Fir bears N.73°E. 28.7 ft. scribed S 7 CS BT.

6

Section Corner to Section 1 & 12, T30S R9W, & Secs. 6 & 7, T30S R8W.
Found - All four Orig. BT's. All check bearings & distances.
Orig. 24", now 36" Fir Snag S.55°W. 29.7 ft. Has good bark scribing,
"S12 T30S R9W".
Orig. 9", now 26" W.Fir S.45°E. 36.3 ft. Good bark scribing above
& good scar below.
Orig. 24", now 40" Fir Stump shows good scar near base.
Orig. 24", now 36" Fir N.53°E. 16.5 ft, now down.
Set Brass Cap at Corner Mkd: R9W S1/S6 R8W T30S County Surveyor's
S12/S7 Office, 1958
New BT's: 9" W.Fir S. 8°W. 38.0 ft. scribed S12 T30S R9W CS BT.
8" W.Fir S.67°E. 15.5 ft. scribed S 7 T30S R8W CS BT.
8" W.Fir N.25 1/2°E. 27.3 ft. scribed S6 T30S R8W CS BT.
16" W.Fir N.36°W. 45.0 ft. scribed S1 T30S R9W CS BT.

7