

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21081

39

Sec. Cor. to Secs. 12 & 13, T30-9W. & Secs. 7 & 18, R9W.
Found - Brass Cap and 3 BT's. as recorded in Ren. #6.
N. W. BT., down.
New BT: 12" W. Fir N. 71° W. 54.6 ft. Mkd: T30S R9W S12 CS BT.

40

Sec. Cor. to Secs. 13 & 24, R9W. & Secs. 18 & 19, R8W.
Found - Squared Post & BT: 15", now 34" D. Fir N. 35° E. 396 ft.,
faint bark scribe "BT" & other not legible.
24" D. Fir, now down & rotted, S. 26° E. 101.6 ft. Found
part of old face & Axe marks in rotten remnants.
No trace of Laurel or Chinq. in S. W. & N. W.
Set - 1" I.P. & Brass Cap Mkd: County Surveyor's Office, 1964

S 13	S 18	T30S
R9W S 24	S 19	

 New BT's: 8" D. Fir N. 87° E. 8.8 ft. Mkd: T30S R8W S18 CS BT.
 8" D. Fir N. 43° W. 10.0 ft. Mkd: T30S R9W S13 CS BT.
 8" D. Fir S. 52° W. 12.4 ft. Mkd: T30S R9W S24 CS BT.
 13" D. Fir S. 19° E. 26.7 ft. Mkd: T30S R8W S19 CS BT.

41

Sec. Cor. to Sections 23 - 24 - 25 - 26.
Found - Squared Post & high stumps of BT's. as follows:
 10", now 15" W. Fir Stump S. 40° W. 10.5 ft., recorded as
 7.3 ft., opened & scribe visible.
 20", now 24" D. Fir stump S. 70° E. 5.9 ft., bark scribe
 plainly visible & previously rescribed in the wood.
 12" D. Fir, down & rotting, N. 16° E. 16.5 ft.
 18", now 22" D. Fir Stump N. 27° W. 15.8 ft., shows bark
 scribe & previous rescribe in wood.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964

T30S R9W	S23	S24
	S26	S25

 New BT's: 15" W. Fir N. 70° E. 88.1 ft. Mkd: T30S R9W S24 CS BT.
 15" D. Fir S. 61½° W. 139.2 ft. Mkd: T30S R9W S26 CS BT.
 Note - No other trees close. This corner lies approx. 75.2 ft.
 East of Road.

FDOK BY
D. Edwards
2/2007
M 152-35

Vernon "Rag" Tracy
 Mike Darby & Jack Barnett
 August 1964
 C. S. File No. 53/53

42

¼ Corner to Sections 13 and 24. *FD. used on Bull Run survey*
 Found - Squared Post & Orig. BT's. as follows: *21068*
 30", now 42" D. Fir S. 8° W. 36.3 ft., showing good "S" bark scribe.
 20", now 36" D. Fir N. 50° W., recorded as N. 58° W. 55.4 ft., showing
 parts of "¼", bark scribe.
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964

T30S R9W ¼	S 13
	S 24

 New BT's: 14" D. Fir S. 52° E. 7.9 ft. Mkd: ¼ S24 CS BT.
 18" D. Fir N. 51° W. 3.0 ft. Mkd: ¼ S13 CS BT.

43

Section Corner to Sections 9 - 10 - 15 - 16.
 Found - Sandstone with 3 notches on E. side & "B" on top measuring
 12" X 10" X 6" & following BT's. of 1893 survey:
 11" Fir, now 18" S. 72° E. 28.1 ft., chopped open & showing good "S".
 12" Fir, now 18", S. 70° E. 29.0 ft., stump showing burlwood.
 9" Fir, now 15", S. 30° W. 17.8 ft., opened & showing "T30R9" scribe.
 6" Fir, now 6", N. 37½° W. 3.4 ft., rotted fragments, fd. good "B".
 Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964

T30S R9W	S 9	S 10
	S 16	S 15

 New BT's: 13" D. Fir N. 15° E. 18.0 ft. Mkd: T30S R9W S10 CS BT.
 10" Cedar S. 24° E. 21.3 ft. Mkd: T30S R9W S15 CS BT.
 19" D. Fir S. 50° W. 3.5 ft. Mkd: T30S R9W S16 CS BT.
 10" D. Fir N. 16° W. 22.6 ft. Mkd: T30S R9W S9 CS BT.

RE-RENEWED CORNER NO. #132

SEE ALSO
 STATE MAP FILE
 MAP. C.S. #
 MAP. M-7