

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Corner to Sections 26 and 25.

Found - BT's. as listed below and recorded in Ren. #35.

11" W. Fir S.14°W. 78.6 ft. Mkd: 1/4 S BT.

8" W. Fir S.75°E. 70.5 ft. Mkd: 1/4 S BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T30S R9W 1/4 S26/S25.

44
FDOK
By D. Edwards
2/2007 M152-35
(see BLM ALSO)

Section Corner to Secs. 19 & 30, T30-8W. & Secs. 24 & 25, T30-9W.

Found - Orig. BT's., as follows:

20", now 40" D. Fir S.66°E. 29.7 ft., shows very old bark scribe "3S R8W S". & BT scar.

6", now 30" W. Fir S.32°W. 17.8 ft., Did not open.

12", now 22" D. Fir N.42°E. 73.9 ft., shows good scar. Didn't Open.

24", now 48" D. Fir N.15°W. 80.5 ft., shows faint bark scribe.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T30S R9W S 24 | S 19
S 25 | S 30 R8W

New BT's: 13" D. Fir N.44°E. 10.5 ft. Mkd: T30S R3W S19 CS BT.

11" W. Fir N.39°W. 32.3 ft. Mkd: T30S R9W S24 CS BT.

30" W. Fir S.32°W. 17.8 ft. Mkd: T30S R9W S25 CS BT.

9" Yew S.43°E. 30.6 ft. Mkd: S30 CS BT.

45

1/4 Corner to Sections 22 and 23.

Found - 24", now 36" D. Fir (Orig) N.50°W. 40.3 ft., open & find "BT" scribe.

No trace of other BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T30S R9W 1/4 S22/S23

New BT's: 7" D. Fir East 7.8 ft. Mkd: 1/4 S23 CS BT.

5" D. Fir S.62°W. 18.2 ft. Mkd: 1/4 S22 CS BT.

7/31/70, FD. O.K. V.R.T. c.s. 56/34
2/73

46

Section Corner to Secs. 22 - 23 - 26 - 27.

Found - Orig. BT's. as follows:

6", now 15" D. Fir S.5°W. 4.0 ft., open & find "B" scribe.

10", now 24" D. Fir S.89°E. 13.9 ft., shows faint scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T30S R9W S22 | S23
S27 | S26

Remarked Orig. BT's: 15" D. Fir S.5°W. 4.0 ft. Mkd: T30SR9W S27CS BT.

24" D. Fir S.89°E. 13.9 ft. Mkd: T30S R9W S26 CS BT.

No other trees available. This corner lies on steep, S.W. slope approx. 100.0 ft. above creek.

47
FDOK
D. Edwards
2/2007 M152-35

Section Corner to Secs. 25 - 26 - 35 - 36.

Found - 3 old BT's. & rotted remains of other and Corner Stone.

18", now 42" Cedar N.1°W. 160.6 ft., shows scar.

12", Fir S.20°W. 13.2 ft., down & very badly rotted.

20", now 36" N.41 1/2°E. 16.8 ft., open & find "B" scribe.

36", now 40" Pine S.59°E. 114.2 ft., shows scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T30S R9W S 26 | S 25
S 35 | S 36

New BT's: 9" D. Fir S.45°E. 25.9 ft. Mkd: T30S R9W S36 CS BT.

8" D. Fir South 14.2 ft. Mkd: T30S R9W S35 CS BT.

13" D. Fir N.19°W. 20.5 ft. Mkd: T30S R9W S26 CS BT.

15" D. Fir N.70°E. 23.8 ft. Mkd: T30S R9W S25 CS BT.

48

1/4 Corner to Sections 35 and 36.

Found - Orig. 20", now 21" Cedar N.60°W. 21.1 ft., open & shows faint "1& B":

Other BT gone, hole remains right bear. & dist. from corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T30S R9W 1/4 S35/S36

New BT's: 8" W. Fir S.14°W. 8.7 ft. Mkd: 1/4 S35 CS BT.

13" W. Fir S.41°E. 6.9 ft. Mkd: 1/4 S36 CS BT.

49

Vernon "Ray" Tracy, Deputy Co. Surv.
Mike Darby and Jack Barnett
October 1964
C. S. File No. 53/53

102