

**Douglas County Surveyor's Record of
Government Corners Renewed**

T. 30 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

50

Sec. Cor. to Secs. 4 & 5, T30-9W. & Secs. 32 & 33, T29-9W.
 Found - Orig. 12", now 20" Hemlock S.74°E. 22.4 ft., shows scribe in scar. (opnd
 Orig. 15", now 24" Hemlock N.74°W. 25.7 ft., shows good scar.
 Orig. 36", now 54" Fir Stump S.38°W. 7.9 ft., shows face on top.
 No trace of N.E. Bearing Tree, Doug. T29S S 32 | S 33
 Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W S 5 | S 4
 Office, 1964
 New BT's: 17" Hemlock N.12°E. 28.8 ft. Mkd: T29S R9W S33 CS BT.
 9" Hemlock S.22°W. 26.9 ft. Mkd: T30S R9W S5 CS BT.
 This corner is on that portion of the county line between Coos and Douglas
 County that runs E. & W. on the N. Line of T30S R9W.

51

Sec. Cor. to Secs. 35 & 36, T30-9W. & Secs. 1 & 2, T31-9W.
 Found - 50", now 60" D.Fir Stump(Orig.BT) S.50°W. 12.5 ft. shows "31S
 R9W S2", bark scribe & BT scar.
 10", now 24" D.Fir Stump(Orig.BT) S.12°E. 16.5 ft., shows faint scar.
 24" D.Fir N.56°W. 11.8 ft., open & shows "30" in approx. 60 yrs.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W S 35 | S 36
 Office, 1964 T31S S 2 | S 1
 New BT's: 24" D.Fir N.56°W. 11.8 ft. Mkd: T30S R9W S35 CS BT.
 24" D.Fir(stump) S.12°E. 16.5 ft. Mkd: T31S R9W S1 CS BT.
 12" W.Fir N.38°E. 19.5 ft. Mkd: T30S R9W S36 CS BT.
 Note - This Corner lies approx. 50 ft. East of new 12 Mile Creek Road.
 7/73 FO.O.K. V.R.T. C.S. 56/34

52

1/4 Corner to Sections 13 and 14.
 Found - Trees recorded in Ren. #18, as follows:
 7" D. Fir N.73°W. 86.6 feet
 20" Cedar N.73°E. 116.0 feet.
 Using the recorded bearings we cannot bring distances to intrscn.
 Set - Brass Cap at Property bearings to BT's. & take new level distances.
 Brass Cap Mkd: County Surveyor's Office, 1964
 T30S R9W 1/4 S14/S13.
 Note - This corner lies on west side of new 12 Mile Creek Road.
 7/11/70 FOUND O.K. V.R.T

53

Section Corner to Sections 16 - 17 - 20 - 21.
 Found - Rock 5" x 10" x 12" for corner & 2 Orig. BT's:
 30", now 36" Cedar S.37 1/2°W. 19.1 ft., open & shows scribe. #172
 48", now 54" D.Fir N.55°W. 16.1 ft., shows very good scar.
 No trace of other BT's.
 Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W S 17 | S 16
 Office, 1964 S 20 | S 21
 New BT's: 10" W.Fir S.80°E. 13.4 ft. Mkd: T30S R9W S21 CS BT.
 8" W.Fir N.54°E. 16.9 ft. Mkd: T30S R9W S16 CS BT.
 Note - We set Rock between Line Tree and Brass Cap & built Mound of Rock.

54

1/4 Corner to Sections 20 and 21. (Witness Corner) FO.O.K. G. SMITHER 1/01 M136-54
 Found - Both Orig. BT's. & Corner Tree called for:
 30", now 40" Fir for corner, shows good scar on West side.
 30", now 44" W.Fir S.52°E. 33.0 ft., shows good scar.
 12", now 24" Fir S.51 1/2°W. 61.4 ft., open & shows "1/2S" scribe.
 Set - Brass Cap 8.0 ft. S. of Corner Tree for Wit. Corner & Mkd:
 County Surveyor's Office, 1964 T30S R9W W.C. 8 ft. N. 1/4 S20/S21
 New BT's: 8" D.Fir N.80°W. 15.9 ft. Mkd: W.C. 1/4 S20 CS BT.
 24" Chinq. N.77°E. 45.5 ft. Mkd: W.C. 1/4 S21 CS BT.
 30" Cedar Line Tree bears South 8.5 feet.

55

1/4 Corner Sections 17 and 20.
 Found - 6", now 20" Fir for Corner Tree, shows faint scar on N. Side.
 Orig. 6", now 20" W.Fir N.58°E. 8.6 ft., open & shows "4" scribe.
 Set - 1" L.P. & Brass Cap on N. Side at base of Corner Tree Mkd:
 County Surveyor's Office, 1964 T30S R9W 1/4 S 17 | S 20 #170
 S 20
 New BT's: 20" W.Fir N.58°E. 8.6 ft. (Orig.) Mkd: 1/4 S17 CS BT.
 18" D.Fir S.46°W. 31.8 ft. Mkd: 1/4 S20 CS BT.

Vernon "Ray" Tracy, Deputy
 Mike Darby and Jack Barnett
 October 1964
 C. S. File No. 53/53