

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 9 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 97301

56

1/4 Corner to Sections 16 and 21.

Found - Rock 12" x 10" x 10" in place with 1/4" on N. face,
6", now 14" D.Fir S.52°E. 16.1 ft., open & find 1/4" scribe.
No trace of other BT.

Set - Brass Cap alongside Rock & Mkd: County Surveyor's Off, 1964
T30S R9W 1/4 S 16
S 21

New BT's: 30" D.Fir S.77°E. 32.3 ft. Mkd: 1/4 S21 CS BT.
20" D.Fir N.42°W. 65.6 ft. Mkd: 1/4 S16 CS BT.

Note - This corner lies on steep, south slope approximately
100 ft. North of Creek.

SEE ALSO
STATE MAP M-6
C.S. FILE NO. 53/53

FD. OK BY D. EDWARDS JUNE, 2003 M142-38

See 2004/2005 57

Section Corner to Sections 8 - 9 - 16 - 17.

Found - 3 Orig. BT's. & Rock Mound. Corner Stone Gone.
12", now 14" Oak N.66°W. 63.4 ft., shows good scar.
30", now 40" Fir S.50°W. 76.9 ft., shows good scar, new snag.
24", now 36" Fir S.17 1/2°E. 123.8 ft., shows good scar.

Set - Brass Cap at Cor. in mound of stone Mkd: T30S R9W S 8 | S 9
County Surveyor's Office, 1964 S17 | S16

New BT's: 14" W.Oak N.22°E. 21.9 ft. Mkd: T30S R9W S9 CS BT.
12" Laurel N.61°W. 19.4 ft. Mkd: T30S R9W S8 CS BT.
9" W.Oak S.33°W. 49.1 ft. Mkd: T30S R9W S17 CSBT.
10" W.Oak S.42°E. 53.4 ft. Mkd: T30S R9W S16 CS BT.

Fd. by
O.S.H.D.
SEPT. 1982
STATE
HWY MAP
M-6

BLM Resurvey Pg 21 274-5
FDOK

Vernon "Ray" Tracy, Deputy
Mike Darby and Jack Barnett
October 1964
C. S. File No. 53/53

58

1/4 Corner to Sections 26 and 35.

Found - Orig. 28", now 38" Fir N.13 1/2°W. 25.7 ft., showed scar, we
open & find 1/4" scribe.
No trace of other BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W 1/4 S 26
Office, 1964 S 35

New BT's: 6" D.Fir S.29°E. 7.8 ft. Mkd: 1/4 S35 CS BT.
11" D.Fir N.28°E. 16.5 ft. Mkd: 1/4 S26 CS BT.

FDOK D-Edwards 2/2007
M150-35

59

1/4 Corner to Sec. 25, T30-9W. & Sec. 30, T30-8W.

Found at Corner - Orig. 8", now 14" Fir S.3°E. 8.6 ft. Open &
find "BT" scribe.

40", now 52" Fir North 37.0 ft. (snag) This is Line Tree.
No trace of Oak BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T30S R9W 1/4 S 25/S 30 R8W

New BT's: 11" W.Fir S.15°E. 5.3 ft. Mkd: 1/4 S30 CS BT.
12" D.Fir S.23°W. 18.5 ft. Mkd: 1/4 S25 CS BT.

60

1/4 Corner to Sections 34 and 35.

Found - Rock 12" x 14" x 16" Mkd: 1/4" on W. face, in place.
14", now 24" D. Fir Snag S.33 1/2°E. 26.1 ft. Open & find
1/4" scribe. No trace of other BT.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1964
T30S R9W 1/4 S34/S35

New BT's: 8" D.Fir N.43°E. 8.5 ft. Mkd: 1/4 S35 CS BT.
6" W.Fir N.25°W. 8.8 ft. Mkd: 1/4 S34 CS BT.

Note - This corner lies approx. 60.0 ft. N. of small creek on
Steep, S. W. slope.

61

Sec. Corner to Secs. 26 - 27 - 34 - 35.

Found - Rock 15"x8"x8", set in ground with 2 notches on E. and
1 notch on S. edges. All 4 BT's. alive and standing.

7", now 24" Fir N.50°E. 13.5 ft., Open & find axe face.
6", now 30" Fir S.13 1/2°E. 5.1 ft., recorded as S.26 1/4°E.
6", now 30" Fir N.34 1/2°W. 38.4 ft., shows scar.
6", now 30" Fir S.40 1/2°W. 42.2 ft., shows scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W S 27 | S 26
Office, 1964 S 34 | S 35

New BT's:

(continued next page)