

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 9 W. R.W.W.M.

KONE-CHAPMAN CO., EUGENE, ORE. 21887

Vernone R. Tracy
1964
October

New BT's: 26" D.Fir N.58°E. 30.2 ft. Mkd: T30S R9W S26 CS BT.
30" D.Fir S.13½°E. 5.1 ft. Mkd: T30S R9W S35 CS BT.
16" D.Fir S.74°W. 36.4 ft. Mkd: T30S R9W S34 CS BT.
15" D.Fir N.32°W. 15.4 ft. Mkd: T30S R9W S27 CS BT.

October 1964

FD. OK BY G. SMITHER JAN. 2001 M136-54 62

Sec. Cor. to Sections 17 - 18 - 19 - 20.

Found - Corner Rock 6"x8"x16" with 5 notches on E. & 3 notches on S. edges, set firmly in ground & 4 BT's:

16", now 24" Cedar Stump N.81½°E. 26.1 ft., open & shows, "T30S R9W S17" scribe.

31", now 40" D.Fir Snag S.57½°E. 22.4 ft., shows scar, partially open & burned face.

32", now 36" Cedar Stump S.24½°W. 35.6 ft. Open & shows "S19" scribe on burned face.

10", now 24" D.Fir (Alive) N.24½°W. 46.7 ft., shows faint scar.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W S 18 | S 17
Office, 1964 S 19 | S 20

New BT's: 7" Chinqp. N.48°E. 21.9 ft. Mkd: T30S R9W S17 CS BT.

5" D.Fir N.33°W. 15.3 ft. Mkd: S18 CS BT.

8" Laurel S.44°W. 10.4 ft. Mkd: S19 CS BT.

4" Cedar S.10°W. 7.3 ft. Mkd: S20 CS BT.

Note - This corner lies N. of spur top in dense brush.

October 1964

63

Vernon "Ray" Tracy
Terry Connell
September 1965
C. S. File No. 53/53

Sec. Cor. to Secs. 7 & 18, T30-9 & Secs. 12 & 13, T30-10W.

Found - Rock 12"x10"x10" with 4 notches on S. edge. N. edge broken off.

3 BT's. as recorded in survey of 1893.

36" Cedar Stump N.46°E. 27.4 ft., shows Orig. "R BT" scribe and new scribe "S 7 183 BT".

30" Cedar Stump S.63½°W. 28.1 ft. Do not open.

26" Cedar, face down & rotten, N.56½°W. 24.4 ft.

Set - Brass Cap at Cor. Mkd: County Surveyor's S 12 | S 7 | T30S
(In Mound of Stone) Office, 1964 R10W S 13 | S 18 | R9W

New BT's: 7" Myrtle N.65°E. 7.0 ft. Mkd: S 7 DCS BT.

16" Alder S. 4°E. 38.6 ft. Mkd: T30S R9W S18 DCS BT.

6" Maple S.16°W. 22.3 ft. Mkd: T30S R10W S13 DCS BT.

15" Alder N.33°W. 36.8 ft. Mkd: T30S R10W S12 DCS BT.

Note - This corner lies on E. bank of Creek approx. 3.0 ft. above Creek.

October 1964

64

¼ Corner to Sections 28 and 33.

Found - Orig. 52, now 55" Fir N.28½°E. 27.1 ft., open & shows "¼ S" scribe. No trace of other BT. or Stone as called for.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W ¼ S 28
Office, 1965 S 33
#159

New BT: 30" D.Fir S.12°W. 39.4 ft. Mkd: ¼ S33 CS BT.

Note - This corner lies on N. top of cut bank on old logging road.

September 1965

65

Section Corner to Sections 19 - 20 - 29 - 30.

Found - Stone at corner, 5 notches on East Face.

Orig. 10", now 22" Fir N.24°E. 38.9 ft.

Orig. 14", now 35" Fir S.54°E. 49.2 ft.

Orig. 15", now 32" Fir N.71½°W. 42.2 ft.

(All BT's. above are standing and have good scars.

12" Hemlock S.24½°W. 42.9 ft., Stump, shows scribing "T S R9W.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W S 19 | S 20
Office, 1965 S 30 | S 29

New BT: 36" D. Fir S. 82° W. 37.8 ft. scribed T30S R9W S30 CS BT.

Sept. 30, 1965

¼ Corner to Sections 11 and 14.

Found - Brass Cap at Corner as shown in Ren. No. 12.

20" D.Fir, now 24" S.42°E. 18.7 ft., scribing visible.

6½" W.Fir, now Stump, N.17½°E. 13.2 ft., scribe visible "BT".

New BT: 12" D.Fir N.83½°W. 36.1 ft. scribed "¼ S11 CS BT.

Oct. 5, 1965

66

John M. Powell
Joe Brady

October 1965
C. S. File No. 53/53