

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 9 W. R. W. W. M.

ROKE-CHAPMAN CO., EUGENE, ORK. 21891

4/95

Section Corner to Sections 28 - 29 - 32 - 33.

67

FDOK
K. Hoffine
M 119-59

Found - 15", now 25" Fir S.57°E. 9½ lks., opened & scribe visible.
15" Fir, now 21" S.20½°W. 36½ lks., shows good scar.
15", now 22" Fir N.42½°W. 37½ lks., shows good scar,
found distance to be 23.7 ft., not 27½ ft.
17", now 23" Fir N.18°E. 49 lks., shows good scar.
No trace of Orig. Rock at Corner.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W S 29 | S 28
Office, 1965 S 32 | S 33

All Trees listed above in good condition. Did not Rescribe.
Note - This corner is in a small draw.

68

Sec. Cor. to Sections 20 - 21 - 28 - 29.

FDOK
K. Hoffine
4/95
M 119-59

Found - 36", now 40" Fir N.12½°E. 38 lks., shows good scar.
(Tree now a snag.)
48", now 56" Fir N.53½°W. 56½ lks., shows good scar.
(Tree in good condition)
40", now 54" Fir S.65½°W. 21½ lks., shows good scar.
(Tree now a snag)
20", now 26" Fir S.18°E. 18½ lks., opened tree for
scribing "S2". (Tree now a snag.)

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W S 20 | S 21
Office, 1965 S 29 | S 28

New BT's: 56" Fir N.53½°W. 37.3 ft. scribed T30S R9W S20 CS BT.
4" Maple S.47°E. 11.9 ft., scribed S28 CS BT.
6" Hemlock N.52°E. 39.5 ft., scribed S21 CS BT.

Note - Location of corner is in a small ravine on N. slope
about 100 ft. south of bottom of ravine.

John M. Powell
F. Jones and J. Brady
October 1965
C. S. File No. 53/53

FD. OK G. SMITHER 1/01 M136-54

69

¼ Corner to Sections 20 and 29.

Found - 16 x 12 x 10 Stone Mkd: "¼".
6", now 14" Hemlock S.35½°E. 12 lks., tree opened
showing "¼" scribe.
10" ChinQ. N.49°E. 75 lks., no trace.

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W ¼ S20
Office, 1965 S29

New BT's: 18" ChinQ. S. 78° W. 24.5 ft. scribed ¼ S2 CS BT.
40" D.Fir N. 29° E. 41.6 ft. scribed ¼ S2 CS BT.

Note - This corner is about 100 ft. off top of ridge.

70

¼ Corner to Sections 4 and 9.

Found - 16" Fir Stump N.62°W. 56½ lks., stump opened
showing "¼" scribe.
10" Fir, found to be 7", S.78½°W. 39½ lks., Tree is
dead but shows scribing "¼S BT".

Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W ¼ S 4
Office, 1965 S 9

Set Cap in mound of Stones on solid Rock Point.

New BT's: 15" D.Fir N. 54° W. 47.0 ft. scribed ¼ S4 CS BT.
20" D.Fir S. 86° W. 40.6 ft. scribed ¼ S9 CS BT.

FD. OK 9/82
M 90-26
W. JOHNSTONE
FDOK BY
Ken Hoffine - 5/24
FOR LOWER ROCK
TIMBER CO
M120-24

¼ Corner to Sections 28 and 27.

71

Found - 36", now 40" Fir S. 54° E. 24 lks., opened & found
scribe "¼S". (Tree now dead snag)

No trace of S.W. BT. # 158

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S R9W ¼ S 28/S 27

New BT's: 11" D.Fir bears N. 30° W. 8.7 ft. Mkd: ¼ S28 CS BT.
6" D.Fir bears N. 46° E. 11.9 ft. Mkd: ¼ S27 CS BT.

FD. B...
Blm...
SEE GIS...

RECORDED