

Douglas County Surveyor's Record of
Government Corners Renewed

T.30 S. T. S. R. 9 W. R.W.W.M.

MOORE-CHAPMAN CO., EUGENE, ORE. 21881

FOOK BY D. EDWARDS, JUNE 2003 - M 142-38

78

1/4 Sec. Cor. to Sections 8 and 9.

Found - Stone, marked "1/4" on West face, has been moved.
14" D. Fir, now 18" N. 19 1/2° W. 22 1/2 lks., tree opened,
showing "1/4 S".

17" D. Fir, now 28", N. 80° E. 26 lks., this tree
has good scar.

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1965
T30S R9W 1/4 S 8/S 9

Put old Stone alongside Brass Cap.

Original BT's. in good shape. Did not rescribe.

Note - This corner is on small ridge, ravine about 70.0 ft.
to the west; ravine about 60.0 ft. to the east.

November 1965

1/4 Corner to Sections 29 and 30.

Found - No trace of Stone set at corner.

4' Doug. Fir Stump S. 67 1/2° E. 17.5 ft., opened stump
for scribe "S".

32" Cedar Stump S. 32 1/2° W. 20.8 ft., scribe visible.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S R9W 1/4 S 30/S 29

New BT's: 4" D. Fir S. 18 1/2° E. 10.7 ft. scribed 1/4 S CS BT.

5" D. Fir S. 30° W. 13.9 ft. scribed 1/4 S 30 CS BT.

79

1/4 Corner to Sections 18 and 17.

Found - 30" Fir Stump S. 66° E. 23.4 ft., opened & found scribing.
8" Hemlock N. 52° W. 13.2 ft. (No trace)

Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1965
T30S R9W 1/4 S 18/S 17

New BT's: 6" Cedar S. 82° E. 45.8 ft. scribed 1/4 S17 CS BT.

13" D. Fir N. 37° W. 50.7 ft. scribed 1/4 S18 CS BT.

This corner is located in badly burnt and brushy area.
Small ravine about 100.0 East.

80

1/4 Corner to Sections 18 and 19.

Found - Iron Pine at 1/4 Corner (unrecorded)

20" Cedar Stump N. 37 1/2° E. 11.5 ft. scribed "1/4 S".

10" W. Fir Stump S. 1° E. 12.8 ft., stump completely rotten.

Set - Brass Cap at 1/4 Cor. Mkd: Co. Surveyor's Office, 1965
1/4 S 18
S 19

New BT's: 6" Cedar N. 22° E. 12.7 ft. scribed 1/4 S18 CS BT.

8" Laurel S. 3° E. 21.4 ft. scribed 1/4 S19 CS BT.

This corner is located about 150.0 ft. from top of ridge,
on the west slope.

81

Sec. Cor. Secs. 30-31, T30-9W. & Secs. 25-36, T30-10W.

Found - 16x14x6 Stone had been rolled downhill.

15" Cedar, now 24", N. 68° E. 20.5 ft., open & fd. scrbing.

40" Cedar, down & burnt, S. 20° E. 10.0 ft.

18" Cedar, now 26", S. 33° W. 95.7 ft. This tree shows
good scars.

36" Cedar, now 45", N. 65° W. 9.9 ft., shows scars.

Set - Brass Cap at Cor. Mkd: Co. Surv. Office, 1965
T30S R9W S 25/S 30
R10W S 36/S 31

New BT's: 24" Cedar N. 68° E. 20.5 ft. scribed T30S R9W S30 CS BT.

40" Fir S. 50° E. 16.3 ft. scribed T30S R9W S31 CS BT.

82

1/4 Cor. Sec. 31, T30-9W. & Sec. 36, T30-10W.

Found - Stone 14x10x9 at 1/4 Corner Mkd. 1/4 on West Face.

10" Cedar, now 12" S. 50° E. 15.8 ft., scribe visible "S".

12" Fir N. 40° W. 17.2 ft. This tree 12" Cedar, now dead.

Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1965
T30S 1/4 R10W S 36/S 31 R9W

New BT: 31" Cedar, Scribed 1/4 S36 CS BT, N. 80 1/2° W. 11.9 ft.

83

John M. Powell
J. Brady & F. Jones
November 1965
C. S. File No. 53/53

RE-RENEWED, SEE CORNER NO. # 173

RE-RENEWED, SEE CORNER NO. # 152

FOOK
By B. Stancer
2-74
M 49-54

RE-RENEWED, SEE CORNER NO. # 153