

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T.S. R. 9 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21681

$\frac{1}{4}$ Corner to Sec. 18, T30-9W. & Sec. 13, T30-10W.
Found - Stone at $\frac{1}{4}$ Corner 14x14x10 mkd. $\frac{1}{4}$ on West Face.
13" D.Fir, now 20", N.26 $\frac{1}{2}$ °W. 34.3 ft., opened & found scribe "S".
12" D.Fir N.45 $\frac{3}{4}$ °E. 46.2 ft. No trace of this tree because of
skid road.

Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1965
T30S $\frac{1}{4}$ RLOW S 13/S 18 R9W

New BT's: 19" D.Fir N. 5° W. 42.4 ft. scribed $\frac{1}{4}$ S13 CS BT.
7" D.Fir N.87°E. 8.0 ft. scribed $\frac{1}{4}$ S18 CS BT.

FD OK
BY B. Shaner
2-74 M 49-54

84

Sec. Cor. Secs. 19 & 30, T30-9W. & Secs. 24 & 25, T30-10W.
Found - 32" Fir Stump S.22°W. 21.8 ft. opened stump, fd. scribing "R10".
14" Fir, now dead snag, N.52 $\frac{1}{2}$ °W. 19.8 ft. scribed.
34" Fir Stump N.27°E. 12.2 ft. (S.B. 10.2 ft.)
30" Fir Stump S.51 $\frac{1}{2}$ °E. 31.0 ft.

Set - Brass Cap at Cor. Mkd: County Surv. Office, 1965
T30S S 24 | S 19
RLOW S 25 | S 30 R9W

New BT's: 20" Cedar N. 30° E. 24.8 ft. scribed T30S R9W S19 CS BT.
6" D.Fir N.84°E. 46.2 ft. scribed S19 CS BT.

WESTERN CORNER NO. # 148

85

$\frac{1}{4}$ Corner to Sec. 19, T30-9W. & Sec. 24, T30-10W.
Found - 28" Cedar Stump N. 62 $\frac{1}{2}$ ° E. 30.4 ft., scribe visible, "S" "4".
14" D.Fir, now 24", N. 35° W. 21.8 ft., shows scar.

Set - Brass Cap at $\frac{1}{4}$ Cor. Mkd: County Surveyor's Office, 1965
T30S $\frac{1}{4}$ RLOW S 24/S 19 R9W

New BT's: 50" D.Fir S. 19° E. 26.0 ft. scribed $\frac{1}{4}$ S19 CS BT.
24" D.Fir N.35°W. 22.5 ft. scribed $\frac{1}{4}$ S24 CS BT.

86

Sec. Cor. to Secs. 18 & 19, T30-9W. & Secs. 13 & 24, T30-10W.
Found - No trace of Mound of Rock or Stone.
40" D.Fir, now 52", S.85 $\frac{1}{2}$ °W. 139.3 ft. Tree had been opened &
badly burned. Reopened stump for scribing "S".

Set - Brass Cap at Cor. Mkd: Co. Surv. Office, 1965
T30S S 13 | S 18
RLOW S 24 | S 19 R9W

New BT's: 17" D.Fir N. 47° E. 14.0 ft. T30S R9W S18 CS BT.
19" D.Fir N. 38° W. 16.3 ft. T30S RLOW S13 CS BT.
19" Cedar S. 48° W. 7.0 ft. T30S RLOW S24 CS BT.
6" Hemlock S. 7° E. 13.0 ft. R9W S19 CS BT.

Corner is about 20.0 ft. north of Rock Bluff.

FD OK
BY B. Shaner
2-74 M 49-54

87

$\frac{1}{4}$ Corner to Sec. 36, T30-9W. & Sec. 1, T31-9W.
Found - 10" D.Fir, down & rotten, N. 10° W. 3.3 ft.
24" D.Fir, down & rotten, S. 85° E. 26.4 ft. Open tree for
scribe, found "BT".

Set - Brass Cap at Cor. Mkd: Co. Surveyor's Office, 1965
T30S
R9W S 36
S 1

New BT's: 8" Cedar N. 13° E. 27.7 ft. scribed T30S R9W $\frac{1}{4}$ S36 CS BT.
5" D.Fir S.37°W. 72.0 ft. scribed S 1 CS BT.

This corner is located in bottom of small ravine.

88

Sec. Cor. to Secs. 32 & 33, T30-9W. & Secs. 4 & 5, T31-9W.
Found - 10" D.Fir, now 13", N. 50° E. 6.6 ft. (should be 10.4 ft.)
shows good scar.
33" D.Fir, now 40", S. 39 $\frac{1}{2}$ ° W. 50.8; (S.B. 48.8 ft.), shows fair scar.
11" D.Fir, now 15", S. 85 $\frac{3}{4}$ ° W. 24.4 ft., shows good scar.
12" Fir, down, N. 85° W. 39.6 ft., opened for scribe "BT".

Set - Brass Cap at Cor. Mkd: Co. Surveyor's Office, 1965
T30S R9W
S 32 | S 33
S 5 | S 4
T31S R9W

New BT: 34" D.Fir N. 71° W. 42.5 ft. scribed T30S R9W S32 CS BT.

Note - I could not match dist. goes so took 4 bearings & 2 distances.

89

John M. Powell
J. Brady
November 1965
C. S. File No. 53/53