

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T.S. R. 9 W. R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

90

1/4 Corner to Sec. 33, T30-9W. & Sec. 4, T31-9W.
Found - 20x12x10" Stone with "1/4" on N. face.
36" Fir N. 2 1/2° W. 14.5 ft., blown down on face, shows
two good face.
10" Hemlock, now 21" S. 79 1/4° E. 12.2 ft., shows scar,
Did not open, call very good on stream. T30S
Set - Brass Cap at 1/4 Cor.Mkd: County Surveyor's Office, 1965 1/4 S 33 / S 4 R9W
New BT's; 21" Hemlock S. 79° E. 12.5 ft. scribed 1/4 S4 CSTBTS.T31S
56" Cedar N. 38° E. 21.6 ft. scribed 1/4 S33 CS BT.

91

Sec. Cor. to Secs. 31-32, T30-9W. & Secs. 5-6, T31-9W.
Found - 1 1/4" I. Pipe & Original Stone - Ren. #33.
8" D.Fir, now 11", S. 60° W. 34.4 ft. scribed S6 BT.
10" Oak, now 10", S. 51° E. 20.4 ft. scribed S5 BT. (This tree is a Chinquapin) T30S
Set - Brass Cap at 1/4 Cor. Mkd: County Surveyor's Office, 1965 S 31 / S 32 / S 6 / S 5 R9W
T31S
No other trees available to scribe:

RE-RENEWED, SEE CORNER NO. #126

John M. Powell
F. Jones & J. Brady
November 1965
C.S. File No. 53/53

92

Wit. Cor. to Sec. 6, T31-9W. & Sec. 1, T31-10W.
(South Boundary of T30-9W)
Found - 60" Fir Stump S. 32° E. 17.8 ft., opened, fd. scribing.
30" Fir N. 63° W. 37.0 ft., Fd. this tree to be N. 63° W.
32.0 ft. Did not find any scribing on this snag.
Set - Brass Cap at W.C. Mkd: Co.Surv. Office, 1965 T31S
R10W S 1 / S 6 R9W
New BT's: 14" Chinquapin bears S. 42° W. 47.6 ft. scribed T31S
R9W S 1 CS BT.
7" Laurel S. 26° E. 65.6 ft., scribed T31S R10W S6 CS BT.
Note - This corner is located right on top of ridge next to
steep bluffs.

93

1/4 Corner to Sections 29 and 28.
Found - 48" D. Fir, now 57", N. 65 1/2° W. 24.4 ft. Opened &
found scribing "S".
No trace of 12" Laurel, S 155 1/2° E. 9.9 ft.
Set - Brass Cap at 1/4 Cor.Mkd: County Surveyor's Office, 1965
T30S R9W 1/4 S 29/S 28
New BT: 37" Laurel S. 41° E. 42.0 ft. scribed 1/4 S28 CS BT.

FOOK 4/95 K-Hoffme 11/9-59

Dec. 2, 1965

94

1/4 Corner to Sec. 32, T30-9W. & Sec. 5, T31-9W.
Found - Original Stone and 2 Original BT's., now Snags.
Scribe 2 Bearing Trees for this Corner:
Doug. Fir, 22 inches, S. 12° W. 34.7 ft. 1/4 S5 BT 473".
Doug. Fir, 22 inches, N. 25° E. 13.5 ft. 1/4 S32 BT".

F. J. LaFlamme
Georgia Pac.
C.S. File 55/23

Dec. 2, 1966

95

1/4 Corner to Sec. 32, T30-9W. & Sec. 5, T31-9W.
Found - Orig. 24" D. Fir, now Snag, S. 37° E. 17.8 ft., scribe visible.
LaFlamme's Trees, See renewal above #94.
24" D.Fir S. 10° E. 34.0 ft. mkd. 1/4 S5 BT. (Tagged all BT's
24" D.Fir N. 26° W. 13.5 ft. mkd. 1/4 S32 BT. (by LaFlamme, 1966)
Post at 1/4 Corner.
Set - Brass Cap at Cor. Mkd: County Surveyor's Office, 1967 T30S R9W
S 32 / S 5 R9W
T31S R9W

John M. Powell
Frank Jones & J. Brady
May 16, 1967
C.S. File No. 53/53

RE-RENEWED, SEE CORNER NO. #127