

Douglas County Surveyor's Record of
Government Corners Renewed

T. 30 S. T. S. R. 9 W. R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

John M.
Powell
& Crew
9/27/67
C.S. File
No.
53/53

Vernon "Ray" Tracy
Jack Heritage & V. Perron
August, 1968
C. S. File No. 53/67

John M. Powell
W. Penley & J. Heritage
July 11, 1970 C.S. File 53/53

1/4 Corner to Sections 3 and 2. 96
Found - 1" Iron Pipe 4' from edge of new road., See Ren. #36. 104
8" Cedar, now uproot, N. 23° W. 13.0 ft.
20" D.Fir, now burnt stump, S. 28° E. 66.6 ft., scribe visible, "S".
Set - Brass Cap at Cor. Mkd: County Surveyor's T 30 S R 9 W
Office, 1967 1/4 S 3 | S 2
New Bearing Objects: 30" Fir Stump N.34°W. 29.4 ft., drove iron spike
in top of stump.
28" Fir Stump N. 7° E. 32.0 ft., drove iron spike
in top of stump.
Note - This area was recently burned. No tree to scribe.
Corner lies on west edge of cat road.

MICROFILM TO HERE 10/67

Sec. Cor. to Secs. 25 & 36, T30-9W. & Secs. 30 & 31, T30-8W. 97
Found - Orig.15", now 28" Fir, alive, N.47°W. 24.4 ft., open, scribe visible. # 134
Orig.30", now 54" Fir, alive, S.1 1/2°W. 356.4 ft., open, scribe visible.
We do not find S.E. BT.
Orig.15", now 30" Pine, alive, N.25°E. 52.4 ft., open, scribe visible.
Set - Brass Cap at Cor.Mkd: County Surveyor's R T 30 S R
Office 9 S 25 | S 30 8
1968 W S 36 | S 31 W
New BT's: 9" D.Fir S. 52° E. 16.2 ft. mkd: T30S R8W S31 CS BT.
11" W.Oak N. 64° E. 34.2 ft. mkd.: T30S R8W S30 CS BT.
8" W.Oak N. 10° W. 30.0 ft. mkd: T30S R9W S25 CS BT.
8" D.Fir S. 82° W. 26.6 ft. mkd: T30S R9W S36 CS BT.
This corner lies on steep, southwest slope.

1/4 Corner to Sec. 36, T30-9W. and Sec. 31, T30-8W. 98
Found - Orig. 15", now 36" Fir, alive, N.52°W. 21.1 ft., open & shows "B 1/4",
bark scribe.
Find depression at approx. location of N.E. BT., Tree gone.
Set - Brass Cap at Cor. Mkd: County Surveyor;s R T 30 S R
Office, 1968 9W 1/4 S 36 | S 31 8W
New BT's: 7" Hemlock N. 36° E. 16.7 ft. mkd. "1/4 S31 CS BT".
8" Hemlock S. 6" W. 13.8 ft. mkd. "1/4 S36 CS BT".
This corner lies on moderate northeast slope.

8/15/68

Section Corner to Secs. 33 & 34, T30-9W. and 99
Secs. 4 & 3, T31-9W.
Found - 14", now 38" D.Fir, N.63 3/4°E. 22.5 ft. (Rec.25.1), shows good scar.
7", now 26" D.Fir, S.31 1/2°E. 38.9 ft., shows good scar.
6", now 14" D.Fir, N.84 1/2°W. 16.7 ft., opened for scribe "W".
20" Cedar, now snag, S.32°W. 19.4 ft. (Rec. S45W 16.5), burnt
face on tree, also "X".
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W S 33 | S 34
Office, 1970 T31S S 4 | S 3
New BT's: 15" D.Fir S.60 1/2° W. 32.5 ft. mkd: "T31S R9W S 4 CS BT".
Other Bearing Trees O. K.
This corner lies in bottom of N - S draw.

8/11/70

1/4 Corner to Sec. 34, T30-9W. & Sec. 3, T31-9W. 100
Found - No trace of Stone at 1/4 corner.
30", now 50" D.Fir, S.72°E. 17.8 ft., opened for scribe "1" "S".
17", now 28" D.Fir, N.44 1/2°W. 7.6 ft., opened for scribe, found burnt
face, parts of scribe & old axe work.
Good Call & distance to creek 72.0 ft. E., hits pretty good.
Old Camp nearby probably fire place.
Set - Brass Cap at Cor. Mkd: County Surveyor's T30S R9W 1/4 S 34
Office, 1970 T31S S 3
New BT: 26" W.Fir N. 9 1/2°W. 34.2 ft. mkd: "1/4 S34 CS BT".

8/11/70