

Douglas County Surveyor's Record of
Government Corners Renewed

T 30 T.S. R 9 R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 31881

112

1/4 Corner for Sec. 4,, and Sec. 33, T29-9
Found - An. orig. 18" D.Fir, now a 30" stump bears N.23°E.,
.20.5 ft.. We open and find good scribing "T".
An orig. 15" D.Fir, now a 36" stump, bears S.32°W.,
27.8 ft. (rec. S.32°W., 26.4 ft.) showing a good
scar and faint scribe marks on the bark above the
scar.

Set - At the corner point we set a 1"x30" I.P, with brass
COUNTY SURVEYORS T 29 S R
OFFICE S 33 9
1974 S 4 W
T 30 S

Gary Langlitz
P. Earle
cap
Office
11/6/74
C.S. 57/12

New BT's - A 12" Hemlock bears N.77 1/2°E., 16.3 ft. scribed
"1/4 S33 CS BT".
An 11" Port Orford cedar bears N.12°E., 14.2 ft.
scribed "1/4 S33 CS BT".
Compass declination setting: 20° East.

3/77 11/6/74 JAN 75

JAN 78

Section corner for 10, 11, 15 and 14.
Set - 1" x 30" pipe with 2 1/2" brass cap by proportional measurement.
BT's - 14" W. Fir bears S.10°W., 16.7 ft. scribed "T30S R9W S15 BT".
12" W. Fir bears S.71°20'W., 22.8 ft. scribed "T30S R9W S15 BT"
14" W. Fir bears N.3°55'W., 9.7 ft. scribed "T30S R9W S10 BT".
16" D. Fir bears N.86°E., 17.9 ft. scribed "T30S R9W S11 BT".

FDOK G Smither 10/2006 113 M151-57

William Ruppert
OLS #866
For: Charlie Hills
April/May 1978
M 71 - 5

1/4 Corner for Secs. 10 and 15.
Set - 1" x 30" Pipe with 2 1/2" brass cap by proportional measurement.
stamped T30S R9W 1/4 S10 S15 PLS 866 1978.
BT's - 9" D. Fir bears N.45°10'W., 22.7 ft. scribed "1/4 S10 BT"
21" Hemlock bears S.72°50'E., 30.9 ft. scribed "1/4 S15 BT".

#191 114

FDOK K Hoffine
10/2001 M138-79
(ALSO Metal Fence
Post W 0.8ft)

1/4 Corner for Secs. 19 and 20
Found - Identified corner from rock and 1 OBT as recorded govt. field notes.
New trees - 14" Hemlock, N.88 3/4°W., 53 lks. slope, 27°20'
26" Fir, N.21 3/4°E., 57 lks. slope, 24°10', scribed 1/4 S20 CS BT.

#171 115

H.L. Eppstein
Co. Surveyor
For: A.P. Sweet
June 6, 1930
C.S. 37/32

Section Corner for Secs. 34 and 35; and 3 & 2 of T.31-9
Set - Chisled "X" in rock
BT's - 12" Fir bears N.28°E., 43.2 ft. scribed T30S R9W S35 BT.
36" Cedar bears N.40°W., 28.2 ft. scribed T30S R9W S34 BT.
12" Hemlock bears S.16°E., 25.7 ft. scribed T30S R9W S2 BT.
20" Cedar bears S.56°W., 54.3 ft. scribed T30S R9W S3 BT.
(No original evidence found)

1/80

Romanso E. Ware
For: Roseburg
Lumber Co.
Jan. 1980
M 79 - 18

1/4 Corner for Secs. 35; and Sec. 2, T.31-9.
Set - 5/8" I.R. with aluminum cap.
BT's - 8" Hemlock bears S.22°W., 13.7 ft. scribed 1/4 S2 BT.
12" Fir bears N.6°E., 9.5 ft. scribed 1/4 S35 BT.

1/80

117

1/4 Corner for Secs. 27 and 34.
Found - Stone and 2 bearing trees per record.
Set - Rod and cap alongside.

1/80

118