

Douglas County Surveyor's Record of
Government Corners Renewed

T 30

T. S.

R 9

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

Ronald Geisler,
L.S. #1988
For: Champion Inter-
national Corp.
May-June 1984
M 97 - 9

1/4 Corner for Section 6; and Sec. 1 of T.30-10 135
Found - a 5/8" Iron rod set by O.L.S. #430 in 1963 in the correct
position. Ren. #30
Set - Replaced I.R. with an Alum. cap 2 1/2" on a 7/8" x 36" I.P. Cap
properly stamped and also with PLS 1988. Drove the Iron rod
alongside the iron pipe.
Found - 1963 BT, a 11" hemlock bears N.80°W., 54.6 ft. (Rec. 55.4 ft.)
with healed face.
New BT - 9" hemlock bears East, 26.1 ft. scribed 1/4 S6 BT.

CORNER REPORTS ONLY

136

Northeast Section Corner for Section 1 only of T.30-10
Found - 1979 BLM 3 1/2" brass cap on a 2 1/2" I.P. extends 1" above ground
Corner stone found alongside monument. See Ren. #28
6" Myrtle now down decayed and out of position. Blazed face
with BT tag visible. (date unknown)
19" D. fir now stump bears N.87 1/2°W., (Rec. S.87 1/2°W.) Healed
face 22.4 ft. (date unknown)
21" D. fir bears S.38°W., 34.3 ft. Healed face. (1963).

137

Northeast corner for Section 6 only.
Found - 1979 BLM 3 1/2" brass cap on a 1" I.P. set in drill hole in
orig. 32" x 32" x 18" stone. Ren. No. 29
Bearing object, rock 5 ft. dia. 4 ft. high bears N.68°E., 18.5 f
Marks visible (original)
Bearing object, rock, 3' x 2' x 1' above ground bears S.70°E.,
14.5 ft. (Rec. 13.2 ft.) Marks visible. (Original.)
20" Fir now stump bears S.52°E., 12.5 ft. Healed face. (1979)

138

Southwest Section corner for Section 31 of T.29-9
Found - 1979 BLM brass cap on a 2 1/2" I.P. extends 2" above ground.
Did not find corner stone. Ren. No. 27
48" fir snag (rotten bears N.55°W., 92.4 ft. (Orig.)
16" D. fir now stump bears N.73°E., 9.9 ft. Healed face.
(date unknown)
16" D. fir bears N.24°W., 19.5 ft. Healed face. (1963)
12" D. fir now stump bears N.29°E., 8.6 ft. Healed face. (1963)

139

Center 1/4 Corner for Section 13
Set - 5/8" x 44? iron rod with alum. cap marked C 1/4 LS 498.
New BTs - 15" Fir, S.59 1/2°W., 7.9 ft.
12" Cedar, N.4°W., 24.0 ft.

Howard Johnstone
For Roseburg Resources
June, 1988
M 106 - 51

3/4" I.P. bears N.13°41'11"W., 4.49 ft. ↑ B 21074
FD used on 2002 BLM survey
Pb 21073-4 M142-69 FO. OK BY RAMBO 7/03

1/4 Corner for Sections 12 and 13

140

CORNER REPORT ONLY

Found - 1958 County BCIP mkd. S12/13 Ren. #5
14" cedar, N.29°W., 39.6 ft. now stump.
20" oak, N.18°E., 83.8 ft. scribe visible (orig.)
36" laurel, S.78°E., 44.2 ft. Now down. Orig.
26" fir, S.74 1/2°E., 26.7 ft. Healed. Ren. #5

Howard Johnstone
For: Roseburg Resources
November, 1988
M 101 - 44

141

Center 1/4 Corner for Section 12 (Witness Corner)
Set - Witness Corner at base of rock bluff 5 ft. south of C 1/4.
5/8" x 30" iron rod and alum. cap marked WC 5' C 1/4 S 12.
Scribed: 10" cedar, N.56°E., 16.7 ft. "C 1/4 WC BT"
8" cedar S.11°E., 14.5 ft. "C 1/4 WC BT".

142

1/4 Corner for Sections 11 and 12
Set - 5/8" x 36" iron rod and alum. cap marked 1/4 S11/12 in mound
of stone.
Scribed: 6" oak, N.81°W., 29.5 ft. "1/4 S11 BT"
10" fir, S.84°E., 12.9 ft. "1/4 S12 BT"