

**Douglas County Surveyor's Record of  
Government Corners Renewed**

30 T. S. 9 R. W. W. M.

KORE-CHAPMAN CO., EUGENE, ORG. 21881

KEN HOFFINE, LS2291  
FOR: LONE ROCK TIMBER CO.  
APRIL 1995  
M 119-59

Douglas County Surveyors Office  
Randall Smith & Stephen Flause  
Sept., 18, 1997 - C.S. 64/78-4

Greg Lang  
7/5/2000  
C.S. File  
65/30-18

**164**

Line Tree originally bearing N.0°02'W., 1326.6 from the SWSC S28  
Found - GLO Line Tree was a 48" D.Fir w/2 blazes on the North & 2 blazes on the South side, bearing N.0°02'W., 1326.6' from the SWSC, NOW a 61" D.Fir snag with chard bark & faint chop marks on the North & 3 good blazes on the South side, bearing N.0°18'W., 1319.5' from the SWSC & 6.0' West of line between W 1/4 & SWSC.  
12" Hemlock bears S.36½°W. 17.0'. This is also R.Ware's BT for S1/16  
54" D.Fir bears East 42.1'. This is also R.Ware's BT for S1/16.  
S 1/16 corner bears S.30°E., 7.7'.

**165**

Line Tree originally bearing N.0°02'W., 759.0' from the SWSC S28  
Found - GLO line tree, was a 38" D.Fir with 2 blazes on the North and 2 blazes on the south side bearing N.0°02'W., 759.0 NOW a 39" D.Fir stump w/a chop mark on the North side & a faint blaze on the South side bearing N.0°10'W., 772.6' from the SWSC & 1.8' West of line between W ¼ & SWSC.  
Scribe- 37" D.Fir bears N.28°W., 24.0' we scribe BT & tag tree.

**166**

Line Tree originally bearing N.0°02'W., 2364.12' from the SESC  
Found - GLO line tree was a 36" D.Fir with 2 blazes on the North & 2 blazes on the South side bearing N.0°02'W., 2364.12' from the SESC NOW 46" D.Fir low stump with only 1 blaze remaining on the North side bearing N.0°07'W., 2365.8' from the SWSC & 4.3' east of line between E ¼ and SESC  
Scribe- 18" D.Fir, bears S.18°W., 17.3'. We scribe BT & tag tree.  
11" D. Fir, bears N.2°W., 20.25'. We scribe BT & tag tree.

**167**

¼ cor. Sec. 1 & 2  
Mon. Fd.- 2½" dia. Brass cap on a 1½" O.D. iron pipe protrudes 6" above ground BC/IP: plumb and firmly set.  
Accessories Fd. -  
24" now 22" dia. 4' high Cedar stump, with visible scribing "¼ S2 BT", Note: Bt has slide out of position now, bears N.4°W., 64' (rec. N.13°W., 66.7' ren. # 107).  
36" now 34" dia. 3' high rotted D.Fir stump, with scribing visible "¼ S1 BT", bears S.18°E., 94' (agrees with rec.) Ren. #107.  
New Accessories -  
6" D.Fir double blazed and scribed "¼ S2 CS BT", bears S.68°W., 5.7'  
15" D.fir double blazed and scribed "¼ S1 CS BT", bears S.59°E., 35'.  
8" D.Fir double blazed and scribed "¼ S2 CS BT", bears N.9°W., 12'.  
8" D.Fir double blazed and scribed "¼ S1 CS BT", bears S.15½°E., 24.5'.  
see previous Ren. # 107

**168**

1/4 Secs. 14 & 23 *FD OK G. Smith 10/2006 M151-57*

Found - 1"x30" IP set by Johnstone (1961) (REN. #20), existing BTs fd. per 1961 rec. are as follows:  
D.Fir stump S.66°W., 7.9 ft.  
17" D.Fir N.10°E., 93.5 ft. (now 21")

New - 11½" Hemlock bears S.66°E., 27.65' from IP - scribed "¼ S23 BT"  
12½" D.Fir bears S.55½°W., 70.55' from IP - scribed "¼ S23 BT"  
14" D.Fir bears N.69°W., 39.0' from IP - scribed "¼ S14 BT"  
21" D.Fir bears N.10¼°E., 92.6' from IP - scribed "¼ S14 BT" {measurement to previous accessory}

Note - Spikes were set in the side & bottom of BTs for dist. reference.  
Corner lies 763' west of ridge top & 50'± westerly of where a bench drops off toward a small creek to the West.