

**Douglas County Surveyor's Record of
Government Corners Renewed**

T 30 T.S. R9 R.W.W.M.

KORE-CHAPMAN CO., EUGENE, ORE. 97401

Greg Lang
7/6/2000
C.S. File
65/30-17

FOCUS 072002 BLM resource pg
21069-70 169

Cor. Secs. 13, 14, 23, & 24

Found - Brass cap, properly mkd. Existing BTs fd. per 1970
rec. {Ren #101}, are as follows:
D.Fir stump N.52°W., 38.4 ft.
23" Cedar N.77°E., 15.8 ft.
7" W.Fir S.15°W., 47.3 ft.
11" D.Fir N.44°W., 53.0 ft.
8" W.Fir S.75°E., 51.4 ft.

*FOOK
G. Smither
10/2006
M151-57*

OUR MEASUREMENTS TO PREVIOUS ACCESSORIES
17" W.Fir bears S.74½°E., 51.55 ft. from BC
14" W.Fir bears S.14½°W., 46.95' from BC
20½" D.Fir bears N.43½°W., 52.05' from BC
31½" Cedar bears N.76½°E., 15.4 ft. from BC

Note - Spikes were set in the side & bottom of BTs for
dist. reference.
Corner lies near the bottom of a small draw west of
Twelvemile Creek.

170

N 1/4 Cor. sec. 20

Found - 1964 County brass cap/iron pipe firmly set in
mound of stone per ren. #55
16" Fir snag cor. tree has been pushed out w/cat
bears S.80°W., 4.0 ft. & is falling over.
31" W.Fir N.58°E., 8.6 ft.
18" D.Fir S.46°W., 31.8 ft. is gone.
11" D.Fir S.24°W., 49.6 ft. is a rotted stump.

New BTs- 8" D.Fir S.11°E., 40.5 ft. to spike side
center scribe "X" at breast height & "BT"
at base with alum. tag.
22" W.Fir N.17°W., 31.7 ft. to spike side
center scribe T30 R9 ¼ S17 BT w/alum. tag
15" D.Fir N.86°W., 32.0 ft. to spike side
center scribe T30 R9 ¼ S17 BT w/alum. tag

Gary Smither
For: Moore Mill Co.
Jan 2001
M136-54

171

1/4 Cor. 19 & 20

No trace of orig. Proportioned between orig. line tree
& SW corner of Sec. 20.

Set - 5/8"x30" IR w/2" alum. cap mkd: T30S R9W
¼
S19 | S20
2001
LS 2485

*See narrative
on map
also*

10" D.Fir N.24°W., 14.5 ft. to spike side center
scribed ¼ S19 BT with alum. tag.
10" D.Fir N.69°E., 12.9 ft. to spike side center
scribed ¼ S20 BT with alum. tag.
8" D.Fir S.23°E., 21.0 ft. to spike side center
scribed ¼ S20 BT with alum. tag.
8" D.Fir S.12°W., 7.6 ft. to spike side center
scribed ¼ S19 BT with alum. tag.

172

Cor. Secs. 16, 17, 20, & 21

Found - 1964 county brass cap/iron pipe per ren. 53
stone is adjacent to corner.
39" Cedar S.37½°W., 19.1 ft. scribe vis. w/tag.
40" D.Fir snag N.55°W., 16.1 ft. w/healed face.
13" W.Fir S.80°E., 13.4 ft. is a rotted stump
w/healed face.
8" W.Fir N.54°E., 16.9 ft. has fallen down.
38" D.Fir snag S.28°E., 3.0 ft. w/scribe visible

New BTs- 7" D.Fir N.84°W., 31.1 ft. to spike side center
scribe "X" at breast height & "BT" at base
w/alum tag.
13" W.Fir N.17°E., 20.7 ft. to spike side center
scribe T30 R9 S16 BT w/alum. tag.