

Douglas County Surveyor's Record of
Government Corners Renewed

T 30S T.S. R9W R.W.W.M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

See BLM Resource U. 54
Cor. Secs. 1, 2, 11, & 12 Pgs 20795-6 178

Tony Hostetter

For: Roseburg
Resources Co.

Found - 1958 DCSSO brass cap
46" DF stump w/vis. scribes bears N.86°E. 18.0'
23" Cedar w/healed face bears N.37½°W., 184.7'
9" Pine w/visible scribes bears N.80¾°E., 7.0'
5" DF with visible scribes bears S.36¾°E. 29.5'
11" DF with visible scribes bears S.32°W., 8.5'
11" Pine w/visible scribes bears N.14¾°W. 15.0'

FD OK By T. Hostetter ↑
1/2007 M 152-28 ↓

May/July 2003

M142-69

1/4 Cor. Secs. 11 & 12 179
Set - 5/8" x 30" rebar w/ 2½" alum. cap.
Scribed - "¼ S12 BT" on an 18" DF bears N.70°E., 38.5 ft.
"¼ S12 BT" on a 13" DF bears S.34°E., 20.0 ft.
"¼ S11 BT" on an 11" DF bears S.4°W., 15.5 ft.
"¼ S11 BT" on an 11" DF bears S.77°W., 37.8 ft.
Note - Per narrative - some corners established on M101-44 were set incorrect. The W¼ S12 monument was pulled & cap removed - per Roseburg Resources request. (Ren. #142)

Center 1/4 Cor. Sec. 12 180

Set 2 WC corners
1st WC corner North 122 ft. of true corner:
Set - 5/8" x 30" rebar w/ 2½" alum. cap.
Scribed - "WC BT" on 12" DF, bears N.4°E., 16.1 ft.
"WC BT" on 7" DF, bears N.25°W., 17.8 ft.
2nd WC corner West 200 ft. of true corner:
Set - 5/8" x 30" rebar w/ 2½" alum. cap.
Scribed - "WC BT" on 16" DF, bears S.73°W., 10.6 ft.
"WC BT" on 11" DF, bears S.12°W., 8.5 ft.

FD OK
Carl Swenden
11/2007
M154-67

Gary Smither
Moore Mill & Lmbr
Rsbg Resources Co.
10/2006

M151-57

1/4 Cor. Secs. 14 & 15 181
Found - County brass cap with steel post alongside
Renew no. 31, M71-5
BTs - 12" hemlock snag S.25°E., 11.9 ft. with
healed face
Co. 15" D.Fir S.51°W., 34.5 ft. (Rec W.Fir) with
healed face & aluminum tag
New BTs - 23" D.Fir S.4°W., 39.4 ft. To spike side
center & at scribe T30R9 ¼15BT
11" D.Fir S.22°E., 24 7 ft to spike side
center & at scribe T30R9 ¼14BT
6 D.Fir N.11°E., 46.3 ft. to spike side
center & at scribe T30R9 ¼14BT

Center ¼ Cor. Sec. 14 182
Set - 2" Alum. cap on 5/8"x30" I.R. mkd: T30S R9W
C¼ S14 2006 2485
BTs - 8" Hemlock West 2.6 ft. to spike side center
Scribe T30R9 C¼ S14 BT & aluminum tag
9" Hemlock N.64°E. 7.7 ft to spike side center
Scribe T30R9 C¼ S14 BT & aluminum tag
11" D.Fir S.63°W., 8.2 ft to spike side center
Scribe T30R9 C¼ S14 BT & aluminum tag
6" D.Fir S11°W., 8.5 ft. to spike side center
Scribe T30R9 C¼ S14 BT & aluminum tag