

Douglas County Surveyor's Record of  
Government Corners Renewed

30

T. S.

9w

R. W. W. M.

KOKE-CHAPMAN CO., EUGENE, ORE. 21881

1/4 Cor. Secs. 11 & 14

FD OK D EDWARDS  
2/2008 CS 65/64-2  
183

Found - 1958 county brass cap. Renew no. 66 and M71-5  
BTs - 24" D.Fir stump S.44°E., 18.7 ft. with healed face  
& alum. tag.  
17" D.Fir N.82°W., 35.7 ft W/healed face & alum tag  
New BTs- 19" D.Fir S.33°E., 32.0 ft. to spike side center &  
alum. tag, scribe T30R9 ¼S14BT  
8" D.Fir N.13°E., 9.4 ft. to spike side center &  
alum tag, scribe T30R9 ¼S14BT  
8 D.Fir N.10°W., 7.8 ft. to spike side center &  
alum. tag. scribe T30R9 ¼S14BT

1/4 Cor. Secs. 13 & 14

184

Found - 1964 county brass cap - Renew #52 & M106-51 BLM notes  
pg 21071  
BTs - 12" D.Fir N.20°W., 20.3 ft. W/healed face & alum tag  
26" Cedar N.73°E., 116.0 ft. W/healed face & alum tag  
New BTs- 7" D.Fir S.22°W., 15.8 ft. To spike side center & alum  
tag, scribe T30R9 ¼S14BT  
12" D.Fir S.70°W., 17.2 ft. to spike side center &  
alum tag, scribe T30R9 ¼S14BT

Gary  
Gary Smither  
For: Moore Mill  
& Lumber Co.  
and  
Roseburg  
Resources Co.

10/2006  
M151-57

1/4 Cor. Secs. 2 & 11

185

Found - Brass cap & BTs as described by Douglas Co.  
Surveyor in 1958 (except Cedar at N.46°W., is  
now a stump  
New - 16" Cedar, scribed "S2 ¼ BT", bears N.11°E., 6.6  
ft. to spike.  
22" Fir scribed "S2 ¼ BT", bears N.56°E., 22.5 ft.  
to spike.  
BT measurements are to the head of a 6" spike  
placed in the root collar below scribed face.

Tony Hostetter

Jan. 2007

M152-28

Center 1/4 Cor. Sec. 26

186

Set - 5/8"x30" steel rebar w/red plastic cap mkd: "D.A.  
EDWARDS - LS 2339"  
12" dia. fir bears N.44°E., 13.09 ft.  
9" dia., fir bears S.81°E., 8.1 ft.  
7" dia., fir bears S.72°W., 11.69 ft.  
9" dia., fir bears N.73½°W., 13.02 ft.

David Edwards

1/4 Cor. Secs. ~~2 & 11~~ 23 & 24

187

BLM administrative surveys are of record for the south & west  
lines of sec. 26. From evidence on the ground it is clear that  
BLM also surveyed the North line. Boundary tags are found both  
East & West from the 3/4" IP at the north ¼ corner. Said pipe  
bears S.9°54'22"E., 2.274 from my computed mid-point. I accept  
the IP as the north ¼ corner because the position is within  
tolerances for the era in which it was set (probably 1981)  
Found - 3/4" IP  
11" dia., Fir bears S.11°E., 10.38 ft.  
15" dia., hemlock bears N.44°W., 3.35 ft.  
Set - 6 ft. steel posts 2 ft. west & 2 ft. east.

Feb. 2007

M152-35

Line tree between secs. 26 & 27 (15.58 chs N of ¼ cor) 188

Found - Orig. line tree, now 43" dia., 30'± mkd: "D.A.  
EDWARDS - LS 2339"  
5" dia., fir bears N.7½°W., 18.5 ft. scribed AP 27 BT  
5" dia., fir bears S.37°W., 16.8 ft. scribed AP 27 BT  
No trees available in sec. 26