

**Douglas County Surveyor's Record of
Government Corners Renewed**

30

T.S.

9

R.W.W.M.

ROSE-CHAPMAN CO., EUGENE, ORG. 21881

189

1/4 Cor. Secs. 15 & 16

Found - BC up 1.3' above ground Ren. #77
60" Cedar BT stump, N.70°E., 20.0' (19.14')
snag down.
Charred Oak BT stump, N.19°W., 43.4' per rec.
not fd.
20" Live Oak BT, S.45°W., 7.3' **not fd.**
20" D.Fir BT, S.7°W., (S.15°E.) 24.3', scar
vis. high up, Lone Rock tag.
New - 18" W.Fir BT, S.53°W. 33.2' scribed "E ¼ S16
BT" tag.
Large boulder w/a 2 inch "+" chiseled on south
face. Boulder measures 5'x2' protruding
from ground, bears N.7°W., 38.4'

Carl Sweeden
For: Roseburg
Resources Co.
11/2007
M154-67

190

1/4 Cor. Secs. 15 & 22

Found - Alum cap up 0.3' above ground Ren. #121
20" Cedar BT stump, N.70°W., 23.0' vis. scribe
& tag, 6' tall.
14" D.Fir BT stump, S.80°E., 9.2', scar & tag,
5' tall.
New - 2½" alum cap up 0.2' above ground, S.74°W.,
(magnetic) S.68°29'58"W., 27.65' per tie.
2½" alum cap up 0.2' above ground, S.7°W.,
(magnetic) S.3°22'49"W., 25.09' per tie.
Both RMs stamped: ROSEBURG RESOURCES COMPANY

" "

" "

REF MON
2007
T30S R9W
1 SEC 15
SEC 22 4
LS 2752

Each rod & cap is marked with a painted
metal post w/tag.
Magnetic declination 19.5° East.

191

1/4 Cor. Secs. 10 & 15

Found - Brass cap up 0.7' above ground. Ren. #114
15" D.Fir BT, N.45°10'W., 22.7', scar & tag.
30" Hemlock BT, S.72°50'E., 30.9' dbl scar & tag
New - 12" W.Fir BT, S.37°W., 22.25', scribed "N ¼ S15
BT" & tag.
5" D.Fir BT, N.35°E., 16.1', dbl scribed "S ¼ S10
BT" & tag.
Both trees with 16 penny nail in bowel.

" "

192

Tony Hostetter - for: Roseburg Resources - March 2008 - M155-26

Center 1/4 Cor. Sec. 18

Found - 1974 Brass cap set by Shaner (Ren #110)
14" Fir, Shaner BT face evident, bears N.48°E.
35.5 ft.
New BTs- 14" Madrone, scribed "S18 ¼ BT" bears
S.36°31'W., to spike.
18" Maple, scribed "S18 ¼ BT" bears N.0°27'W.,
24.2 ft to spike.
8" Madrone, scribed "S18 ¼ BT: bears
N.0°27'W., 24.2 ft. to spike.