

Douglas County Surveyor's Record of
Government Corners Renewed

31 T. S. 1 R. W. W. M.

KONE-CHAPMAN CO., EUGENE, ORE. 97106

S. E. Corner Section 32.
as determined by O. B. T's:
30" W. Fir bears N. 88° W. 37.6 ft. O.B.T., fd. scribe &
remarked S32 B.T.
16" W. Fir bears S. 86° W. 39.6 ft. O.B.T., fd. scribe &
remarked S32 B.T.
24" Fir Stump (logged) N. 30° E. 24.8 ft. O.B.T., fd. scribe &
remarked S32 B.T.
At Corner Point Set $\frac{1}{4}$ " x $\frac{1}{4}$ " Iron Pipe from which:
5" Fir bears S. 39° E. 15.5 ft. dist. mkd. S 5 RLW B.T.
5" Fir bears N. 41° W. 20.7 ft. dist. mkd. S32 B.T.
A fence bears North and also West from Corner.
Road bears North 355.0 ft.

8

John H. Markham, Jr.
For Stomar Lbr. Co.
Jan. 18, 1961
C. S. File No. 51/112

Corner to Sections 31 and 32 only.
Found - Brass Cap at Corner.
Orig. 40", now 44" Cedar N. 1° W., not N. 5° W., 13.2 ft.
Orig. N. 38° E. 44.2 ft. Cedar BT., now down, shows scribing.
New BT's: Rescribed Orig., now 48" Cedar N. 1° W. 15.5 ft. scribed
S31 T31S RLW CS BT.
16" W. Fir bears N. 38° E. 54.5 ft. scribed S32 T31S RLW CS

9

James W.
Byron & Crew
March 27,
1963
BT.C.S. File
No. 53/15

South $\frac{1}{4}$ Corner to Section 32 only, T31 - 1 W.
Found - Snag of one BT in place, other BT. down & out of place.
 $\frac{1}{2}$ " I. Pipe pulled out & laying at approx. corner.
10", now 12" W. Fir Snag N. 10° W. 16.5 ft. shows scribe.
This snag 6 ft. tall. Recorded Ren. #5.
Set - Brass Cap at Cor. Mkd: County Surveyor's T31S RLW $\frac{1}{4}$ S 32
T32S only
New BT's:
9" W. Fir N. 78° E. 54.9 ft. Mkd: $\frac{1}{4}$ S32 CS BT.
12" D. Fir N. 48° W. 58.0 ft. Mkd: $\frac{1}{4}$ S32 CS BT.
Note - This corner lies 165 ft. east of the C. C. of Sections
5 and 6, of T. 32S., R. 1 W.

10

Vernon "Ray" Tracy
Mike Darby & J Barnett
December 15, 1964
C. S. File No. 53/15

Closing Corner Sections 5 & 6, T32-1W.
Found - Corner Stone Mound & BT's. as follows: (Ren. #9.-T32-1)
8" Maple S. 1° 40' W. 106.9 ft. Mkd: S5 3683 BT.
5" W. Oak North 55.6 ft. Mkd: "3683 BT"
Set - Iron Pipe with Brass Cap at Cor. Mkd: County Surveyor's
T32S RLW C.C. S 6/3/5 Office, 1964
Do not mark new BT's. as none are close.
This corner lies on small bench between two small creeks.

11

$\frac{1}{4}$ Corner to Sec. 6, T31-1W. & Sec. 31, T30-1W.
Found - 6" Cedar Corner Tree, down.
12" Fir, now snag, S. 35° W. 5.9 ft., opened for scribing "B".
12" Fir, now stump, N. 75° E. 9.9 ft., burnt off at ground.
Set - Brass Cap at Cor. Mkd: County Surveyor's
Office 1966 $\frac{1}{4}$ S 31 RLW
S 6
T 31 S
New BT's:
5" Fir N. 32 $\frac{1}{2}$ ° E. 13.4 ft. scribed $\frac{1}{4}$ S 31 CS BT.
4" Fir S. 87° E. 48.8 ft. scribed $\frac{1}{4}$ CS BT.
Logging Road bears West 100.0 ft. - No larger trees available.
June 6, 1966

12

John M. Powell
Frank Jones & Joe Brady
June 1966
C. S. File 53/15

Sec. Cor. to Secs. 5 & 6, T31-1W. & Secs. 31 & 32, T30-1W.
Found - 10" Fir, now 11", S. 35° W. 9.2 ft., opened for scribe "6".
6" Fir, now stump, S. 28° E. 14.5 ft.
18" Fir, now 27", N. 20° W. 15.2 ft. scribed S31 BT scar.
24" Fir, now stump, N. 2° E. 21.0 ft.
Set - Brass Cap at Cor. Mkd: County Surveyor's
Office, 1966 RLW T30S S 31 | S 32
T31S S 6 | S 5
New BT's: 11" D. Fir N. 80° E. 40.8 ft. scribed T30S RLW S32 CS BT.
17" D. Fir S. 52° E. 51.3 ft. scribed T31S RLW S 5 CS BT.
26" D. Fir S. 72° W. 21.2 ft. scribed T31S RLW S6 CS BT.
June 7, 1966

13

John M. Powell
Frank Jones & Joe Brady
June 1966
C. S. File 53/15